



FOUR-QUADRANT TRIAC, ENHANCED NOISE IMMUNITY


DESCRIPTION

The UTC **UOT406** is a Four-quadrant triac, it uses UTC's advanced technology to provide customers with direct interfacing to low power gate drive circuits and sensitive gate, etc.


The UTC **UOT406** is suitable for Low power AC fan speed controllers, Low power motor control and Home appliances, etc.

FEATURES

- * $V_{DRM} \leq 600V$, $I_{GT} \leq 3mA$, $I_{GT} \leq 5mA$ (T2-G+)
- $I_{TSM} \leq 12.5A$ (t=20ms), $I_{TSM} \leq 13.8A$ (t=16.7ms), $I_{T(RMS)} \leq 1A$
- * Direct interfacing to low power gate drive circuits
- * Sensitive gate



SYMBOL




ORDERING INFORMATION

Ordering Number	Package	Pin Assignment			Packing
		1	2	3	
UOT406G-x-AA3-R	SOT-223	MT1	MT2	G	Tape Reel

Note: Pin Assignment: MT1: MT1 MT2: MT2 G: Gate

<p>UOT406G-AA3-R</p> <p>(1)Packing Type (2)Package Type (3)Green Package</p>	<p>(1) R: Tape Reel (2) AA3: SOT-223 (3) G: Halogen Free and Lead Free</p>
--	--

MARKING



■ ABSOLUTE MAXIMUM RATINGS

PARAMETER		SYMBOL	RATINGS	UNIT	
Repetitive Peak Off-State Voltage		V_{DRM}	600	V	
Repetitive Peak Reverse Voltage		V_{RRM}	600	V	
RMS On-State Current	full sine wave, $T_{sp} \leq 103^{\circ}C$	$I_{T(RMS)}$	1	A	
Non-Repetitive Peak On-State Current	full sine wave, $T_J \leq 25^{\circ}C$ prior to surge	I_{TSM}	$t=20ms$	12.5	A
			$t=16.7ms$	13.8	A
I^2t for Fusing	$t_p=10ms$	I^2t	1.28	A^2s	
Rate of Rise of On-State Current	$I_{TM}=1A, I_G=20mA, di_G/dt=0.2A/\mu s$	di_T/dt	T2+G+	50	$A/\mu s$
			T2+G-	50	$A/\mu s$
			T2-G-	50	$A/\mu s$
			T2-G+	10	$A/\mu s$
Peak Gate Current		I_{GM}	1	A	
Peak Gate Power		P_{GM}	2	W	
Average Gate Power	Over any 20ms period	$P_{G(AV)}$	0.1	W	
Storage Temperature		T_{STG}	-40 ~ +150	$^{\circ}C$	
Junction Temperature		T_J	125	$^{\circ}C$	

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL RESISTANCES

PARAMETER		SYMBOL	MIN	TYP	MAX	UNIT
Junction to Case		θ_{JC}			15	K/W
Junction to Ambient	For minimum footprint	θ_{JA}		156		K/W
	For pad area			70		K/W

■ ELECTRICAL CHARACTERISTICS ($T_J=25^{\circ}C$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Gate Trigger Current	I_{GT}	$V_D=12V, I_T=0.1A$	T2+G+		3	mA
			T2+G-		3	mA
			T2-G-		3	mA
			T2-G+		5	mA
Gate Trigger Voltage	V_{GT}	$V_D=12V, I_T=0.1A$			1.3	V
		$V_D=V_{DRM}, I_T=0.1A, T_J=125^{\circ}C$	0.2			V
Holding Current	I_H	$V_D=12V, I_G=0.1A$			7	mA
Latching Current	I_L	$V_D=12V, I_G=0.1A$	T2+G+		7	mA
			T2+G-		20	mA
			T2-G-		7	mA
			T2-G+		7	mA
On-State Voltage	V_T	$I_T=1A$		1.3	1.6	V
Off-State Current	I_D	$V_D=V_{DRM(max)}, T_J=125^{\circ}C$			0.5	mA
Rate of Rise of Off-State Voltage	dV_D/dt	$V_{DM}=0.67V_{DRM(max)}, T_J=110^{\circ}C$, exponential waveform, gate open circuit	10			$V/\mu s$
Rate of Change of Commutating Voltage	dV_{com}/dt	$V_{DM}=400V, T_J=110^{\circ}C, I_{TM}=1A$, $di_{com}/dt=0.44A/ms$	0.5			$V/\mu s$

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.