



UP9971

Power MOSFET

5A, 60V N-CHANNEL POWER MOSFET



■ DESCRIPTION

The UTC **UP9971** uses UTC's advanced technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with low gate voltages. This device is suitable for being used as a load switch or in PWM applications.

■ FEATURES

- * $R_{DS(ON)} < 60 \text{ m}\Omega @ V_{GS}=10\text{V}, I_D=5\text{A}$
- * $R_{DS(ON)} < 72 \text{ m}\Omega @ V_{GS}=4.5\text{V}, I_D=2.5\text{A}$
- * Ultra low gate charge (typical 32.5 nC)
- * Low reverse transfer Capacitance (C_{RSS} = typical 109 pF)
- * Fast switching capability
- * Avalanche energy Specified
- * Improved dv/dt capability, high ruggedness

■ SYMBOL




■ ORDERING INFORMATION

Ordering Number		Package	Pin Assignment								Packing
Lead Free	Halogen Free		1	2	3	4	5	6	7	8	
UP9971L-D08-T	UP9971G-D08-T	DIP-8	S	G	S	G	D	D	D	D	Tube
-	UP9971G-S08-R	SOP-8	S	G	S	G	D	D	D	D	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

<p>UP9971L-D08-T</p> <p>(1) Packing Type</p> <p>(2) Package Type</p> <p>(3) Green Package</p>	<p>(1) R: Tape Reel, T: Tube</p> <p>(2) D08: DIP-8, S08: SOP-8</p> <p>(3) L: Lead Free, G: Halogen Free and Lead Free</p>
---	---

■ MARKING



■ ABSOLUTE MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	RATINGS	UNIT
Drain-Source Voltage	V_{DSS}	60	V
Gate-Source Voltage	V_{GSS}	± 25	V
Continuous Drain Current ($V_{GS}=10\text{V}$)	I_D	5	A
Pulsed Drain Current (Note 2,3)	SOP-8	30	A
	DIP-8	20	A
Power Dissipation	P_D	2	W
Junction Temperature	T_J	+150	$^{\circ}\text{C}$
Operating Temperature	T_{OPR}	-55 ~ +150	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-55 ~ +150	$^{\circ}\text{C}$

Note: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Pulse width limited by $T_{J(MAX)}$

3. Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$

■ THERMAL DATA





PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	θ_{JA}	62.5	$^{\circ}\text{C/W}$

■ ELECTRICAL CHARACTERISTICS ($T_J=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT	
OFF CHARACTERISTICS							
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0\text{V}, I_D=250\mu\text{A}$	60			V	
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=60\text{V}, V_{GS}=0\text{V}$			1	μA	
Gate-Body Leakage Current	I_{GSS}	$V_{GS}=\pm 25\text{V}$			± 100	nA	
Breakdown Voltage Temperature Coefficient	$\Delta BV_{DSS}/\Delta T_J$	Reference to $25^{\circ}\text{C}, I_D=1\text{mA}$		0.06		$\text{V}/^{\circ}\text{C}$	
ON CHARACTERISTICS							
Gate Threshold Voltage	$V_{GS(TH)}$	$V_{DS}=V_{GS}, I_D=250\mu\text{A}$	1.5		3	V	
Static Drain-Source On-Resistance (Note)	$R_{DS(ON)}$	$V_{GS}=10\text{V}, I_D=5\text{A}$			60	$\text{m}\Omega$	
		$V_{GS}=4.5\text{V}, I_D=2.5\text{A}$			72		
Forward Transconductance (Note)	SOP-8	$V_{DS}=10\text{V}, I_D=5\text{A}$		16		S	
	DIP-8			7		S	
DYNAMIC PARAMETERS							
Input Capacitance	SOP-8	$V_{DS}=25\text{V}, V_{GS}=0\text{V}, f=1.0\text{MHz}$		1658		pF	
	DIP-8			1560		pF	
Output Capacitance	C_{OSS}			156		pF	
Reverse Transfer Capacitance	SOP-8		C_{RSS}		109		pF
	DIP-8				110		pF
SWITCHING PARAMETERS							
Total Gate Charge (Note)	Q_G	$V_{DS}=48\text{V}, V_{GS}=10\text{V}, I_D=5\text{A}$		32.5		nC	
Gate Source Charge	Q_{GS}			4.9		nC	
Gate Drain Charge	Q_{GD}			8.8		nC	
Turn-ON Delay Time (Note)	$t_{D(ON)}$	$V_{GS}=10\text{V}, V_{DS}=30\text{V}, R_D=6\Omega, R_G=3.3\Omega, I_D=5\text{A}$		9.6		ns	
Turn-ON Rise Time	t_R			10		ns	
Turn-OFF Delay Time	$t_{D(OFF)}$			30		ns	
Turn-OFF Fall-Time	t_F			5.5		ns	
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS							
Diode Forward Voltage (Note)	V_{SD}	$I_S=1.6\text{A}, V_{GS}=0\text{V}$			1.2	V	
Body Diode Reverse Recovery Time	t_{rr}	$I_S=5\text{A}, V_{GS}=0\text{V}, di/dt=100\text{A}/\mu\text{s}$		29.2		ns	
Body Diode Reverse Recovery Charge	Q_{RR}			48		nC	

Note: Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$

■ TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.