


**4-BIT SINGLE CHIP MICROCOMPUTER**

**DESCRIPTION** The μPD550L is a μCOM-45 4-bit single chip microcomputer with high voltage outputs, and low power consumption. The outputs can be pulled to -35V for direct interfacing to vacuum fluorescent displays. The μPD550L is manufactured with a low-power-consumption PMOS process, allowing use of a -8V, low current power supply. The μPD550L provides all of the hardware features of the μCOM-45 family, except that it has a 640 x 8 bit ROM to reduce device cost. The μPD550L executes all 58 instructions of the μCOM-45 instruction set.

**PIN CONFIGURATION**



**PIN NAMES**

PA <sub>0</sub> -PA <sub>3</sub>	Input Port A
PC <sub>0</sub> -PC <sub>3</sub>	Input/Output Port C
PD <sub>0</sub> -PD <sub>3</sub>	Input/Output Port D
PE <sub>0</sub> -PE <sub>3</sub>	Output Port E
PF <sub>0</sub> -PF <sub>3</sub>	Output Port F
PG <sub>0</sub>	Output Port G
CL <sub>0</sub> -CL <sub>1</sub>	External Clock Signals
INT	Interrupt Input
RESET	Reset
VGG	Power Supply Negative
VSS	Power Supply Positive
TEST	Factory Test Pin (Connect to VSS)

<b>ABSOLUTE MAXIMUM RATINGS*</b>	Operating Temperature . . . . .	-10°C to +70°C
	Storage Temperature . . . . .	-40°C to +125°C
	Supply Voltage . . . . .	-15 to +0.3 Volts
	Input Voltages (Port A, INT, RESET) . . . . .	-15 to +0.3 Volts
	(Ports C, D) . . . . .	-40 to +0.3 Volts
	Output Voltages . . . . .	-40 to +0.3 Volts
	Output Current (Ports C, D, each bit) . . . . .	-4 mA
	(Ports E, F, G, each bit) . . . . .	-15 mA
	(Total, all ports) . . . . .	-60 mA

COMMENT: Stress above those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

\*T<sub>a</sub> = 25°C

# μ PD550L

$T_a = -10^\circ\text{C}$  to  $+70^\circ\text{C}$ ;  $V_{GG} = -8.0\text{V} \pm 10\%$

PARAMETER	SYMBOL	LIMITS			UNIT	TEST CONDITIONS
		MIN	TYP	MAX		
Input Voltage High	$V_{IH}$	0		-1.6	V	Ports A, C, D, $\overline{\text{INT}}$ , RESET
Input Voltage Low	$V_{IL1}$	-4.5		$V_{GG}$	V	Ports A, $\overline{\text{INT}}$ , RESET
	$V_{IL2}$	-4.5		-35	V	Ports C, D
Clock Voltage High	$V_{\phi H}$	0		-0.6	V	CLG Input, External Clock
Clock Voltage Low	$V_{\phi L}$	-5.0		$V_{GG}$	V	CLG Input, External Clock
Input Leakage Current High	$I_{LIH}$			+10	$\mu\text{A}$	Ports A, C, D, $\overline{\text{INT}}$ , RESET $V_I = -1\text{V}$
Input Leakage Current Low	$I_{LIL1}$			-10	$\mu\text{A}$	Ports A, C, D, $\overline{\text{INT}}$ , RESET $V_I = -9\text{V}$
	$I_{LIL2}$			-30	$\mu\text{A}$	Ports C, D, $V_I = -35\text{V}$
Clock Input Leakage Current High	$I_{L\phi H}$			+200	$\mu\text{A}$	CLG Input, $V_{\phi H} = 0\text{V}$
Clock Input Leakage Current Low	$I_{L\phi L}$			-200	$\mu\text{A}$	CLG Input, $V_{\phi L} = -9\text{V}$
Output Voltage High	$V_{OH1}$			-1.0	V	Ports C, D, $I_{OH} = -2\text{mA}$
	$V_{OH2}$			-2.5	V	Ports E, F, G, $I_{OH} = -10\text{mA}$
Output Leakage Current Low	$I_{LOL1}$			-10	$\mu\text{A}$	Ports C through G, $V_O = -9\text{V}$
	$I_{LOL2}$			-30	$\mu\text{A}$	Ports C through G, $V_O = -35\text{V}$
Supply Current	$I_{GG}$			-12 -24	mA	

## DC CHARACTERISTICS

$T_a = 25^\circ\text{C}$


PARAMETER	SYMBOL	LIMITS			UNIT	TEST CONDITIONS
		MIN	TYP	MAX		
Input Capacitance	$C_I$			15	pF	f = 1 MHz
Output Capacitance	$C_O$			15	pF	
Input/Output Capacitance	$C_{IO}$			15	pF	

## CAPACITANCE

$T_a = -10^\circ\text{C}$  to  $+70^\circ\text{C}$ ;  $V_{GG} = -8.0\text{V} \pm 10\%$

PARAMETER	SYMBOL	LIMITS			UNIT	TEST CONDITIONS
		MIN	TYP	MAX		
Oscillator Frequency	f	100		180	KHz	
Rise and Fall Times	$t_r, t_f$	0		0.3	$\mu\text{s}$	External Clock
Clock Pulse Width High	$t_{\phi W_H}$	2.0		8.0	$\mu\text{s}$	
Clock Pulse Width Low	$t_{\phi W_L}$	2.0		8.0	$\mu\text{s}$	

## AC CHARACTERISTICS



## CLOCK WAVEFORM