

## L, S-BAND SINGLE CONTROL SPDT SWITCH

### DESCRIPTION

The  $\mu$ PG2160T5K is a GaAs MMIC for L, S-band SPDT (Single Pole Double Throw) switch which was developed for mobile phone and other L, S-band applications.

This device can operate frequency from 0.5 to 3.0 GHz, with low insertion loss and high isolation.

This device is housed in a 6-pin plastic TSSON (Thin Shrink Small Out-line Non-leaded) package, and is suitable for high-density surface mounting.

### FEATURES

- Supply voltage :  $V_{DD} = 2.4$  to  $2.8$  V (2.6 V TYP.)
- Switch control voltage :  $V_{cont(H)} = 2.4$  to  $V_{DD}$  (2.6 V TYP.)  
:  $V_{cont(L)} = -0.2$  to  $0.2$  V (0 V TYP.)
- Low insertion loss :  $L_{ins1} = 0.30$  dB TYP. @  $f = 0.5$  to  $1.0$  GHz,  $V_{DD} = 2.6$  V,  $V_{cont(H)} = 2.6$  V,  $V_{cont(L)} = 0$  V  
:  $L_{ins2} = 0.35$  dB TYP. @  $f = 1.0$  to  $2.0$  GHz,  $V_{DD} = 2.6$  V,  $V_{cont(H)} = 2.6$  V,  $V_{cont(L)} = 0$  V  
:  $L_{ins3} = 0.40$  dB TYP. @  $f = 2.0$  to  $2.5$  GHz,  $V_{DD} = 2.6$  V,  $V_{cont(H)} = 2.6$  V,  $V_{cont(L)} = 0$  V  
:  $L_{ins4} = 0.50$  dB TYP. @  $f = 2.5$  to  $3.0$  GHz,  $V_{DD} = 2.6$  V,  $V_{cont(H)} = 2.6$  V,  $V_{cont(L)} = 0$  V
- High isolation :  $ISL1 = 25$  dB TYP. @  $f = 0.5$  to  $1.0$  GHz,  $V_{DD} = 2.6$  V,  $V_{cont(H)} = 2.6$  V,  $V_{cont(L)} = 0$  V  
:  $ISL2 = 18$  dB TYP. @  $f = 1.0$  to  $2.0$  GHz,  $V_{DD} = 2.6$  V,  $V_{cont(H)} = 2.6$  V,  $V_{cont(L)} = 0$  V  
:  $ISL3 = 17$  dB TYP. @  $f = 2.0$  to  $2.5$  GHz,  $V_{DD} = 2.6$  V,  $V_{cont(H)} = 2.6$  V,  $V_{cont(L)} = 0$  V  
:  $ISL4 = 13$  dB TYP. @  $f = 2.5$  to  $3.0$  GHz,  $V_{DD} = 2.6$  V,  $V_{cont(H)} = 2.6$  V,  $V_{cont(L)} = 0$  V
- Handling power :  $P_{in(0.1\text{ dB})} = +21.0$  dBm TYP. @  $f = 2.0/2.5$  GHz,  $V_{DD} = 2.6$  V,  $V_{cont(H)} = 2.6$  V,  $V_{cont(L)} = 0$  V
- High-density surface mounting : 6-pin plastic TSSON package ( $1.0 \times 1.0 \times 0.37$  mm)

### APPLICATIONS

- L, S-band digital cellular or cordless telephone
- W-LAN, WLL and Bluetooth™ etc.

### ORDERING INFORMATION

| Part Number        | Order Number         | Package  | Marking | Supplying Form   |
|--------------------|----------------------|--|---------|--|
| $\mu$ PG2160T5K-E2 | $\mu$ PG2160T5K-E2-A | 6-pin plastic TSSON<br>(Pb-Free) <sup>Note</sup> | G4      | <ul style="list-style-type: none"> <li>• Embossed tape 8 mm wide</li> <li>• Pin 1, 6 face the perforation side of the tape</li> <li>• Qty 5 kpcs/reel</li> </ul> |


**Note** With regards to terminal solder (the solder contains lead) plated products (conventionally plated), contact your nearby sales office.

**Remark** To order evaluation samples, contact your nearby sales office.  
Part number for sample order:  $\mu$ PG2160T5K-A

**Caution** Observe precautions when handling because these devices are sensitive to electrostatic discharge.

The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version.

**PIN CONNECTIONS AND INTERNAL BLOCK DIAGRAM**



| Pin No. | Pin Name          |
|---------|-------------------|
| 1       | OUTPUT1           |
| 2       | GND               |
| 3       | OUTPUT2           |
| 4       | V <sub>cont</sub> |
| 5       | INPUT             |
| 6       | V <sub>DD</sub>   |

**TRUTH TABLE**

| V <sub>cont</sub> | INPUT-OUTPUT1 | INPUT-OUTPUT2 |
|-------------------|---------------|---------------|
| High              | OFF           | ON            |
| Low               | ON            | OFF           |

**ABSOLUTE MAXIMUM RATINGS (T<sub>A</sub> = +25°C, unless otherwise specified)**

| Parameter                     | Symbol            | Ratings     | Unit |
|-------------------------------|-------------------|-------------|------|
| Supply Voltage                | V <sub>DD</sub>   | +6.0        | V    |
| Switch Control Voltage        | V <sub>cont</sub> | +6.0        | V    |
| Input Power                   | P <sub>in</sub>   | +26         | dBm  |
| Operating Ambient Temperature | T <sub>A</sub>    | -45 to +85  | °C   |
| Storage Temperature           | T <sub>stg</sub>  | -55 to +135 | °C   |

**RECOMMENDED OPERATING RANGE (T<sub>A</sub> = +25°C, unless otherwise specified)**

| Parameter                                  | Symbol                | MIN. | TYP. | MAX.            | Unit |
|--|-----------------------|------|------|-----------------|------|
| Supply Voltage <sup>Note</sup>             | V <sub>DD</sub>       | 2.4  | 2.6  | 2.8             | V    |
| Switch Control Voltage (H) <sup>Note</sup> | V <sub>cont (H)</sub> | 2.4  | 2.6  | V <sub>DD</sub> | V    |
| Switch Control Voltage (L)                 | V <sub>cont (L)</sub> | -0.2 | 0    | 0.2             | V    |

**Note** V<sub>cont (H)</sub> ≤ V<sub>DD</sub>

**ELECTRICAL CHARACTERISTICS**


( $T_A = +25^\circ\text{C}$ ,  $V_{DD} = 2.6\text{ V}$ ,  $V_{cont(H)} = 2.6\text{ V}$ ,  $V_{cont(L)} = 0\text{ V}$ , DC cut capacitors = 56 pF, unless otherwise specified)

| Parameter   | Symbol                  | Test Conditions                                      | MIN.  | TYP.  | MAX. | Unit |
|---|-------------------------|--|-------|-------|------|------|
| Insertion Loss 1                                    | $L_{ins1}$              | $f = 0.5\text{ to }1.0\text{ GHz}$                   | –     | 0.30  | 0.45 | dB   |
| Insertion Loss 2                                    | $L_{ins2}$              | $f = 1.0\text{ to }2.0\text{ GHz}$                   | –     | 0.35  | 0.50 |      |
| Insertion Loss 3                                    | $L_{ins3}$              | $f = 2.0\text{ to }2.5\text{ GHz}$                   | –     | 0.40  | 0.55 |      |
| Insertion Loss 4                                    | $L_{ins4}$              | $f = 2.5\text{ to }3.0\text{ GHz}$                   | –     | 0.50  | 0.65 |      |
| Isolation 1   | ISL1                    | $f = 0.5\text{ to }1.0\text{ GHz}$                   | 22    | 25    | –    | dB   |
| Isolation 2   | ISL2                    | $f = 1.0\text{ to }2.0\text{ GHz}$                   | 15    | 18    | –    |      |
| Isolation 3   | ISL3                    | $f = 2.0\text{ to }2.5\text{ GHz}$                   | 14    | 17    | –    |      |
| Isolation 4   | ISL4                    | $f = 2.5\text{ to }3.0\text{ GHz}$                   | 10    | 13    | –    |      |
| Input Return Loss                                   | $RL_{in}$               | $f = 0.5\text{ to }3.0\text{ GHz}$                   | 15    | 20    | –    | dB   |
| Output Return Loss                                  | $RL_{out}$              | $f = 0.5\text{ to }3.0\text{ GHz}$                   | 15    | 20    | –    | dB   |
| 0.1 dB Loss Compression Input Power <sup>Note</sup> | $P_{in(0.1\text{ dB})}$ | $f = 2.0/2.5\text{ GHz}$                             | +18.0 | +21.0 | –    | dBm  |
| 2nd Harmonics                                       | $2f_0$                  | $f = 2.0/2.5\text{ GHz}$ , $P_{in} = +10\text{ dBm}$ | 65    | 75    | –    | dBc  |
| 3rd Harmonics                                       | $3f_0$                  | $f = 2.0/2.5\text{ GHz}$ , $P_{in} = +10\text{ dBm}$ | 65    | 75    | –    | dBc  |
| Supply Current                                      | $I_{DD}$                | No signal  | –     | 50    | 100  | μA   |
| Switch Control Current                              | $I_{cont}$              |  | –     | 4     | 20   | μA   |
| Switch Control Speed                                | $t_{sw}$                | 50% CTL to 90/10% RF                                 | –     | 150   | –    | ns   |

**Note**  $P_{in(0.1\text{ dB})}$  is measured the input power level when the insertion loss increases more 0.1 dB than that of linear range.

**Caution** This device is used it is necessary to use DC cut capacitors.


EVALUATION CIRCUIT



**Remark**  $C_0$  : 56 pF

The application circuits and their parameters are for reference only and are not intended for use in actual design-ins.

**ILLUSTRATION OF THE TEST CIRCUIT ASSEMBLED ON EVALUATION BOARD**




**USING THE NEC EVALUATION BOARD**


| Symbol     | Values   |
|------------|----------|
| C1, C2, C3 | 56 pF    |
| C4, C5     | 1 000 pF |

**TYPICAL CHARACTERISTICS** ( $T_A = +25^\circ\text{C}$ ,  $V_{DD} = 2.6\text{ V}$ ,  $V_{cont(H)} = 2.6\text{ V}$ ,  $V_{cont(L)} = 0\text{ V}$ , DC cut capacitors = 56 pF, using test fixture, unless otherwise specified)


INPUT-OUTPUT1  
INSERTION LOSS vs. FREQUENCY




INPUT-OUTPUT2  
INSERTION LOSS vs. FREQUENCY




INPUT-OUTPUT1  
ISOLATION vs. FREQUENCY




INPUT-OUTPUT2  
ISOLATION vs. FREQUENCY



INPUT-OUTPUT1  
INPUT RETURN LOSS vs. FREQUENCY




INPUT-OUTPUT2  
INPUT RETURN LOSS vs. FREQUENCY




**Remark** The graphs indicate nominal characteristics.


INPUT-OUTPUT1  
OUTPUT RETURN LOSS vs. FREQUENCY



INPUT-OUTPUT2  
OUTPUT RETURN LOSS vs. FREQUENCY




OUTPUT POWER vs. INPUT POWER



**Remark** The graphs indicate nominal characteristics.

**MOUNTING PAD DIMENSIONS**

**6-PIN PLASTIC TSSOP (UNIT: mm)**




**Remark** The mounting pad layouts in this document are for reference only.




**PACKAGE DIMENSIONS**

**6-PIN PLASTIC TSSOP (UNIT: mm)**

**(Top View)**



**(Bottom View)**



**RECOMMENDED SOLDERING CONDITIONS**

This product should be soldered and mounted under the following recommended conditions. For soldering methods and conditions other than those recommended below, contact your nearby sales office.

| Soldering Method | Soldering Conditions  | Condition Symbol |
|------------------|---|------------------|
| Infrared Reflow  | Peak temperature (package surface temperature) : 260°C or below<br>Time at peak temperature : 10 seconds or less<br>Time at temperature of 220°C or higher : 60 seconds or less<br>Preheating time at 120 to 180°C : 120±30 seconds<br>Maximum number of reflow processes : 3 times<br>Maximum chlorine content of rosin flux (% mass) : 0.2%(Wt.) or below | IR260            |
| Wave Soldering   | Peak temperature (molten solder temperature) : 260°C or below<br>Time at peak temperature : 10 seconds or less<br>Preheating temperature (package surface temperature) : 120°C or below<br>Maximum number of flow processes : 1 time<br>Maximum chlorine content of rosin flux (% mass) : 0.2%(Wt.) or below  | WS260            |
| Partial Heating  | Peak temperature (terminal temperature) : 350°C or below<br>Soldering time (per side of device) : 3 seconds or less<br>Maximum chlorine content of rosin flux (% mass) : 0.2%(Wt.) or below   | HS350            |

**Caution Do not use different soldering methods together (except for partial heating).**

Bluetooth is a trademark owned by Bluetooth SIG, Inc., U.S.A.

- **The information in this document is current as of September, 2006. The information is subject to change without notice. For actual design-in, refer to the latest publications of NEC Electronics data sheets or data books, etc., for the most up-to-date specifications of NEC Electronics products. Not all products and/or types are available in every country. Please check with an NEC Electronics sales representative for availability and additional information.**

- No part of this document may be copied or reproduced in any form or by any means without the prior written consent of NEC Electronics. NEC Electronics assumes no responsibility for any errors that may appear in this document.
- NEC Electronics does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from the use of NEC Electronics products listed in this document or any other liability arising from the use of such products. No license, express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC Electronics or others.
- Descriptions of circuits, software and other related information in this document are provided for illustrative purposes in semiconductor product operation and application examples. The incorporation of these circuits, software and information in the design of a customer's equipment shall be done under the full responsibility of the customer. NEC Electronics assumes no responsibility for any losses incurred by customers or third parties arising from the use of these circuits, software and information.
- While NEC Electronics endeavors to enhance the quality, reliability and safety of NEC Electronics products, customers agree and acknowledge that the possibility of defects thereof cannot be eliminated entirely. To minimize risks of damage to property or injury (including death) to persons arising from defects in NEC Electronics products, customers must incorporate sufficient safety measures in their design, such as redundancy, fire-containment and anti-failure features.
- NEC Electronics products are classified into the following three quality grades: "Standard", "Special" and "Specific".

The "Specific" quality grade applies only to NEC Electronics products developed based on a customer-designated "quality assurance program" for a specific application. The recommended applications of an NEC Electronics product depend on its quality grade, as indicated below. Customers must check the quality grade of each NEC Electronics product before using it in a particular application.

"Standard": Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots.

"Special": Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support).

"Specific": Aircraft, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems and medical equipment for life support, etc.

The quality grade of NEC Electronics products is "Standard" unless otherwise expressly specified in NEC Electronics data sheets or data books, etc. If customers wish to use NEC Electronics products in applications not intended by NEC Electronics, they must contact an NEC Electronics sales representative in advance to determine NEC Electronics' willingness to support a given application.

(Note)

- (1) "NEC Electronics" as used in this statement means NEC Electronics Corporation and also includes its majority-owned subsidiaries.
- (2) "NEC Electronics products" means any product developed or manufactured by or for NEC Electronics (as defined above).

|                       |                      |   |
|-----------------------|----------------------|---|
| <p><b>Caution</b></p> | <p>GaAs Products</p> | <p>This product uses gallium arsenide (GaAs). GaAs vapor and powder are hazardous to human health if inhaled or ingested, so please observe the following points.</p> <ul style="list-style-type: none"> <li>• Follow related laws and ordinances when disposing of the product. If there are no applicable laws and/or ordinances, dispose of the product as recommended below.             <ol style="list-style-type: none"> <li>1. Commission a disposal company able to (with a license to) collect, transport and dispose of materials that contain arsenic and other such industrial waste materials.</li> <li>2. Exclude the product from general industrial waste and household garbage, and ensure that the product is controlled (as industrial waste subject to special control) up until final disposal.</li> </ol> </li> <li>• Do not burn, destroy, cut, crush, or chemically dissolve the product.</li> <li>• Do not lick the product or in any way allow it to enter the mouth.</li> </ul> |
|-----------------------|----------------------|---|

► For further information, please contact

**NEC Compound Semiconductor Devices Hong Kong Limited**

E-mail: [contact@ncsd-hk.necel.com](mailto:contact@ncsd-hk.necel.com)

Hong Kong Head Office TEL: +852-3107-7303 FAX: +852-3107-7309  
 Taipei Branch Office TEL: +886-2-8712-0478 FAX: +886-2-2545-3859  
 Korea Branch Office TEL: +82-2-558-2120 FAX: +82-2-558-5209

**NEC Electronics (Europe) GmbH** <http://www.eu.necel.com/>

TEL: +49-211-6503-0 FAX: +49-211-6503-1327

**California Eastern Laboratories, Inc.** <http://www.cel.com/>

TEL: +1-408-988-3500 FAX: +1-408-988-0279

**Compound Semiconductor Devices Division**

**NEC Electronics Corporation**

URL: <http://www.ncsd.necel.com/>

Subject: Compliance with EU Directives

CEL certifies, to its knowledge, that semiconductor and laser products detailed below are compliant with the requirements of European Union (EU) Directive 2002/95/EC Restriction on Use of Hazardous Substances in electrical and electronic equipment (RoHS) and the requirements of EU Directive 2003/11/EC Restriction on Penta and Octa BDE.

CEL Pb-free products have the same base part number with a suffix added. The suffix –A indicates that the device is Pb-free. The –AZ suffix is used to designate devices containing Pb which are exempted from the requirement of RoHS directive (\*). In all cases the devices have Pb-free terminals. All devices with these suffixes meet the requirements of the RoHS directive.

This status is based on CEL’s understanding of the EU Directives and knowledge of the materials that go into its products as of the date of disclosure of this information.

| Restricted Substance per RoHS | Concentration Limit per RoHS (values are not yet fixed) | Concentration contained in CEL devices |     |
|-------------------------------|---|--|-----|
|                               |   | -A                                     | -AZ |
| Lead (Pb)                     | < 1000 PPM  | Not Detected                           | (*) |
| Mercury                       | < 1000 PPM  | Not Detected                           |     |
| Cadmium                       | < 100 PPM   | Not Detected                           |     |
| Hexavalent Chromium           | < 1000 PPM  | Not Detected                           |     |
| PBB                           | < 1000 PPM  | Not Detected                           |     |
| PBDE                          | < 1000 PPM  | Not Detected                           |     |

If you should have any additional questions regarding our devices and compliance to environmental standards, please do not hesitate to contact your local representative.

**Important Information and Disclaimer:** Information provided by CEL on its website or in other communications concerning the substance content of its products represents knowledge and belief as of the date that it is provided. CEL bases its knowledge and belief on information provided by third parties and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. CEL has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. CEL and CEL suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall CEL’s liability arising out of such information exceed the total purchase price of the CEL part(s) at issue sold by CEL to customer on an annual basis.

See CEL Terms and Conditions for additional clarification of warranties and liability.