



## SURFACE MOUNT ULTRAFAST RECOVERY RECTIFIER

Reverse Voltage - 50 to 1000 V

Forward Current - 3 A

### FEATURES

- For surface mounted applications
- Low profile package
- Glass Passivated Chip Junction
- Easy to pick and place
- High efficiency
- Lead free in comply with EU RoHS 2011/65/EU directives

### MECHANICAL DATA

- Case: SMA
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.055g / 0.002oz

### PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode



Top View

Marking Code: US3A~US3M  
Simplified outline SMA and symbol

### Maximum Ratings and Electrical characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20 %.

Parameter	Symbols	US3A	US3B	US3D	US3G	US3J	US3K	US3M	Units					
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V					
Maximum RMS voltage	$V_{RMS}$	35	70	140	280	420	560	700	V					
Maximum DC Blocking Voltage	$V_{DC}$	50	100	200	400	600	800	1000	V					
Maximum Average Forward Rectified Current at $T_c = 125^\circ C$	$I_{F(AV)}$	3							A					
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load	$I_{FSM}$	80							A					
Maximum Instantaneous Forward Voltage at 3 A	$V_F$	1.0		1.3		1.68		V						
Maximum DC Reverse Current $T_a = 25^\circ C$ at Rated DC Blocking Voltage $T_a = 125^\circ C$	$I_R$	5 100							$\mu A$					
Maximum Reverse Recovery Time <sup>(1)</sup>	$t_{rr}$	50			75			ns						
Typical Thermal Resistance <sup>(2)</sup>	$R_{\theta JA}$ $R_{\theta JC}$	50 16							$^\circ C/W$					
Operating and Storage Temperature Range	$T_j, T_{stg}$	-55 ~ +150							$^\circ C$					

( 1 ) Measured with  $I_F = 0.5 A$ ,  $I_R = 1 A$ ,  $I_{rr} = 0.25 A$ .

( 2 ) P.C.B. mounted with 2.0" X 2.0" (5 X 5 cm) copper pad areas.



Fig.1 Maximum Average Forward Current Rating




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Forward Characteristics





Fig.4 Maximum Non-Repetitive Peak Forward Surge Current









## PACKAGE OUTLINE


Plastic surface mounted package; 2 leads

SMA



UNIT		A	D	E	H <sub>E</sub>	c	e	g	a
mm	max	2.2	4.5	2.7	5.2	0.31	1.6	1.5	0.3
	min	1.9	4.0	2.3	4.7	0.15	1.3	0.9	
mil	max	87	181	106	205	12	63	59	12
	min	75	157	91	185	6	51	35	

### The recommended mounting pad size



Unit : mm  
(mil)

### Marking

Type number	Marking code
US3A	US3A
US3B	US3B
US3D	US3D
US3G	US3G
US3J	US3J
US3K	US3K
US3M	US3M