



UTC606P-H

Preliminary

Power MOSFET

-6A, -12V, P-CHANNEL 1.8V TRENCH MOSFET

DESCRIPTION


The UTC **UTC606P-H** is a P-channel MOSFET, it uses UTC's advanced technology to provide the customers with a minimum on state resistance and high switching speed.

The UTC **UTC606P-H** is suitable for battery management, load switch and battery protection.

FEATURES

- * $R_{DS(ON)} < 26m\Omega$ @ $V_{GS} = -4.5V, I_D = -6A$
- * $R_{DS(ON)} < 35m\Omega$ @ $V_{GS} = -2.5V, I_D = -5A$
- * $R_{DS(ON)} < 53m\Omega$ @ $V_{GS} = -1.8V, I_D = -4A$
- * High switching speed
- * High performance trench technology for extremely low $R_{DS(ON)}$

SYMBOL





ORDERING INFORMATION

Ordering Number	Package	Pin Assignment						Packing
		1	2	3	4	5	6	
UTC606PG-AG6-R	SOT-26	D	D	G	D	D	S	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

<p>UTC606PG-AG6-R</p> <p>(1) Packing Type</p> <p>(2) Package Type</p> <p>(3) Green Package</p>	<p>(1) R: Tape Reel</p> <p>(2) AG6: SOT-26</p> <p>(3) G: Halogen Free and Lead Free</p>
--	---

MARKING



SOT-26

■ ABSOLUTE MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	RATINGS	UNIT
Drain-Source Voltage	V_{DSS}	-12	V
Gate-Source Voltage	V_{GSS}	± 8	V
Drain Current	Continuous (Note 2)	I_D	-6
	Pulsed	I_{DM}	-20
Power Dissipation	P_D	300	mW
Junction Temperature	T_J	-55~+150	$^{\circ}\text{C}$
Storage Temperature Range	T_{STG}	-55~+150	$^{\circ}\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL CHARACTERISTICS

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	θ_{JA}	380	$^{\circ}\text{C}/\text{W}$
Junction-to-Case	θ_{JC}	110	$^{\circ}\text{C}/\text{W}$

■ ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}\text{C}$, unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
STATIC PARAMETERS						
Drain-Source Breakdown Voltage	BV_{DSS}	$I_D=-250\mu\text{A}$, $V_{GS}=0\text{V}$	-12			V
Breakdown Voltage Temperature Coefficient	$\frac{\Delta BV_{DSS}}{\Delta T_J}$	$I_D=-250\mu\text{A}$, Referenced to 25°C		-3		$\text{mV}/^{\circ}\text{C}$
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=-10\text{V}$, $V_{GS}=0\text{V}$			-1	μA
Gate-Source Leakage Current	Forward	$V_{GS}=+8\text{V}$, $V_{DS}=0\text{V}$			100	nA
	Reverse	$V_{GS}=-8\text{V}$, $V_{DS}=0\text{V}$			-100	nA
ON CHARACTERISTICS (Note)						
Gate Threshold Voltage	$V_{GS(TH)}$	$V_{DS}=V_{GS}$, $I_D=-250\mu\text{A}$	-0.4	-0.5	-1.5	V
Gate Threshold Voltage Temperature Coefficient	$\frac{\Delta BV_{GS(th)}}{\Delta T_J}$	$I_D=-250\mu\text{A}$, Referenced to 25°C		2.5		$\text{mV}/^{\circ}\text{C}$
Static Drain-Source On-State Resistance	$R_{DS(ON)}$	$V_{GS}=-4.5\text{V}$, $I_D=-6\text{A}$		21	26	$\text{m}\Omega$
		$V_{GS}=-2.5\text{V}$, $I_D=-5\text{A}$		26	35	$\text{m}\Omega$
		$V_{GS}=-1.8\text{V}$, $I_D=-4\text{A}$		34	53	$\text{m}\Omega$
		$V_{GS}=-4.5\text{V}$, $I_D=-6\text{A}$, $T_J=125^{\circ}\text{C}$		28	35	$\text{m}\Omega$
On State Drain Current	$I_{D(ON)}$	$V_{GS}=-4.5\text{V}$, $V_{DS}=-5\text{V}$	-20			A
Forward Transconductance	g_{FS}	$V_{DS}=-5\text{V}$, $I_D=-6\text{A}$		25		S
DYNAMIC PARAMETERS						
Input Capacitance	C_{ISS}	$V_{GS}=0\text{V}$, $V_{DS}=-6\text{V}$, $f=1.0\text{MHz}$		1699		pF
Output Capacitance	C_{OSS}			679		pF
Reverse Transfer Capacitance	C_{RSS}			423		pF
SWITCHING PARAMETERS (Note)						
Total Gate Charge	Q_G	$V_{GS}=-4.5\text{V}$, $V_{DS}=-6\text{V}$, $I_D=-6\text{A}$		18	25	nC
Gate to Source Charge	Q_{GS}			3		nC
Gate to Drain Charge	Q_{GD}			4.2		nC
Turn-ON Delay Time	$t_{D(ON)}$	$V_{GS}=-4.5\text{V}$, $V_{DD}=-6\text{V}$, $I_D=-1\text{A}$, $R_{GEN}=6\Omega$		11	19	ns
Rise Time	t_R			10	20	ns
Turn-OFF Delay Time	$t_{D(OFF)}$			89	142	ns
Fall-Time	t_F			70	112	ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS						
Maximum Continuous Drain-Source Diode Forward Current	I_S				-1.3	A
Drain-Source Diode Forward Voltage	V_{SD}	$I_S=-1.3\text{A}$, $V_{GS}=0\text{V}$ (Note)		-0.6	-1.2	V

Note: Pulse Test: Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2.0\%$

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.