

■ Features


- Low power loss, high efficiency.
- High surge current capability.
- Ultra fast recovery time for switching mode application.
- Low power loss.
- Glass passivated chip junctions.
- Suffix "G" indicates Halogen free parts, ex. UTF8005G.
- Lead-free parts meet environmental standards of MIL-STD-19500 /228

■ Mechanical data

- Epoxy : UL94-V0 rated flame retardant.
- Case : JEDEC ITO-220AC molded plastic body.
- Terminals : Solder plated, solderable per MIL-STD-750, Method 2026.
- Polarity: As marked.
- Mounting Position : Any.
- Weight : Approximated 2.24 gram.

■ Outline

ITO-220AC



■ Maximum ratings and electrical characteristics

Rating at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

Parameter			Conditions			Symbol	MIN.	TYP.	MAX.	UNIT		
Forward rectified current						I _O			8.0	A		
Forward surge current			8.3ms single half sine-wave superimposed on rate load (JEDEC method)			I _{FSM}			150	A		
Reverse current			V _R = V _{RRM} T _A = 25°C		I _R			5.0	uA			
			V _R = V _{RRM} T _A = 125°C					100				
Diode junction capacitance			f=1MHz and applied 4V DC reverse voltage			C _J		80		pF		
Storage temperature						T _{STG}	-55		+150	°C		
Symbol	Marking code	Max. repetitive peak reverse voltage V _{RRM} (V)	Max. RMS voltage V _{RMS} (V)	Max. DC blocking voltage V _R (V)	Max. forward voltage @8A, T _A = 25°C V _F (V)	Max. reverse recovery time(1) T _{rr} (ns)		Operating temperature T _J (°C)				
UTF8005	UTF8005	50	35	50	1.0	50		-55 ~ +150				
UTF801	UTF801	100	70	100								
UTF802	UTF802	200	140	200								
UTF804	UTF804	400	280	400	1.40	75						
UTF806	UTF806	600	420	600	1.70							
UTF808	UTF808	800	560	800								

Note : 1. $I_F = 0.5A$, $I_R = 1.0A$, $I_{RR} = 0.25A$

Rating and characteristic curves

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.5- TEST CIRCUIT DIAGRAM AND REVERSE

RECOVERY TIME CHARACTERISTICS




FIG.3-TYPICAL FORWARD CHARACTERISTICS





FIG.4 - TYPICAL REVERSE CHARACTERISTICS



- CITC reserves the right to make changes to this document and its products and specifications at any time without notice.
- Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.
- CITC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does CITC assume any liability for application assistance or customer product design.
- CITC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.
- No license is granted by implication or otherwise under any intellectual property rights of CITC.
- CITC products are not authorized for use as critical components in life support devices or systems without express written approval of CITC.