




**PHASE NOISE (1 Hz BW, typical)**



**FEATURES**

- Frequency Range: 1600 - 3200 MHz
- Tuning Voltage: 0.5-20 Vdc
- MINI-16-L - Style Package

**APPLICATIONS**

- Test Instrumentation
- CATV Headend Equipment
- Satellite Communication Systems

PERFORMANCE SPECIFICATIONS	VALUE	UNITS
Oscillation Frequency Range	1600 - 3200	MHz
Phase Noise @ 10 kHz offset (1 Hz BW, typ.)	-86	dBc/Hz
Harmonic Suppression (2nd, typ.)	-15	dBc
Tuning Voltage	0.5-20	Vdc
Tuning Sensitivity (avg.)	120	MHz/V
Power Output	10±3	dBm
Load Impedance	50	$\Omega$
Input Capacitance (max.)	75	pF
Pushing	<6	MHz/V
Pulling (14 dB Return Loss, Any Phase)	<8	MHz
Operating Temperature Range	-20 to 70	°C
Package Style	MINI-16-L	
POWER SUPPLY REQUIREMENTS		
Supply Voltage (Vcc, nom.)	15	Vdc
Supply Current (Icc, typ.)	36	mA


All specifications are typical unless otherwise noted and subject to change without notice.

**APPLICATION NOTES**


- AN-100/1 : Mounting and Grounding of VCOs
- AN-102 : Proper Output Loading of VCOs
- AN-107 : How to Solder Z-COMM VCOs

**NOTES:**

**TUNING CURVE, typ.**



**POWER CURVE, typ.**



**PHYSICAL DIMENSIONS**

