


PHASE NOISE (1 Hz BW, typical)



FEATURES

- Frequency Range: 1900 - 2270 MHz
- Tuning Voltage: 2-10 Vdc
- MINI-14H - Style Package

APPLICATIONS

- Basestations
- Test Instruments
- Downconvertors

PERFORMANCE SPECIFICATIONS

VALUE

UNITS

Oscillation Frequency Range	1900 - 2270	MHz
Phase Noise @ 10 kHz offset (1 Hz BW, typ.)	-91	dBc/Hz
Harmonic Suppression (2nd, typ.)	-17	dBc
Tuning Voltage	2-10	Vdc
Tuning Sensitivity (avg.)	61	MHz/V
Power Output	7±3	dBm
Load Impedance	50	Ω
Input Capacitance (max.)	150	pF
Pushing	<5	MHz/V
Pulling (14 dB Return Loss, Any Phase)	<25	MHz
Operating Temperature Range	-40 TO 70	°C
Package Style	MINI-14H	

POWER SUPPLY REQUIREMENTS

Supply Voltage (Vcc, nom.)	12	Vdc
Supply Current (Icc, typ.)	15	mA


All specifications are typical unless otherwise noted and subject to change without notice.

APPLICATION NOTES


- AN-100/1 : Mounting and Grounding of VCOs
- AN-102 : Proper Output Loading of VCOs
- AN-107 : How to Solder Z-COMM VCOs

NOTES:

TUNING CURVE, typ.



POWER CURVE, typ.



PHYSICAL DIMENSIONS

