

14118 Stowe Drive, Suite B | Poway, CA 92064
TEL: (858) 621-2700 | FAX: (858) 486-1927

URL: www.zcomm.com

EMAIL: applications@zcomm.com

Voltage-Controlled Oscillator Surface Mount Module


Applications

- Satellite Communications
- Microwave Relay Links
- Test Equipment

Application Notes

- AN-101: Mounting and Grounding
- AN-102: Output Loading
- AN-107: Manual Soldering

PHASE NOISE (1 Hz BW, typical)



Performance Specifications

	Min	Typ	Max	Units
Oscillation Frequency Range	1626.5		1660.5	MHz
Phase Noise @ 10 kHz offset (1 Hz BW)		-99		dBc/Hz
Harmonic Suppression (2nd)		-15	-13	dBc
Tuning Voltage	0		3	Vdc
Tuning Sensitivity (avg.)		42		MHz/V
Power Output	-5	-2.5	0	dBm
Load Impedance		50		Ω
Input Capacitance			50	pF
Pushing			6	MHz/V
Pulling (14 dB Return Loss, Any Phase)			3	MHz
Operating Temperature Range	-25		70	$^{\circ}\text{C}$
Package Style		MINI-14S		


Power Supply Requirements

	Min	Typ	Max	Units
Supply Voltage (Vcc, nom.)		3		Vdc
Supply Current (Icc)		15	22	mA

Additional Notes


Tuning Curve, typ.

www.DataSheet4U.com



Power Curve, typ.


Footprint




RECOMMENDED FOOTPRINT

SEVERAL HOLES OF $\phi 0.015$ ON GND. PLANE ARE RECOMMENDED FOR GOOD GROUNDING.

0.030 MIN. CUTBACK FROM LIVE PADS



Physical Dimensions



LFSuffix = RoHS Compliant. All specifications are subject to change without notice.