

Silicon Abrupt Tuning Varactors: General Purpose - Ultra Low Leakage

Rev. V1

Features

- Ultra-Low Leakage
- Available as Bare Die or in Glass Axial Leaded Package
- RoHS* Compliant



Bare Die



Glass Axial Leaded

Electrical Specifications: $T_A = +25^\circ\text{C}$

Part Number	Total Capacitance -4 V, 1 MHz	Capacitance Ratio C 0.5 V / C MWV	Working Voltage $I_R = 100 \mu\text{A}$	Breakdown Voltage
	(pF)	Ratio)	(V _{DC})	(V _{DC})
	(Typ.)	(Typ.)	(Max.)	(Min.)
V907	7	4.1	25	28
V910	10	4.1	25	28
V912	12	4.2	25	28
V915	15	4.2	25	28
V920	20	3.9	20	22
V927	27	4.0	20	22
V933	33	4.1	20	22
V939	39	4.1	20	22
V947	47	3.9	20	22
V956	56	3.5	15	17
V968	68	3.5	15	17
V982	82	3.5	15	17
V900	100	3.5	15	17
V907E	7	6.9	100	110
V910E	10	6.9	100	110
V912E	12	7.5	100	110
V915E	15	7.5	100	110
V920E	20	7.9	90	99
V927E	27	7.4	65	72
V933E	33	6.5	60	66
V939E	39	6.3	55	61
V947E	47	6.1	50	55
V956E	56	5.7	40	44
V968E	68	4.6	30	33
V982E	82	4.0	20	22
V900E	100	4.0	20	22

Absolute Maximum Ratings^{5,6}

Parameter	Absolute Maximum
Forward Voltage Drop	1.0 V _{DC}
DC Power Dissipation	400 mW
Reverse Current	5 nA
Capacitance Tolerance	+/-20%
Operating Temperature	-65°C to +150°C
Storage Temperature	-65°C to +200°C

M/A-COM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with M/A-COM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.