



4-Line Bidirectional Symmetrical (BiSy) ESD-Protection Diode in SOT-23-5L

Features


- SOT-23-5L package
- 4-line ESD-protection
- Working range ± 5.5 V
- Low leakage current $< 0.1 \mu\text{A}$
- Low load capacitance $C_D = 16$ pF
- ESD-protection acc. IEC 61000-4-2
 - ± 20 kV contact discharge
 - ± 30 kV air discharge
- Pin plating tin (e3)
- Compliant to RoHS directive 2002/95/EC and in accordance to WEEE 2002/96/EC



RoHS
COMPLIANT
GREEN
[5-2008]**



Marking (example only)



YYY = Type code (see table below)
XX = Date code

Ordering Information

Device name	Ordering code	Taped units per reel (8 mm tape on 7" reel)	Minimum order quantity
VCUT05A4-05S	VCUT05A4-05S-G-08	3000	15 000

Package Data

Device name	Package name	Type code	Weight	Molding compound flammability rating	Moisture sensitivity level	Soldering conditions
VCUT05A4-05S	SOT-23-5L	5A4	15.5 mg	UL 94 V-0	MSL level 1 (according J-STD-020)	260 °C/10 s at terminals

Absolute Maximum Ratings

Parameter	Test conditions	Symbol	Value	Unit
Peak pulse current	Acc. IEC 61000-4-5, 8/20 μs /single shot	I_{PPM}	3.5	A
Peak pulse power	Pin 1 to pin 2, acc. IEC 61000-4-5, 8/20 μs /single shot	P_{PP}	56	W
ESD immunity	Contact discharge acc. IEC61000-4-2; 10 pulses	V_{ESD}	± 20	kV
	Air discharge acc. IEC61000-4-2; 10 pulses		± 30	
Operating temperature	Junction temperature	T_j	- 40 to + 85	°C

** Please see document "Vishay Material Category Policy": <http://www.vishay.com/doc?99902>

Cut the spikes with VCUT05A4-05S:

The **VCUT05A4-05S** is a **Bidirectional** and **Symmetrical (BiSy)** ESD-protection device which clamps positive and negative overvoltage transients to ground. Connected between the signal or data line and the ground the **VCUT05A4-05S** offers a high isolation (low leakage current, low capacitance) within the specified working range.

Electrical Characteristics ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)

VCUT05A4-05S

Parameter	Test conditions/remarks	Symbol	Min.	Typ.	Max.	Unit
Protection paths	Number of lines which can be protected	N_{lines}			4	lines
Reverse stand-off voltage	at $I = 0.1\text{ }\mu\text{A}$	V_{RWM}	5.5			V
Reverse current	at $V = 5.5\text{ V}$	I_R			0.1	μA
Reverse breakdown voltage	at $I = 1\text{ mA}$	V_{BR}	7	7.5		V
Reverse clamping voltage	at $I_{PP} = 1\text{ A}$	V_C			12	V
	at $I_{PP} = I_{PPM} = 3.5\text{ A}$	V_C			16	V
Capacitance	at $V = 0\text{ V}$; $f = 1\text{ MHz}$	C_D		16	20	pF

Typical Characteristics ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)




Figure 1. ESD Discharge Current Wave Form
acc. IEC 61000-4-2 (330 Ω /150 pF)




Figure 2. 8/20 μs Peak Pulse Current Wave Form
acc. IEC 61000-4-5




Figure 3. Typical Capacitance C_D vs. Reverse Voltage V_R




Figure 6. Typical Clamping Performance at +8 kV Contact Discharge (acc. IEC 61000-4-2)




Figure 4. Typical Reverse Voltage V_R vs. Reverse Current I_R




Figure 7. Typical Clamping Performance at -8 kV Contact Discharge (acc. IEC 61000-4-2)




Figure 5. Typical Peak Clamping Voltage V_C vs. Peak Pulse Current I_{PP}








Figure 8. Typical Peak Clamping Voltage at ESD Contact Discharge (acc. IEC 61000-4-2)

Package Dimensions in millimeters (inches): SOT-23-5L




foot print recommendation:



Document no.: S8-3929.01-001 (4)
 Rev. 1 - Date: 15.Jan.2010
 21955

Orientation in Blister Tape



S8-V-3929.01-003 (4)
 Date: 23. 11. 2009
 22006



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.