

NPN SILICON RF POWER TRANSISTOR

DESCRIPTION:

The ASI VHB25-28S is Designed for

FEATURES:

-
-
- **Omnigold™** Metalization System

MAXIMUM RATINGS

I_C	4.0 A
V_{CB0}	65 V
V_{CEO}	35 V
V_{EBO}	4.0 V
P_{DISS}	40 W @ T _C = 25 °C
T_J	-65 °C to +200 °C
T_{STG}	-65 °C to +150 °C
θ_{JC}	4.4 °C/W

PACKAGE STYLE .380 4L STUD

DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	.220 / 5.59	.230 / 5.84
B	.980 / 24.89	
C	.370 / 9.40	.385 / 9.78
D	.004 / 0.10	.007 / 0.18
E	.320 / 8.13	.330 / 8.38
F	.100 / 2.54	.130 / 3.30
G	.450 / 11.43	.490 / 12.45
H	.090 / 2.29	.100 / 2.54
I	.155 / 3.94	.175 / 4.45
J		.750 / 19.05

ORDER CODE: ASI10725

CHARACTERISTICS T_C = 25 °C

SYMBOL	TEST CONDITIONS			MINIMUM	TYPICAL	MAXIMUM	UNITS
BV_{CEO}	I _C = 200 mA			35			V
BV_{CES}	I _C = 200 mA			65			V
BV_{EBO}	I _E = 10 mA			4.0			V
I_{CB0}	V _E = 28 V					2.0	mA
h_{FE}	V _{CE} = 5.0 V	I _C = 200 mA		5		---	---
C_{OB}	V _{CB} = 28 V	f = 1.0 MHz				50	pF
f_T	V _{CE} = 10 V	I _C = 200 mA	f = 100 MHz	250			MHz
P_G	V _{CC} = 28 V	P _{OUT} = 25 W	f = 175 MHz	8.5			dB
η_C					60		%