


VMIL 100

100 Watts, 28 Volts, Class AB
Defcom 100 - 200 MHz

GENERAL DESCRIPTION

The VMIL100 is an input matched COMMON EMITTER broadband transistor specifically intended for use in the 100-200 MHz frequency band. It may be operated in Class AB or C. Gold metallization and silicon diffused resistors ensure ruggedness and high reliability.

CASE OUTLINE 55HV, Style 2



ABSOLUTE MAXIMUM RATINGS

Maximum Power Dissipation @ 25°C 270 Watts

Maximum Voltage and Current

BVces Collector to Emitter Voltage 65 Volts
BVebo Emitter to Base Voltage 4.0 Volts
Ic Collector Current 20 A

Maximum Temperatures

Storage Temperature - 65 to +150°C
Operating Junction Temperature +150°C

ELECTRICAL CHARACTERISTICS @ 25 °C


SYMBOL	CHARACTERISTICS	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Pout	Power Output	F = 175 MHz	100			Watts
Pin	Power Input	Vcc = 28 Volts		14	20	Watts
Pg	Power Gain		7.0	8.5		dB
η_c	Efficiency			60		%
VSWR	Load Mismatch Tolerance	Po=100W, F=175 MHz			30:1	

BVebo	Emitter to Base Breakdown	Ie = 5 mA	4.0			Volts
BVces	Collector to Emitter Breakdown	Ic = 100 mA	65			Volts
BVceo	Collector to Emitter Breakdown	Ie = 50 mA	33			Volts
Cob	Output Capacitance	Vcb = 28 V, F = 1 MHz		220		pF
h_{FE}	DC - Current Gain	Vce = 5 V, Ic = 1 A	10			
θ_{jc}	Thermal Resistance				.65	°C/W


Issue August 1996

GHz TECHNOLOGY INC. RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE. GHz RECOMMENDS THAT BEFORE THE PRODUCT(S) DESCRIBED HEREIN ARE WRITTEN INTO SPECIFICATIONS, OR USED IN CRITICAL APPLICATIONS, THAT THE PERFORMANCE CHARACTERISTICS BE VERIFIED BY CONTACTING THE FACTORY.

DC SAFE OPERATING AREA



POWER GAIN VS FREQUENCY



POWER OUTPUT vs POWER INPUT

Vcc= 28V f=200MHz

