

Features


- Low on-resistance $R_{DS(on)}$ @ $V_{GS} = -2.5V$
- Fast Switching and High efficiency
- Enhancement mode
- Pb-free lead plating; RoHS compliant



Halogen-Free

V_{DS}	-20	V
$R_{DS(on),TYP} @ V_{GS} = -4.5V$	7.3	mΩ
$R_{DS(on),TYP} @ V_{GS} = -2.5V$	10	mΩ
I_D	-55	A

PDFN3333



Part ID	Package Type	Marking	Tape and reel information
VS2508AE	PDFN3333	2508AE	5000pcs/Reel

Drain Pin5-8



Source Pin1-3

Maximum ratings, at $T_A = 25^\circ\text{C}$, unless otherwise specified

Symbol	Parameter	Rating	Unit
$V_{(BR)DSS}$	Drain-Source breakdown voltage	-20	V
V_{GS}	Gate-Source voltage	± 12	V
I_S	Diode continuous forward current	$T_C = 25^\circ\text{C}$	A
I_D	Continuous drain current @ $V_{GS} = -4.5V$	$T_C = 25^\circ\text{C}$	A
		$T_C = 100^\circ\text{C}$	A
I_{DM}	Pulse drain current tested ①	$T_C = 25^\circ\text{C}$	A
I_{DSM}	Continuous drain current @ $V_{GS} = -4.5V$	$T_A = 25^\circ\text{C}$	A
		$T_A = 70^\circ\text{C}$	A
EAS	Avalanche energy, single pulsed ②	90	mJ
P_D	Maximum power dissipation	$T_C = 25^\circ\text{C}$	W
P_{DSM}	Maximum power dissipation ③	$T_A = 25^\circ\text{C}$	W
T_{STG}, T_J	Storage and junction temperature range	-55 to 150	$^\circ\text{C}$

Thermal Characteristics

Symbol	Parameter	Typical	Unit
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	3.3	$^\circ\text{C/W}$
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	35	$^\circ\text{C/W}$







Electrical Characteristics

Symbol	Parameter	Condition	Min.	Typ.	Max.	Unit
Static Electrical Characteristics @ T _j = 25°C (unless otherwise stated)						
V _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =-250μA	-20	--	--	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =-20V, V _{GS} =0V	--	--	-1	μA
	Zero Gate Voltage Drain Current(T _j =125°C)	V _{DS} =-20V, V _{GS} =0V	--	--	-100	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} =±12V, V _{DS} =0V	--	--	±100	nA
V _{GS(TH)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =-250μA	-0.3	-0.6	-1.0	V
R _{DS(ON)}	Drain-Source On-State Resistance ④	V _{GS} =-4.5V, I _D =-15A	--	7.3	9	mΩ
R _{DS(ON)}	Drain-Source On-State Resistance ④	V _{GS} =-2.5V, I _D =-12A	--	10	13	mΩ
R _{DS(ON)}	Drain-Source On-State Resistance ④	V _{GS} =-1.8V, I _D =-10A	--	16	20	mΩ
Dynamic Electrical Characteristics @ T _j = 25°C (unless otherwise stated)						
C _{iss}	Input Capacitance	V _{DS} =-10V, V _{GS} =0V, f=1MHz	3900	4590	5280	pF
C _{oss}	Output Capacitance		430	505	580	pF
C _{rss}	Reverse Transfer Capacitance		375	440	505	pF
R _g	Gate Resistance	f=1MHz	--	2.3	--	Ω
Q _g	Total Gate Charge	V _{DS} =-10V, I _D =-15A, V _{GS} =-4.5V	--	49	--	nC
Q _{gs}	Gate-Source Charge		--	7.7	--	nC
Q _{gd}	Gate-Drain Charge		--	11	--	nC
Switching Characteristics						
t _{d(on)}	Turn-on Delay Time	V _{DD} =-10V, I _D =-15A, R _G =2.7Ω, V _{GS} =-10V	--	8.4	--	ns
t _r	Turn-on Rise Time		--	69	--	ns
t _{d(off)}	Turn-Off Delay Time		--	117	--	ns
t _f	Turn-Off Fall Time		--	46	--	ns
Source- Drain Diode Characteristics@ T _j = 25°C (unless otherwise stated)						
V _{SD}	Forward on voltage	I _{SD} =-20A, V _{GS} =0V	--	-0.8	-1.2	V
t _{rr}	Reverse Recovery Time	T _j =25°C, I _{sd} =-15A, V _{GS} =0V	--	16	--	ns
Q _{rr}	Reverse Recovery Charge	di/dt=-100A/μs	--	7.1	--	nC

NOTE:

- ① Repetitive rating; pulse width limited by max junction temperature.
- ② Limited by T_{Jmax}, starting T_J = 25°C, L = 0.5mH, R_G = 25Ω, I_{AS} = -19A, V_{GS} = -10V. Part not recommended for use above this value
- ③ The power dissipation P_{DSM} is based on R_{θJA} and the maximum allowed junction temperature of 150°C.
- ④ Pulse width ≤ 300μs; duty cycle ≤ 2%.

Typical Characteristics



Typical Characteristics




Fig7. Typical Capacitance Vs. Drain-Source Voltage




Fig8. Typical Gate Charge Vs. Gate-Source Voltage




Fig9. Normalized Maximum Transient Thermal Impedance




Fig10. Unclamped Inductive Test Circuit and Waveforms





Fig11. Switching Time Test Circuit and waveforms

Marking Information

1st line: Vanguard Code (Vs)

2nd line: Part Number (2508AE)


3rd line: Date code (XXXYWW)

XXX: Wafer Lot Number Code , code changed with Lot Number

YY: Year Code, (e.g. E=2017, F=2018, G=2019, H=2020, etc)

WW: Week Code (01 to 53)

PDFN3333 Package Outline Data



Symbol	DIMENSIONS (unit : mm)		
	Min	Typ	Max
A	0.7	0.75	0.8
b	0.25	0.3	0.35
C	0.1	0.15	0.25
D	3.25	3.35	3.45
D1	3	3.1	3.2
D2	1.78	1.88	1.98
D3	--	0.13	--
E	3.2	3.3	3.4
E1	3	3.15	3.2
E2	2.39	2.49	2.59
e	0.65 BSC		
H	0.3	0.39	0.5
L	0.3	0.4	0.5
L1	--	0.13	--
θ	--	10°	12°
M	*	*	0.15
* Not specified			

Notes:

1. Follow JEDEC MO-240 variation CA.
2. Dimensions "D1" and "E1" do NOT include mold flash protrusions or gate burrs.
3. Dimensions "D1" and "E1" include interterminal flash or protrusion. Interterminal flash or protrusion shall not exceed 0.25mm per side.

Customer Service

Sales and Service:

sales@vgsemi.com

Vanguard Semiconductor CO., LTD

TEL: (86-755) -26902410

FAX: (86-755) -26907027

WEB: www.vgsemi.com