

Features


- N-Channel, 5V Logic Level Control
- Enhancement mode
- Low on-resistance $R_{DS(on)}$ @ $V_{GS}=4.5\text{ V}$
- Fast Switching
- 100% Avalanche Tested
- Pb-free lead plating; RoHS compliant



Part ID	Package Type	Marking	Tape and reel information
VSI007N07MS	TO-251	007N07M	75pcs/Tube

V_{DS}	80	V
$R_{DS(on),TYP} @ V_{GS}=10\text{ V}$	9.3	m Ω
$R_{DS(on),TYP} @ V_{GS}=4.5\text{ V}$	10	m Ω
I_D	70	A

TO-251



Maximum ratings, at $T_j=25\text{ }^\circ\text{C}$, unless otherwise specified

Symbol	Parameter	Rating	Unit
$V_{(BR)DSS}$	Drain-Source breakdown voltage	80	V
I_S	Diode continuous forward current	$T_C=25\text{ }^\circ\text{C}$	70 A
I_D	Continuous drain current @ $V_{GS}=10\text{ V}$	$T_C=25\text{ }^\circ\text{C}$	70 A
		$T_C=100\text{ }^\circ\text{C}$	44 A
I_{DM}	Pulse drain current tested ①	$T_C=25\text{ }^\circ\text{C}$	280 A
EAS	Avalanche energy, single pulsed ②	81	mJ
P_D	Maximum power dissipation	$T_C=25\text{ }^\circ\text{C}$	83 W
V_{GS}	Gate-Source voltage	± 20	V
$T_{STG} T_J$	Storage and operating temperature range	-55 to 150	$^\circ\text{C}$

Thermal Characteristics

Symbol	Parameter	Typical	Unit
$R_{\theta JC}$	Thermal Resistance-Junction to Case	1.5	$^\circ\text{C/W}$
$R_{\theta JA}$	Thermal Resistance-Junction to Ambient	100	$^\circ\text{C/W}$



Symbol	Parameter	Condition	Min.	Typ.	Max.	Unit
Static Electrical Characteristics @ T_j = 25°C (unless otherwise stated)						
V _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250μA	80	--	--	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =80V, V _{GS} =0V	--	--	1	μA
	Zero Gate Voltage Drain Current(T _j =125°C)	V _{DS} =80V, V _{GS} =0V	--	--	100	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} =±20V, V _{DS} =0V	--	--	±100	nA
V _{GS(TH)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250μA	1.2	1.9	2.4	V
R _{DS(ON)}	Drain-Source On-State Resistance ^③	V _{GS} =10V, I _D =30A	--	9.3	12	mΩ
R _{DS(ON)}	Drain-Source On-State Resistance ^③	V _{GS} =4.5V, I _D =15A	--	10	13	mΩ
Dynamic Electrical Characteristics @ T_j= 25°C (unless otherwise stated)						
C _{iss}	Input Capacitance	V _{DS} =30V, V _{GS} =0V, f=1MHz	3900	4350	4800	pF
C _{oss}	Output Capacitance		100	220	300	pF
C _{rss}	Reverse Transfer Capacitance		100	180	250	pF
R _g	Gate Resistance	f=1MHz		2.2		Ω
Q _g	Total Gate Charge	V _{DS} =40V, I _D =30A, V _{GS} =10V	--	78	--	nC
Q _{gs}	Gate-Source Charge		--	19	--	nC
Q _{gd}	Gate-Drain Charge		--	10	--	nC
Switching Characteristics						
t _{d(on)}	Turn-on Delay Time	V _{DD} =40V, I _D =30A, R _G =3Ω, V _{GS} =10V	--	13	--	nS
t _r	Turn-on Rise Time		--	25	--	nS
t _{d(off)}	Turn-Off Delay Time		--	98	--	nS
t _f	Turn-Off Fall Time		--	43	--	nS
Source- Drain Diode Characteristics @ T_j= 25°C (unless otherwise stated)						
V _{SD}	Forward on voltage	I _{SD} =30A, V _{GS} =0V	--	0.8	1.2	V
t _{rr}	Reverse Recovery Time	T _j =25°C, I _{sd} =30A, di/dt=500A/μs	--	25	--	nS
Q _{rr}	Reverse Recovery Charge			47		nC

NOTE:

- ① Repetitive rating; pulse width limited by max. junction temperature.
- ② Limited by T_{Jmax}, starting T_J = 25°C, L = 0.5mH, R_G = 25Ω, I_{AS} = 18A, V_{GS} = 10V. Part not recommended for use above this value
- ③ Pulse width ≤ 300μs; duty cycle ≤ 2%.

Typical Characteristics




Fig1. Typical Output Characteristics




Fig2. $V_{GS(TH)}$ Gate-Source Voltage Vs. T_j




Fig3. Typical Transfer Characteristics




Fig4. Normalized On-Resistance Vs. T_j




Fig5. Typical Source-Drain Diode Forward Voltage




Fig6. Maximum Safe Operating Area

Typical Characteristics




Fig7. Typical Capacitance Vs.Drain-Source Voltage




Fig8. Typical Gate Charge Vs.Gate-Source Voltage




Fig9 . Normalized Maximum Transient Thermal Impedance




Fig10. Unclamped Inductive Test Circuit and waveforms





Fig11. Switching Time Test Circuit and waveforms

TO-251 Package Outline



DIMENSIONS (unit : mm)

Label	Min	Typ	Max	Label	Min	Typ	Max
A	2.22	2.30	2.38	A ₁	0.46	0.55	0.93
b	0.71	0.78	0.89	c	0.46	0.51	0.56
D ₁	0.96	1.02	1.10	D ₂	5.98	6.05	6.22
E	6.47	6.60	6.73	E ₁	5.20	5.33	5.55
e	--	4.57	--	e ₁	--	2.28	--
L	9.00	9.38	9.60	L ₁	--	2.70	--
Q	1.00	1.05	1.10	w	--	0.30	--

Customer Service

Sales and Service:

sales@vgsemi.com

Vanguard Semiconductor CO., LTD

TEL: (86-755) -26902410

FAX: (86-755) -26907027

WEB: www.vgsemi.com