


Features

- N-Channel
- Enhancement mode
- Very low on-resistance $R_{DS(on)}$ @ $V_{GS}=4.5\text{ V}$
- Fast Switching
- High conversion efficiency
- Pb-free lead plating; RoHS compliant



Halogen-Free

V_{DS}	80	V
$R_{DS(on),TYP@ V_{GS}=10\text{ V}}$	8.0	mΩ
$R_{DS(on),TYP@ V_{GS}=4.5V}$	9.0	mΩ
I_D	16	A



Part ID	Package Type	Marking	Tape and reel information
VSO010N08MS	SOP8	010N08M	3000pcs/Reel

Maximum ratings, at $T_j=25\text{ °C}$, unless otherwise specified

Symbol	Parameter		Rating	Unit
$V_{(BR)DSS}$	Drain-Source breakdown voltage		80	V
I_S	Diode continuous forward current	$T_C=25\text{ °C}$	16	A
I_D	Continuous drain current@ $V_{GS}=10V$	$T_C=25\text{ °C}$	16	A
		$T_A=100\text{ °C}$	10	A
I_{DM}	Pulse drain current tested ①	$T_C=25\text{ °C}$	64	A
EAS	Avalanche energy, single pulsed ②	$I_D=17A$	72	mJ
IAS	Avalanche energy, single pulsed ②		30	A
P_D	Maximum power dissipation	$T_A=25\text{ °C}$	2.5	W
V_{GS}	Gate-Source voltage		±20	V
MSL			Level 3	
$T_{STG} T_J$	Storage and operating temperature range		-55 to 150	°C

Thermal Characteristics

Symbol	Parameter	Typical	Unit
$R_{\theta JC}$	Thermal Resistance-Junction to Case	1.5	°C/W
$R_{\theta JA}$	Thermal Resistance Junction-Ambient	50	°C/W

Symbol	Parameter	Condition	Min.	Typ.	Max.	Unit
Static Electrical Characteristics @ T _c = 25°C (unless otherwise stated)						
V _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V I _D =250μA	80	--	--	V
I _{DSS}	Zero Gate Voltage Drain Current(T _c =25°C)	V _{DS} =80V,V _{GS} =0V	--	--	1	μA
	Zero Gate Voltage Drain Current(T _c =125°C)	V _{DS} =80V,V _{GS} =0V	--	--	100	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} =±20V,V _{DS} =0V	--	--	±100	nA
V _{GS(TH)}	Gate Threshold Voltage	V _{DS} =V _{GS} ,I _D =250μA	1.0	1.6	3.0	V
R _{DS(ON)}	Drain-Source On-State Resistance③	V _{GS} =10V, I _D =10A	--	8.0	10	mΩ
R _{DS(ON)}	Drain-Source On-State Resistance③	V _{GS} =4.5V, I _D =4A	--	9.0	13	mΩ
Dynamic Electrical Characteristics @ T _c = 25°C (unless otherwise stated)						
C _{iss}	Input Capacitance	V _{DS} =40V,V _{GS} =0V, f=1MHz	--	3950	--	pF
C _{oss}	Output Capacitance		--	390	--	pF
C _{rss}	Reverse Transfer Capacitance		--	175	--	pF
Q _g	Total Gate Charge	V _{DS} =40V,I _D =5A, V _{GS} =10V	--	68	--	nC
Q _{gs}	Gate-Source Charge		--	23	--	nC
Q _{gd}	Gate-Drain Charge		--	19	--	nC
Switching Characteristics						
t _{d(on)}	Turn-on Delay Time	V _{DD} =40V, I _D =4A, R _G =6.8Ω, V _{GS} =10V	--	24	--	nS
t _r	Turn-on Rise Time		--	16	--	nS
t _{d(off)}	Turn-Off Delay Time		--	35	--	nS
t _f	Turn-Off Fall Time		--	10.5	--	nS
Source- Drain Diode Characteristics@ T _c = 25°C (unless otherwise stated)						
V _{SD}	Forward on voltage	I _{SD} =10A,V _{GS} =0V	--	0.77	1.2	V
t _{rr}	Reverse Recovery Time	T _J =25°C,I _{sd} =10A, V _{GS} =0V	--	30	--	nS
Q _{rr}	Reverse Recovery Charge	di/dt=100A/μs		75		nC

NOTE:

- ① Repetitive rating; pulse width limited by max. junction temperature.
- ② Limited by T_{Jmax}, starting T_J = 25°C, L = 0.5mH, R_G = 25Ω, I_{AS} = 17A, V_{GS}=10V. Part not recommended for use above this value
- ③ Pulse width ≤ 300μs; duty cycle ≤ 2%.

Typical Characteristics




Fig1. Typical Output Characteristics




Fig2. Normalized Threshold Voltage Vs. Temperature




Fig3. Typical Transfer Characteristics




Fig4. Normalized On-Resistance Vs. Temperature




Fig5. Typical Source-Drain Diode Forward Voltage










Fig6. Maximum Safe Operating Area

Typical Characteristics



Marking Information

1st line: Company Code (Vs), Company Logo

2nd line: Part Number (010N08M)


3rd line: Date code (XXXYWW)

XXX: Wafer Lot Number

Y: Year Code, e.g. E means 2017

WW: Week Code

SOP8 Package Outline Data



Label	Dimensions (unit: mm)		
	Min	Typ	Max
A	--	--	1.75
A ₁	0.10	0.18	0.25
A ₂	1.25	1.35	1.50
A ₃	--	0.25	--
b _p	0.36	0.42	0.51
c	0.19	0.22	0.25
D	4.80	4.92	5.00
E	3.80	3.90	4.00
e	--	1.27	--
H _E	5.80	6.00	6.20
L	--	1.05	--
L _p	0.40	0.68	1.00
Q	0.60	0.65	0.725
v	--	0.25	--
w	--	0.25	--
y	--	0.10	--
Z	0.30	0.50	0.70
θ	0°		8°

Notes:

1. Follow JEDEC MS-012.
2. Dimension "D" does NOT include mold flash, protrusions or gate burrs. Mold flash, protrusions or gate burrs shall not exceed 0.15mm per side.
3. Dimension "E" does NOT include interlead flash or protrusion. Interlead flash or protrusion shall not exceed 0.25mm per side.
4. Dimension "b_p" does NOT include dambar protrusion. Allowable dambar protrusion shall be 0.1mm total in excess of "b_p" dimension at maximum material condition. The dambar cannot be located on the lower radius of the foot.

Customer Service

Sales and Service:

sales@vgsemi.com

Vanguard Semiconductor CO., LTD

TEL: (86-755) -26902410

FAX: (86-755) -26907027

WEB: www.vgsemi.com