SPECIFICATION

MODULE NO.:   WG160128C

General Specification

Item	Dimension	Unit
Number of dots	160 x 128	—
Module dimension	150.0 x 112.0 x 23.0 (MAX)	mm
View area	101.0 x 82.0	mm
Active area	95.96 x 76.76	mm
Dot size	0.56 x 0.56	mm
Dot pitch	0.60 x 0.60	mm
Duty	1/128	
Backlight Type	LED	
IC	RA6963	
Interface	8080	

Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	T_{OP}	-20	—	+70	℃
Storage Temperature	T_{ST}	-30	—	+80	℃
Input Voltage	V_{IN}	-0.3	—	V_{DD}+0.3	V
Supply Voltage For Logic	V_{DD}-V_{SS}	-0.3	—	+7.0	V

Electrical Characteristics

Item	Symbol	Condition	Min	Typ	Max	Unit
Supply Voltage For Logic	V_{DD}-V_{SS}	—	4.5	5.0	5.5	V
Supply Voltage For LCD	V_{DD}-V_0	Ta=-20℃	—	—	22.1	V
		Ta=25℃	18.4	18.95	19.5	V
		Ta=70℃	16.1	—	—	V
Input High Volt.	V_{IH}	—	0.8V_{DD}	—	V_{DD}	V
Input Low Volt.	V_{IL}	—	0	—	0.15 V_{DD}	V
Output High Volt.	V_{OH}	—	V_{DD}-0.3	—	V_{DD}	V
Output Low Volt.	V_{OL}	—	0	—	0.3	V
Supply Current	I_{DD}	—	—	42	—	mA

Interface Pin Function

Pin No.	Symbol	Level	Description
1	FG	-	Frame ground
2	Vss	-	Ground
3	Vdd	-	Power supply for logic
4	Vo	-	contrast adjustment
5	Vee	-	Negative Voltage Output
6	/WR	L	Data write. Write data into RA6963when WR = L
7	/RD	L	Data read. Read data from RA6963when RD = L
8	/CE	L	Chip enable the controller RA6963
9	C/D	H / L	WR=L , C/D=H : Command Write C/D=L: Data write RD=L , C/D=H : Status Read C/D=L: Data read
10	/HALT	L	Clock operating stop signal
11	/RESET	H / L	Reset signal
12	DB0	H / L	Data bus line
13	DB1	H / L	Data bus line
14	DB2	H / L	Data bus line
15	DB3	H / L	Data bus line
16	DB4	H / L	Data bus line
17	DB5	H / L	Data bus line
18	DB6	H / L	Data bus line
19	DB7	H / L	Data bus line
20	NC		No connection

Contour Drawing

PIN NO	SYMBOL
1	FG
2	Vss
3	Vdd
4	Vo
5	Vee
6	$\overline{WR}$
7	$\overline{RD}$
8	$\overline{CE}$
9	$C/\overline{D}$
10	$\overline{HALT}$
11	$\overline{RESET}$
12	DB0
13	DB1
14	DB2
15	DB3
16	DB4
17	DB5
18	DB6
19	DB7
20	NC

The non-specified tolerance of dimension is ±0.3mm.

DOT SIZE
SCALE 10/1

LED B/L

JST XHP-3 or Equivalent