

WJA1001

+5V Active-Bias InGaP HBT Gain Block



Product Features

- 50 – 3000 MHz
- 19 dB Gain @ 900MHz
- +20 dBm P1dB @ 900MHz
- +45 dBm OIP3 @ 900MHz
- +5V Single Supply
- Low current draw (100 mA)
- Unconditionally stable
- Internally matched to 50 Ω
- Robust 1000V ESD, Class 1C
- Lead-free/green/RoHS-compliant SOT-89 package

Applications

- GSM, PCS, CDMA, WCDMA
- WiMAX, WiBro
- Repeaters, BTS Transceivers
- RFID


Product Description

The WJA1001 is a cascadable gain block that offers high linearity in a low-cost surface-mount package. At 900 MHz, the WJA1001 typically provides 19 dB gain, +45 dBm OIP3, and +20 dBm P1dB. The device is housed in a lead-free/green/RoHS-compliant SOT-89 SMT package using a NiPdAu plating to eliminate the possibility of tin whiskering.

The WJA1001 consists of a Darlington-pair amplifier using a high reliability InGaP/GaAs HBT process technology. The amplifier has been optimized internally to offer very high linearity performance at 1 GHz while drawing very low current. The MMIC amplifier is internally matched to 50Ω and only requires DC-blocking capacitors and a bias inductor for operation. An internal active bias is designed to enable stable performance over temperature and allow for operation directly from a +5V supply voltage.

The broadband amplifier can be directly applied to various current and next generation wireless technologies such as GSM, CDMA, W-CDMA, WiBro, and WiMAX. The WJA1001 is ideal for general purpose applications such as LO buffering or amplification and pre-driver stages within the 50 to 3000 MHz frequency range.

Functional Diagram



Function	Pin No.
Input	1
Output/Bias	3
Ground	2, 4

Specifications ⁽¹⁾

Parameter	Units	Min	Typ	Max
Operational Bandwidth	MHz	50		3000
Test Frequency	MHz		900	
Gain	dB	17.5	19	20.5
Input Return Loss	dB		12	
Output Return Loss	dB		14	
Output P1dB	dBm		+19.7	
Output IP3 ⁽²⁾	dBm	+39	+44.5	
Noise Figure	dB		5.4	
Device Voltage	V		5.0	
Device Current	mA	88	100	108

1. Test conditions: 25 °C, Supply Voltage = +5 V, 50 Ω System. S-parameters and 3OIP measured at device pins. All other specifications measured on evaluation board.
2. 3OIP measured with two tones at an output power of +8 dBm/tone separated by 1 MHz. The suppression on the largest IM3 product is used to calculate the 3OIP using a 2:1 rule.

Typical Performance ⁽³⁾

Parameter	Units	Typical				
Frequency	MHz	200	500	900	1900	2100
S21	dB	19.6	19.2	18.5	16.7	16.4
S11	dB	-13	-15	-18	-30	-26
S22	dB	-22	-20	-15	-11	-12
Output P1dB	dBm	+20.4	+20.3	+19.7	+19.2	+18.1
Output IP3 ⁽²⁾	dBm	+39.7	+39	+44	+34	+34
Noise Figure	dB	4.8	5.0	5.4	6.1	6.4

3. Listed typical performance parameters measured on evaluation board.

**Not Recommended For
New Designs**
Recommended replacement parts:
TQP3M9009

Absolute Maximum Rating

Parameter	Rating
Storage Temperature	-55 to +150 °C
Supply Voltage	+6.5 V
Input Power	+24 dBm
θ _{jc} (junction to paddle)	80.6 °C / W
Maximum Junction Temperature	150 °C

Operation of this device above any of these parameters may cause permanent damage.










Ordering Information

Part No.	Description
WJA1001	+5V Active Bias InGaP HBT Gain Block (lead-free/green/RoHS-compliant SOT-89 Package)



Standard tape / reel size = 1000 pieces on a 7" reel

Specifications and information are subject to change without notice

Typical Evaluation Board RF Performance Supply Bias = +5V, $I_{cc} = 100\text{ mA}$



Application Circuit



Recommended Component Values ⁽¹⁾

Ref. Name	Value / Type	Size
L1	470 nH ferrite core wire wound inductor ⁽²⁾	0805
C1, C2	1000 pF NPO chip capacitor	0603
C3	0.018 μF chip capacitor	0603
R1, R2, R4	0 Ω ⁽³⁾	0603
C4, R3, R5	Do Not Place ⁽³⁾	

1. The listed values are contained on the evaluation board to achieve optimal broadband performance
2. For lower cost and performance (500 – 2000 MHz) option use 39 nH ceramic core wire wound inductor.
3. Place holders for the 0Ω resistors and “Do Not Place” references are not needed for final design.

Typical Device Data

S-Parameters ($V_{device} = +5\text{ V}$, $I_{CC} = 100\text{ mA}$, $T = 25\text{ }^\circ\text{C}$, calibrated to device leads)

Freq (GHz)	S11 (dB)	S11 (ang)	S21 (dB)	S21 (ang)	S12 (dB)	S12 (ang)	S22 (dB)	S22 (ang)
10	-16.19	-74.53	22.52	170.02	-25.75	12.97	-11.35	-37.50
50	-13.73	-150.31	20.24	167.55	-23.34	6.00	-17.22	-110.83
100	-13.40	-165.59	19.82	167.74	-23.16	2.19	-18.78	-136.33
200	-13.27	-173.49	19.60	162.77	-23.09	-1.09	-19.05	-148.58
400	-12.67	-178.71	19.50	149.81	-23.01	-4.76	-18.29	-151.10
600	-12.13	177.74	19.35	136.50	-22.97	-8.79	-17.08	-151.78
800	-11.99	172.41	19.15	122.68	-22.90	-12.46	-15.70	-150.91
1000	-12.07	163.93	18.99	109.45	-22.85	-16.03	-13.92	-151.81
1200	-12.02	152.87	18.73	94.83	-22.84	-19.42	-12.73	-157.08
1400	-11.71	142.18	18.33	81.54	-22.75	-23.24	-11.59	-165.19
1600	-11.76	132.89	18.10	67.63	-22.81	-27.41	-10.74	-173.87
1800	-12.61	125.70	17.71	53.78	-22.66	-30.65	-9.99	179.93
2000	-14.95	116.23	17.35	40.27	-22.75	-35.01	-9.15	175.81
2200	-18.89	100.16	16.88	26.53	-22.71	-38.53	-8.48	171.38
2400	-24.73	70.36	16.27	12.71	-22.78	-41.54	-8.13	165.83
2600	-32.51	32.55	15.76	-1.15	-22.67	-45.93	-8.09	157.59
2800	-28.92	-123.80	15.14	-14.50	-22.65	-49.54	-8.09	148.86
3000	-18.69	-139.28	14.31	-28.11	-22.55	-53.67	-7.84	140.92
3200	-13.74	-143.12	13.44	-41.58	-22.62	-57.98	-7.43	135.57
3400	-10.86	-145.10	12.37	-53.94	-22.64	-61.93	-7.02	130.30
3600	-9.38	-150.89	11.40	-65.62	-22.59	-65.84	-6.80	126.09
3800	-8.61	-162.51	10.54	-76.54	-22.46	-69.00	-6.67	121.50
4000	-7.74	-178.88	9.54	-88.57	-22.15	-73.94	-6.65	116.69

Device S-parameters are available for Download from the website at: <http://www.triquint.com>

