

WLM54AG 6B-23 MINIPCI

Atheros AR5414 Chipset

23dBm @ 2.4/5GHz (200mW)



- ◆ **High Performance with Low Power Consumption**
- ◆ **Output Power of up to 23dBm at a/b/g band**
- ◆ **Affordable and ideal for a variety of applications**

Complex WLM54AG 6B-23 MiniPCI network adapter is compact, lightweight, has high-performance and low power consumption. Built on Atheros AR5414 chipset, it can be used for all IEEE802.11 a/b/g compatible WLAN and support up to 108Mbps high-speed data rate. It is ideally suited for integration in a wide range of OEM devices.

WLM54AG 6B-23 MiniPCI network adapter offers an output power of up to 23dBm on a/b/g band, and also supports a variety of security features such as WEP, AES, receive and transmit filtering, error recovery, quality of service (QoS) as well as IEEE802.1x standard, thus providing security to the wireless network and increase WLAN performance.

Features

- 2.4/ 5GHz IEEE 802.11 a/b/g standard
- Up to 108Mbps high-speed data rate
- Output Power of up to 23dBm @ a/b/g Band
- Dynamic Frequency Selection (DFS)
- Wi-Fi Protected Access Client Support (WPA)
- Transmission Power Control (TPC)
- Multi-country Roaming Support (IEEE802.11d)
- Flexibility: flexible design for embedded system or OEM project

Applications

- Infrastructure Networking
- Embedded system or OEM device

WLM54AG 6B-23 MINIPCI TECHNICAL SPECIFICATIONS

MODEL	WLM54AG 6B-23 (Wireless-superAG)	
CHIPSET	AR5414	
SPEED (max)	108Mbps	
OUTPUT POWER		
802.11a	6-24Mbps	23dBm
	36Mbps	22dBm
	48Mbps	19dBm
	54Mbps	17dBm
802.11b	1-11Mbps	23dBm
802.11g	6-24Mbps	23dBm
	36Mbps	22dBm
	48Mbps	19dBm
	54Mbps	17dBm
POWER CONSUMPTION		
	2.5W	
STANDARDS		
IEEE 802.11a:	54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 9Mbps, 6Mbps	
IEEE 802.11b:	11Mbps, 5.5Mbps, 2Mbps, 1Mbps	
IEEE 802.11g:	54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 9Mbps, 6Mbps, automatically fallback to 5.5Mbps, 2Mbps, 1Mbps	
Super-AG	108Mbps, 96Mbps, 72Mbps, 54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 9Mbps, 6Mbps	
FREQUENCY RANGE		
IEEE 802.11b/g	2.412GHz ~ 2.462GHz (US & Canada)	
	2.412GHz ~ 2.472GHz (Europe)	
	2.412GHz ~ 2.484GHz (Japan)	
IEEE 802.11a	5.15~5.35GHz, 5.725~5.850GHz (US & Canada)	
	5.15~5.35GHz, 5.47~5.725GHz (Europe)	
	4.90~5.00GHz, 5.03~5.091GHz, 5.15~5.25GHz (Japan)	
NETWORK INTERFACE		
PCI interface v2.3 (Type III-B Mini PCI form factor)		
ANTENNA CONNECTOR		
Two antenna connectors (U.FL)		
MODULATION TECHNIQUES		
OFDM and DSSS		
OFDM: BPSK, QPSK, 16 QAM, 64QAM		
DSSS: DBPSK, DQPSK, CCK		
RECEIVER SENSITIVITY		
802.11a	-90 dBm @ 6Mbps,	-70 dBm @ 54Mbps
802.11b	-92 dBm @ 1Mbps,	-87 dBm @ 11Mbps
802.11g	-90 dBm @ 6Mbps,	-70 dBm @ 54Mbps
OPERATING CHANNELS		
US and Canada	11 Channels	
Europe	13 Channels	
Japan	14 Channels	
SECURITY		
64/128 Bit WEP, WPA/WPA2 , IEEE802.1X Authentication		
CERTIFICATE		
FCC, CE		
RoHS COMPLIANCE		
Yes		
ENVIRONMENTAL SPECIFICATIONS		
Temperature	Operating -20°C to 70°C	
	Storage -65°C to 100°C	
Humidity	Operating 5% to 95% (non-condensing)	
DIMENSIONS & WEIGHT		
Dimensions	6.0cm x 4.5cm (L x B)	
Weight	20 grams	

Compex Systems Pte Ltd
135 Joo Seng Road,
#08-01
PM Industrial Building
Singapore 368363

tel: (65) 6288 8220
fax: (65) 6280-9947
www.compex.com.sg

Compex Inc, USA.
840 Columbia Street,
Suite B Brea. CA 92821

tel: (714) 482 0333
fax: (714) 482-0332
www.cpx.com

