

## WR SERIES 0.50mm LOW PROFILE SMT PCB CONNECTORS

- For connection between parallel boards spaced 4 to 9mm
- Ribbon type contacts ensure reliable electrical continuity, resisting twisting force of coupling
- PCB area beneath insulator may be used for circuit traces
- Current Rating: 0.3Amps
- Operating Temperature: -40° to +85°C
- For use in applications that require boards to be stacked

For quantities of 500 and up, call for quote.

MOUSER STOCK NO.	JAE Part No.	Fig.	Pos.	Description	Price Each			
					1	10	50	100
<a href="#">656-WR-50S-VF-1</a>	WR-50S-VF-1	C	50	Receptacle, 4mm height	6.38	5.93	4.79	3.42
<a href="#">656-WR-80S-VF-1</a>	WR-80S-VF-1	C	80	Receptacle, 4mm height	9.49	8.81	7.12	5.09
<a href="#">656-WR-120S-VF-1</a>	WR-120S-VF-1	C	120	Receptacle, 4mm height	13.72	12.74	10.29	7.35
<a href="#">656-WR-160SB-VF-1</a>	WR-160SB-VF-1	C	160	Receptacle, 4mm height	18.26	16.95	13.69	9.78
<a href="#">656-WR-50P-VF-1</a>	WR-50P-VF-1	D	50	Plug, 4mm height	6.38	5.93	4.79	3.42
<a href="#">656-WR-80P-VF-1</a>	WR-80P-VF-1	D	80	Plug, 4mm height	9.49	8.81	7.12	5.09
<a href="#">656-WR-120P-VF-1</a>	WR-120P-VF-1	D	120	Plug, 4mm height	13.72	12.74	10.29	7.35
<a href="#">656-WR-160PB-VF50-1</a>	WR-160PB-VF50-1	D	160	Plug, 5mm height	18.26	16.95	13.69	9.78

[www.DataSheet4U.com](http://www.DataSheet4U.com)

