


# Power Metal Strip® Resistors, High Power, Surface-Mount, 4-Terminal



## FEATURES

- 4-terminal design
- All welded construction of the Power Metal Strip® resistors are ideal for all types of current sensing, voltage division, and pulse applications
- Proprietary processing technique produces low resistance values
- Solid metal nickel-chrome and manganese-copper alloy resistive element with low TCR (< 20 ppm/°C)
- Sulfur resistance by construction that is unaffected by high sulfur environments
- Very low inductance 0.5 nH to 5 nH
- Low thermal EMF (< 3 μV/°C)
- AEC-Q200 qualified <sup>(1)</sup>
- PATENT(S): [www.vishay.com/patents](http://www.vishay.com/patents)
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)

AUTOMOTIVE GRADE


**RoHS\***  
Available

**HALOGEN FREE**  
Available

**GREEN [5-2008]**  
Available

## LINKS TO ADDITIONAL RESOURCES



3D Models



Design Tools



Videos



Calculators

## Notes

- \* This datasheet provides information about parts that are RoHS-compliant and / or parts that are non-RoHS-compliant. For example, parts with lead (Pb) terminations are not RoHS-compliant. Please see the information / tables in this datasheet for details
- <sup>(1)</sup> Flame retardance test may not be applicable to some resistor technologies

## STANDARD ELECTRICAL SPECIFICATIONS

| GLOBAL MODEL | SIZE | POWER RATING<br>$P_{70^\circ\text{C}}$<br>W | TOLERANCE<br>± % | RESISTANCE VALUE RANGE <sup>(1)</sup><br>Ω | WEIGHT (typical)<br>g/1000 pieces |
|--------------|------|---|------------------|--|-----------------------------------|
| WSKW0612     | 0612 | 1.0   | 1.0, 5.0         | 0.5m to 5m                                 | 8.5                               |

## Notes

- Qualified to AEC-Q200 rev. D
- <sup>(1)</sup> Other values may be available, contact factory

## GLOBAL PART NUMBER INFORMATION

Global Part Numbering Example: WSKW06121L000FEA (visit [www.vishay.net](http://www.vishay.net) Vishay Dale parts numbering manual for all options)

W S K W 0 6 1 2 1 L 0 0 0 F E A

GLOBAL MODEL  
(8 digits)  
**WSKW0612**

RESISTANCE VALUE <sup>(1)</sup>  
(5 digits)  
L = mΩ  
L5000 = 0.0005 Ω  
5L000 = 0.005 Ω

TOLERANCE CODE  
(1 digit)  
F = ± 1.0 %  
J = ± 5.0 %

PACKAGING CODE <sup>(2)</sup>  
(2 digits)  
EA = lead (Pb)-free, tape / reel  
EK = lead (Pb)-free, bulk

**SPECIAL** <sup>(3)</sup>  
(up to 2 digits)  
(dash number)  
from 1 to 99 as applicable

## Notes

- Per PCN-DR-00009-2022-REV-0, WSL marking will be removed effective March 1st, 2023
- <sup>(1)</sup> WSL marking ([www.vishay.com/doc?30327](http://www.vishay.com/doc?30327))
- <sup>(2)</sup> Packaging code: EB (lead (Pb)-free) are non-standard packaging codes designating 1000 piece reels. These non-standard packaging codes are identical to our standard EA (lead (Pb)-free), except that they have a package quantity of 1000 pieces
- <sup>(3)</sup> Follow link for customization capabilities: [www.vishay.com/doc?48163](http://www.vishay.com/doc?48163)


PATENT(S): [www.vishay.com/patents](http://www.vishay.com/patents)

This Vishay product is protected by one or more United States and international patents.

| TECHNICAL SPECIFICATIONS  |        |                                  |
|---|--------|----------------------------------|
| PARAMETER   | UNIT   | RESISTOR CHARACTERISTICS         |
| Component temperature coefficient (including terminal) <sup>(1)</sup><br>TCR measured from -55 °C to 150 °C | ppm/°C | -300 / +50 for 0.5 mΩ to 0.99 mΩ |
|   |        | ± 150 for 1 mΩ and 2 mΩ          |
|   |        | ± 75 for 3 mΩ to 5 mΩ            |
| Element TCR <sup>(2)</sup>  | ppm/°C | < 20                             |
| Operating temperature range   | °C     | -65 to +170                      |
| Maximum working voltage <sup>(3)</sup>  | V      | $(P \times R)^{1/2}$             |

**Notes**


- (1) Component TCR - total TCR that includes the TCR effects of the resistor element and the copper terminal
- (2) Element TCR - only applies to the alloy used for the resistor element
- (3) Maximum working voltage - the WSL is not voltage sensitive, but is limited by power / energy dissipation and is also not ESD sensitive

**DIMENSIONS**

**Note**


- Surface-mount solder profile recommendations: [www.vishay.com/doc?31052](http://www.vishay.com/doc?31052)

| MODEL    | DIMENSIONS in inches (millimeters) |                                 |                                  |                                  |                                 |                                 |
|----------|------------------------------------|---------------------------------|----------------------------------|----------------------------------|---------------------------------|---------------------------------|
|          | L                                  | W                               | H                                | T                                | A                               | B                               |
| WSKW0612 | 0.060 ± 0.010<br>(1.50 ± 0.254)    | 0.120 ± 0.010<br>(3.05 ± 0.254) | 0.018 ± 0.010<br>(0.457 ± 0.254) | 0.015 ± 0.010<br>(0.381 ± 0.254) | 0.020 ± 0.005<br>(0.51 ± 0.127) | 0.020 ± 0.005<br>(0.51 ± 0.127) |


| MODEL    | SOLDER PAD DIMENSIONS in inches (millimeters) |              |               |               |              |
|----------|---|--------------|---------------|---------------|--------------|
|          | a   | b            | c             | d             | l            |
| WSKW0612 | 0.040 (1.01)                                  | 0.135 (3.43) | 0.030 (0.762) | 0.015 (0.381) | 0.030 (0.76) |

**4 TERMINAL KELVIN CONNECTIONS**

**Notes**

- E1 and E2: voltage sense connection
- I1 and I2: current connection

**CONSTRUCTION OUTLINE**

**Notes**

1. Resistive element
2. Terminal: solid copper and element with 100 % Sn finish
3. Terminal to element weld
4. Laser calibration
5. High temperature encapsulant: siliconized polyester coating material

**DERATING**

**PULSE CAPABILITY**

[www.vishay.com/en/resistors/joulewizard/](http://www.vishay.com/en/resistors/joulewizard/)

| PERFORMANCE               |   |             |              |
|---------------------------|---|-------------|--------------|
| TEST                      | CONDITIONS OF TEST  | TEST LIMITS | TYPICAL      |
| Thermal shock             | -55 °C to +150 °C, 1000 cycles, 15 min at each extreme  | ± 1.0 %     | 0.20 %       |
| Short time overload       | Refer to link for short time overload performance and pulse capability;<br><a href="http://www.vishay.com/en/resistors/power-metal-strip-calculator/">www.vishay.com/en/resistors/power-metal-strip-calculator/</a> | ± 1.0 %     | 0.20 %       |
| Low temperature storage   | -65 °C for 24 h   | ± 0.5 %     | 0.1 % (24 h) |
| High temperature exposure | 2000 h at +170 °C   | ± 1.0 %     | ± 0.2 %      |
| Bias humidity             | +85 °C, 85 % RH, 10 % bias, 1000 h  | ± 0.5 %     | 0.20 %       |
| Mechanical shock          | 100 g's for 6 ms, 5 pulses  | ± 0.5 %     | 0.01 %       |
| Vibration                 | Frequency varied 10 Hz to 2000 Hz in 1 min, 3 directions, 12 h  | ± 0.5 %     | 0.01 %       |
| Load life                 | 2000 h at +70 °C, 1.5 h "ON", 0.5 h "OFF"   | ± 1.0 %     | -0.20 %      |
| Resistance to solder heat | +260 °C solder, 10 s to 12 s dwell, 25 mm/s emergence   | ± 0.5 %     | 0.05 %       |
| Moisture resistance       | MIL-STD-202, method 106, 0 % power, 7b not required   | ± 1.0 %     | 0.01 %       |

**Note**

- Contact [ww2bresistors@vishay.com](mailto:ww2bresistors@vishay.com) for application specific performance requirements or qualification data. Typical performance is better than stated test limits


| PACKAGING (1) |                         |             |             |      |
|---------------|-------------------------|-------------|-------------|------|
| MODEL         | REEL                    |             |             |      |
|               | TAPE WIDTH              | DIAMETER    | PIECES/REEL | CODE |
| WSKW0612      | 8 mm / embossed plastic | 178 mm / 7" | 4000        | EA   |

**Notes**

- Embossed carrier tape per EIA-481
- (1) Additional packaging details at [www.vishay.com/doc?20051](http://www.vishay.com/doc?20051)



REEL ORIENTATION



| LINKS TO RELATED DOCUMENTS                                |  |
|---|--|
| <b>SELECTOR GUIDE</b>                                     |  |
| Overview of Automotive Grade Products                     | <a href="http://www.vishay.com/doc?49924">www.vishay.com/doc?49924</a> |
| <b>TECHNICAL NOTES</b>                                    |  |
| SMD Current Sense: AEC-Q200 vs. Vishay Qualification      | <a href="http://www.vishay.com/doc?30416">www.vishay.com/doc?30416</a> |
| MIL-PRF vs. AEC-Q200: Do You Know What You Are Getting?   | <a href="http://www.vishay.com/doc?11000">www.vishay.com/doc?11000</a> |
| <b>WHITE PAPER</b>  |  |
| Thermal Management for Surface-Mount Devices              | <a href="http://www.vishay.com/doc?30380">www.vishay.com/doc?30380</a> |
| Temperature Coefficient of Resistance for Current Sensing | <a href="http://www.vishay.com/doc?30405">www.vishay.com/doc?30405</a> |



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.