

General Description

The WSR80N08 is the highest performance trench N-ch MOSFET with extreme high cell density, which provide excellent $R_{DS(on)}$ and gate charge for most of the synchronous buck converter applications.

The WSR80N08 meet the RoHS and Green Product requirement, 100% EAS guaranteed with full function reliability approved.

Features

- Advanced high cell density Trench technology
- Super Low Gate Charge
- Excellent CdV/dt effect decline
- 100% EAS Guaranteed
- Green Device Available



Product Summary

BV_{DSS}	$R_{DS(on)}$	I_D
80V	8.4m Ω	80A

Applications

- Power Management
- DC/DC Converter
- Load Switch

TO-220-3L Pin Configuration



Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	80	V
V_{GS}	Gate-Source Voltage	± 20	V
I_D	$T_C = 25^\circ\text{C}$, Continuous Drain Current. Lead current limit.	80	A
I_{DM}	$T_C = 25^\circ\text{C}$, pulse width limited by T_{JM}	75	A
I_{AR}	$T_C = 25^\circ\text{C}$, Avalanche Current.	320	A
E_{AR}	$T_C = 25^\circ\text{C}$, Single Pulse Avalanche Energy ³	30	mJ
E_{AS}	$T_C = 25^\circ\text{C}$, Single Pulse Avalanche Energy ³	1.0	J
P_D	$T_C = 25^\circ\text{C}$, Total Power Dissipation ⁴	230	W
T_J	Operating Junction Temperature Range	-55 to 175	$^\circ\text{C}$
T_{JM}	Storage Temperature Range	-55 to 175	$^\circ\text{C}$
T_J	MAX Junction Temperature Range	175	$^\circ\text{C}$
$R_{\theta JA}$	Thermal Resistance Junction-Ambient ¹	62	$^\circ\text{C/W}$
$R_{\theta JC}$	Thermal Resistance Junction-Case ¹	0.65	$^\circ\text{C/W}$

Electrical Characteristics (T_J=25 °C, unless otherwise noted)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250uA	80	---	---	V
ΔBV _{DSS} /ΔT _J	BV _{DSS} Temperature Coefficient	Reference to 25°C, I _D =1mA	---	0.096	---	V/°C
R _{DS(ON)}	Static Drain-Source On-Resistance ²	V _{GS} =10V, I _D =40A.	---	8.4	9.5	mΩ
V _{GS(th)}	Gate Threshold Voltage	V _{GS} =V _{DS} , I _D =250uA	2.0	3	4.0	V
ΔV _{GS(th)}	V _{GS(th)} Temperature Coefficient		---	-5.5	---	mV/°C
I _{DSS}	Drain-Source Leakage Current	V _{DS} =55V, V _{GS} =0V, T _J =25°C	---	---	50	uA
		V _{DS} =55V, V _{GS} =0V, T _J =85°C	---	---	1000	
I _{GSS}	Gate-Source Leakage Current	V _{GS} =±20V, V _{DS} =0V	---	---	±100	nA
g _{fs}	Forward Transconductance	V _{DS} =10V, I _D =40A	35	55	---	S
R _g	Gate Resistance	V _{DS} =0V, V _{GS} =0V, f=1MHz	---	1.8	3.8	Ω
Q _g	Total Gate Charge (10V)	V _{DS} =60V, V _{GS} =10V, I _D =40A.	---	180	---	nC
Q _{gs}	Gate-Source Charge		---	42	---	
Q _{gd}	Gate-Drain Charge		---	75	---	
T _{d(on)}	Turn-On Delay Time	V _{DS} =60V, V _{GS} =10V, R _G =2.5Ω, I _D =40A.	---	50	---	ns
T _r	Rise Time		---	75	---	
T _{d(off)}	Turn-Off Delay Time		---	31	---	
T _f	Fall Time		---	95	---	
C _{iss}	Input Capacitance	V _{DS} =25V, V _{GS} =0V, f=1MHz	---	4800	---	pF
C _{oss}	Output Capacitance		---	1670	---	
C _{rss}	Reverse Transfer Capacitance		---	590	---	

Diode Characteristics(T_J = 25°C, unless otherwise specified)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I _S	Continuous Source Current ^{1,6}	V _{GS} =0V,	---	---	80	A
I _{SM}	Pulsed Source Current ^{2,6}	pulse width limited by T _{JM}	---	---	320	A
V _{SD}	Diode Forward Voltage ²	V _{GS} =0V, I _S =I _F . Note2	---	---	1.5	V
t _{rr}	Reverse Recovery Time	I _F =25A, d _i /d _t =100A/μs.	---	200	---	nS
Q _{rr}	Reverse Recovery Charge		---	500	---	nC

Note :

1. The data tested by surface mounted on a 1 inch² FR-4 board with 20Z copper, t_c≤10sec.
2. The data tested by pulsed, pulse width ≤ 300us, duty cycle ≤ 2%
3. The EAS data shows Max. rating. The test condition is V_{DS}=25V, V_{GS}=10V, L=0.1mH, I_{AS}=25A
4. The power dissipation is limited by 150°C junction temperature
5. The Min. value is 100% EAS tested guarantee.
6. The data is theoretically the same as I_D and I_{DM}, in real applications, should be limited by total power dissipation.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance




Figure 4. On-Resistance Variation with Temperature




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Body Diode Forward Voltage Variation with Source Current

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7. Gate Charge




Figure 8. Maximum Safe Operating Area





Figure 9. Normalized Thermal Transient Impedance Curve

Packaging information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	4.470	4.670	0.176	0.184
A1	2.520	2.820	0.099	0.111
b	0.710	0.910	0.028	0.036
b1	1.170	1.370	0.046	0.054
c	0.310	0.530	0.012	0.021
c1	1.170	1.370	0.046	0.054
D	10.010	10.310	0.394	0.406
E	8.500	8.900	0.335	0.350
E1	12.060	12.460	0.475	0.491
e	2.540 TYP		0.100 TYP	
e1	4.980	5.180	0.196	0.204
F	2.590	2.890	0.102	0.114
h	0.000	0.300	0.000	0.012
L	13.400	13.800	0.528	0.543
L1	3.560	3.960	0.140	0.156
Φ	3.735	3.935	0.147	0.155

Attention

- 1, Any and all Winsok power products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your Winsok power representative nearest you before using any Winsok power products described or contained herein in such applications.
- 2, Winsok power assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all Winsok power products described or contained herein.
- 3, Specifications of any and all Winsok power products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- 4, Winsok power Semiconductor CO., LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- 5, In the event that any or all Winsok power products (including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- 6, No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of Winsok power Semiconductor CO., LTD.
- 7, Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. Winsok power believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- 8, Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the Winsok power product that you intend to use.
- 9, this catalog provides information as of Sep. 2014. Specifications and information herein are subject to change without notice.