



**RoHS 2002/95/EC Compliant****Thermoelectric Cooler XLT2419****Performance Values**

Hot Side Temperature (°C)	27°C	50°C
ΔT_{max} (°C-dry N ₂):	56.5	64.0
Q _{max} (watts):	72	79
I _{max} (amps):	13.9	13.8
V _{max} (vdc):	8.0	8.8
AC Resistance (ohms):	0.47	---

**Mechanical Characteristics****Ordering Options**

Model Number	Description
XLT2419-03AC	Leadwires
XLT2419-04AC	No Leadwires
XLT2419-05AC	Leadwires, Diced
XLT2419-07AC	Leadwires, Sealed
XLT2419-08AC	Leadwires 8 inches long

Features

- **RoHS 2002/95/EC compliant**
- Specifically designed for thermal cycling applications
- Capable of rapid heating and cooling rates
- Proven High Reliability (Data available upon request)
- Rugged construction
- Porched configuration for enhanced leadwire strength
- Rated operating temperature of 150°C
- Height tolerance of ± .001 in. (± .025 mm) allows for multiple module applications
- RTV sealing available





Performance Curves

Environment: One atmosphere dry nitrogen

Hot Side Temperature: 27°C
 TA(C) = 27

Hot Side Temperature 50°C
 TA(C) = 50



For performance information in a vacuum or with hot side temperatures other than 27°C or 50°C, consult one of our Applications Engineers.

Installation

XLT coolers are typically mounted under compression using thermal grease or flexible graphite products. Consult Marlow Industries' Thermoelectric Installation Guide for more details. For additional information, please contact one of our application engineers for technical support.

Addresses

Marlow Industries, Inc.
 10451 Vista Park Road
 Dallas Texas 75238-1645
 214-340-4900 (tel)
 214-341-5212 (fax)
www.marlow.com

Marlow Industries Europe
 Aberdeen House, South Road
 Haywards Heath
 West Sussex RH164NG UK
 +44 (0)1444-443404 (tel)
 +44 (0)1444-443334(fax)

Marlow Industries Japan
 1-1-8-401
 Uehara, Shibuya-ku
 Tokyo, Japan 151-0064
 +81 (3) 5454-5280 (tel)
 +81 (3) 5454-5281(fax)