Product data sheet Characteristics

XPSAK311144

module XPSAK - Emergency stop - 24 V AC DC



Main

Main	
Range of product	Preventa Safety automation
Product or component type	Preventa safety module
Safety module name	XPSAK
Safety module application	For emergency stop, switch, sensing mat/edges or safety light curtain monitoring
Function of module	Monitoring of electro-sensitive protection equipment (ESPE) Monitoring of a movable guard associated with 2 switches and automatic start Monitoring of a movable guard Emergency stop monitoring 1-channel wiring Emergency stop with 2 NC contacts monitoring 2-channel wiring Multiple emergency stop monitoring 2-channel wiring Proximity sensor monitoring Sensing mat and edges monitoring
Safety level	Can reach SILCL 3 conforming to EN/IEC 62061 Can reach PL e/category 4 conforming to EN/ISO 13849-1
Safety reliability data	PFHd = 7.39E-9 1/h conforming to EN/IEC 62061 MTTFd = 154.5 years conforming to EN/ISO 13849-1 DC > 99 % conforming to EN/ISO 13849-1
Type of start	Configurable
Connections - terminals	Captive screw clamp terminals (2 x 0.52 x 1.5 mm²)flexible cable with cable end, with double bezel Captive screw clamp terminals (2 x 0.252 x 1 mm²)flexible cable with cable end, with double bezel Captive screw clamp terminals (2 x 0.142 x 0.75 mm²)solid cable with cable end, with double bezel Captive screw clamp terminals (2 x 0.142 x 0.75 mm²)sflexible cable with cable end, with double bezel Captive screw clamp terminals (1 x 0.251 x 2.5 mm²)flexible cable with cable end, with double bezel Captive screw clamp terminals (1 x 0.251 x 1.5 mm²)flexible cable with cable end, with double bezel Captive screw clamp terminals (1 x 0.141 x 2.5 mm²)solid cable with cable end, with double bezel Captive screw clamp terminals (1 x 0.141 x 2.5 mm²)flexible cable with cable end, with double bezel Captive screw clamp terminals (1 x 0.141 x 2.5 mm²)flexible cable with cable end, with double bezel
Output type	Relay instantaneous opening 3 NO, volt-free
Number of additional circuits	1 NC + 4 solid state outputs
[Us] rated supply voltage	24 V DC (- 1510 %) 24 V AC (- 1510 %)

Complementary

Synchronisation time between inputs	2 or 4 s depending of wiring (automatic start) Unlimited (manual start)	
Supply frequency	50/60 Hz	
Power consumption in VA	<= 5 VA AC	
Input protection type	Internal, electronic	
Control circuit voltage	24 V DC	
Line resistance	28 Ohm	
Breaking capacity	C300: 1800 VA, AC-15 (inrush) for relay output C300: 180 VA, AC-15 (holding) for relay output	

Breaking capacity	1.5 A at 24 V (DC-13) time constant: 50 ms for relay output
Output thermal current	6 A per relay for relay output
[lth] conventional free air thermal current	18 A
Associated fuse rating	6 A fuse type fast blow for relay output conforming to EN/IEC 60947-5-1, DIN VDE 0660 part 200 4 A fuse type gG or gL for relay output conforming to EN/IEC 60947-5-1, DIN VDE 0660 part 200
Minimum output current	10 mA for relay output
Minimum output voltage	17 V for relay output
Response time on input open	<= 40 ms
[Ui] rated insulation voltage	300 V (degree of pollution: 2) conforming to IEC 60647-5-1, DIN VDE 0110 part 1
[Uimp] rated impulse withstand voltage	4 kV overvoltage category III conforming to IEC 60647-5-1, DIN VDE 0110 part 1
Local signalling	4 LEDs
Current consumption	30 mA at 24 V AC (on power supply)
Mounting support	35 mm symmetrical DIN rail
Product weight	0.3 kg

Environment


Standards	EN 1088/ISO 14119 EN/IEC 60204-1 EN/IEC 60947-5-1	
	EN/ISO 13850	
Product certifications	CSA TÜV UL	
IP degree of protection	IP40 (enclosure) conforming to EN/IEC 60529 IP20 (terminals) conforming to EN/IEC 60529	
Ambient air temperature for operation	-1055 °C	
Ambient air temperature for storage	-2585 °C	



Product data sheet Dimensions Drawings

XPSAK311144

Dimensions



XPSAK311144

Wiring Diagrams

Refer to the Instruction Sheet

To download the instruction sheet, follow below procedure:



- Click on Download & Documents.
- 2 Click on Instruction sheet.