


**NOTES:**

1. MATERIALS:  
 HOUSING: HIGH TEMP. THERMOPLASTIC, BLACK, UL 94V-0  
 CONTACTS: 0.014 INCHES (0.35 MILLIMETERS) THICK PHOSPHOR BRONZE PLATED WITH 150 MICROINCHES (3.81 MICROMETERS) MINIMUM THICK TIN LEAD IN SOLDER AREA. 15 MICROINCHES (0.38 MICROMETERS) MINIMUM GOLD IN LOCALIZED PLATE AREA. ENTIRE CONTACTS PLATED WITH 50 MICROINCHES (1.27 MICROMETERS) MINIMUM THICK NICKEL.  
 SHIELDED: 0.0098 INCHES (0.25 MILLIMETERS) THICK COPPER ZINC ALLOY PLATED WITH 30 MICROINCHES (0.762 MICROMETERS) MINIMUM THICK NICKEL
2. JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS PART 68, SUBPART F
3. PART NUMBER: XRJD-S-21-8-8-X  
 REFER TO LED OPTIONS TABLE FOR ORDERING CODES
4. UNSPECIFIED TOLERANCE: .XX ±0.25[0.010]  
 .X ±0.30[0.012]

<b>XMULTIPLE</b>				CONNECTING THE INFORMATION AGE
MULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu Chiu, Taipei 114, Taiwan 11475		MULTIPLE USA 1402 Los Angeles Ave., Suite G, Simi Valley, CA 93065		CUSTOMER/NO:
THIS DRAWING IS A CONTROLLED DOCUMENT.				DWG NO: XRJD-S-21-8-8-X
TITLE: Stacked RJ45 Connectors, W/LED, 8P, 8C, Shielded, Thru Hole, 2 Piece Structure				DRAWN: LEON
PART NO: XRJD-S-21-8-8-X		CHKD: JEFF		
		DIMENSIONS mm[inch ]	SHEET 1 of 1	REV S01
				DATE: 12/04/05

# XMULTIPLE

CONNECTING  
THE INFORMATION  
AGE

## LED COLOR OPTION TABLE

LED CODE	LEFT LED #2	RIGHT LED #1	LED CODE	LEFT LED #2	RIGHT LED #1	LED CODE	LEFT LED #2	RIGHT LED #1	LED CODE	LEFT LED #2	RIGHT LED #1
0	BK	BK	A	GR/YE	GR/YE	L	GR/YE	RD/GR	W8	RD	GR
1	YE	GR	B	RD/GR	RD/GR	M	RD	YE	W11	GR	RD
2	BK	GR	C	RD/GR	GR/YE	N	GR/OR	YE	W18	BL/GR	RD
3	GR	BK	D	GR	GR/YE	P	OR/GN	YE			
4	GR	YE	E	YE	GR/YE	Q	GR	YE/GR			
5	GR	GR	F	OR	GR	R	GR	GR/OR			
6	YE	YE	G	GR/OR	GR/OR	T	RD	RD			
7	OR/GR	OR/GR	H	GR/YE	GR	V	YE/GR	GR			
8	YE/GR	YE/GR	J	RD/GR	YE	Y	GR/OR/YE	YE			
9	RD	BK	K	YE	OR/GR	Z	REFER TO DRAWING				

BK = Blocked

YE = Yellow

GR = Green

OR = Orange

RD = Red

BL = Blue

Xmultiple USA, 1420 Los Angeles Avenue, Suite G, Simi Valley, CA 93065 Tel: (805) 579-1100, Fax: (805) 579-7800  
Xmultiple ASIA, 4F, No. 347, Yang Guang Street, Neihu Chiu, Taipei 11475, Taiwan 886-2-2658-2298, Fax: 886-2-2627-8659

REV 2005-A (1-03-05)