


## P-Channel Enhancement Mode Field Effect Transistor



### Feature

- $V_{DS} = -20V, I_D = -3.4A$
- $R_{DS(ON)} < 64m\Omega @ V_{GS} = -4.5V$
- $R_{DS(ON)} < 89m\Omega @ V_{GS} = -2.5V$
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level1
- High density cell design for low  $R_{DS(ON)}$
- High Speed switching
- Rugged and reliable
- SOT-23 Package

### Application

- Battery protection
- Load switch
- Power management

### ■ Maximum Ratings (TA=25°C unless otherwise noted)

Symbol	Parameter	Value	Unit
$V_{DS}$	Drain-source Voltage	-20	V
$V_{GS}$	Gate-source Voltage	$\pm 10$	V
$I_D$	Drain Current	-3.4	A
$P_D$	Total Power Dissipation	1	W
$R_{thJA}$	Thermal Resistance From Junction To Ambient	125	°C/W
$T_J$	Operation Junction Temperature	-55~+150	°C
$T_{STG}$	Storage Temperature	-55~+150	°C

### ■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	Marking	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
YJL2301C	F2		3000	30000	120000	7" reel



# YJL2301C

## ■ Electrical Characteristics (TA=25°C unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
<b>Static Characteristics</b>						
Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=-250\mu A$	-20			V
Zero gate voltage drain current	$I_{DSS}$	$V_{DS}=-20V, V_{GS}=0V$			-1	$\mu A$
Gate-body leakage current	$I_{GSS}$	$V_{GS}=\pm 10V, V_{DS}=0V$			$\pm 100$	nA
Gate threshold voltage*	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=-250\mu A$	-0.4	-0.7	-1.0	V
Drain-source on-resistance*	$R_{DS(on)}$	$V_{GS}=-4.5V, I_D=-3.4A$		49	64	m $\Omega$
		$V_{GS}=-2.5V, I_D=-3.0A$		59	89	
Forward Transconductance	$g_{FS}$	$V_{DS}=-5V, I_D=-3.4A$	5			s
<b>Dynamic Characteristics **</b>						
Input Capacitance	$C_{iss}$	$V_{DS}=-10V, V_{GS}=0V, f=1MHz$		478		pF
Output Capacitance	$C_{oss}$			81		
Reverse Transfer Capacitance	$C_{rss}$			52		
<b>Switching Characteristics**</b>						
Turn-on delay time	$t_{d(on)}$	$V_{DD}=-10V, V_{GS}=-4.5V, R_L=2.8\Omega, I_D=-1A, R_{GEN}=6\Omega$		12		ns
Turn-on rise time	$t_r$			54		
Turn-off delay time	$t_{d(off)}$			15		
Turn-off Fall time	$t_f$			9		
Total Gate Charge	$Q_g$	$V_{DS}=-10V, I_D=-3.4A, V_{GS}=-4.5V$		4.3		nC
Gate-Source Charge	$Q_{gs}$			0.8		
Gate-Drain Charge	$Q_{gd}$			1.1		
<b>Source-Drain Diode characteristics</b>						
Drain-Source Diode Forward Current	$I_S$				-3.4	A
Diode Forward voltage	$V_{SD}$	$V_{GS}=0V, I_S=-3.4A$		-0.8	-1.2	V

Notes:

\*Pulse Test: Pulse Width  $\leq 300\mu A$ , Duty Cycle  $\leq 2\%$ .

\*\*These parameters have no way to verify.



## ■ Characteristics (Typical)




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance




Figure 4. On-Resistance Variation with Temperature




Figure 5. Gate Threshold Variation with Temperature






Figure 6. Body Diode Forward Voltage Variation with Source Current




# YJL2301C

## ■ SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°		8°	

## ■ SOT-23 Suggested Pad Layout



Note:  
 1. Controlling dimension: in millimeters.  
 2. General tolerance:  $\pm 0.05\text{mm}$ .  
 3. The pad layout is for reference purposes only.



## Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.