



IC301: YM3404DF or YM3619DF (16 bit over sampling digital filter)

● YM3404DF



● YM3619DF



YM3619 Pin No.	YM3404 Pin No.	Pin-Name	I/O	Function
11	7	SDI	I	Encoded digital signal serial input
10	6	SDSY	I	Distinction between Lch and Rch, Data input timing
8	5	BCI	I	Bit clock input for input data
4	3	XI	I	Clock OSC. 196 fs = 17.2872MHz or 192 fs = 16.9344 MHz
3	2	XO	O	
22	14	ST	I	1DAC = "L" 2DAC = "H" Switch input
23	15	FEN	I	System clock switch input 196 fs = "L" 192 fs = "H"
13	9	DLO	O	1DAC: L, Rch Data input 2DAC: Lch Data input
14	10	DRO	O	Rch Data output
15	11	WCO	O	Word clock for output data (DLO, DRO)
17	12	BCO	O	Bit clock for output data and system clock output for SPC II 98 fs = 8.6436MHz or 96 fs = 8.4672MHz
2	1	SHL	O	1DAC: Lch deglitch signal output 2DAC: L, Rch deglitch signal output
24	16	SHR	O	1 DAC: Rch deglitch signal output
12	8	VDD <sub>1</sub>		Power supply +5V for digital signal
5	4	VDD <sub>2</sub>		Power supply for clock and deglitch signal
20	13	VSS		GND