

# High IP3 Low Noise Amplifier

50Ω 1400 to 2300 MHz

**NEW!**

**ZRL-2300**



**BLUE CELL™**

CASE STYLE: FJ893  
PRICE: \$119.95 ea. QTY (1-9)

## Maximum Ratings

Operating Temperature	-40°C to 80°C case -40°C to 60°C ambient
Storage Temperature	-55°C to 100°C
DC Voltage	+17V max.


## Features

- high IP3, +46 dBm typ.
- low noise figure, 2.5 dB typ.
- broadband flat gain response
- internal voltage regulated
- over voltage and transient protected

## Applications

- high dynamic range
- PCS, UMTS, GSM, cellular, wireless data
- defense and satellite communications
- high linearity driver amplifier

## Outline Drawing



## Outline Dimensions (inch / mm)

A	B	C	D	E	F	G	H	J
2.00	3.75	.80	3.00	.19	3.374	1.624	.156	.44
50.80	95.25	20.32	76.20	4.83	85.70	41.25	3.96	11.18
K	L	M	N	P	Q	R	S	wt.
.26	1.00	.51	.22	.26	—	.19	.10	grams
6.60	25.40	12.95	5.59	6.60	—	4.83	2.54	135

## Electrical Specifications (T<sub>AMB</sub> = 25°C)

FREQ. RANGE (MHz)	GAIN (dB)		NOISE FIGURE (dB)		MAXIMUM POWER (dBm)			INTERCEPT POINT (dBm)	VSWR (:1)		DIRECTIVITY (dB)	DC POWER	
	Typ.	Min.	Typ.	Max.	Output (1 dB Comp.)	Input (no damage)	IP3 dBm Typ.*		In	Out		Typ.	Volt <sup>1</sup> Typ.
1400-2300	23.5	21	±0.7	±1.0	24.6	23	+10	46	1.20	1.16	21	12	550
1650-2150	24	22	±0.5	±0.8	24.6	23	+10	46	1.20	1.16	20	12	550

\* 1MHz tone spacing

<sup>1</sup> Other voltages available in the 6.5 to 17V range, please contact factory.

