


NPN SILICON PLANAR MEDIUM POWER TRANSISTORS

ZTX454 ZTX455

ISSUE 2 – MARCH 1994

FEATURES

- * 140 Volt V_{CE0}
- * 1 Amp continuous current
- * $P_{tot} = 1$ Watt



E-Line
TO92 Compatible

ABSOLUTE MAXIMUM RATINGS.

| PARAMETER | SYMBOL | ZTX454 | ZTX455 | UNIT |
|--|----------------|-------------|--------|-------------|
| Collector-Base Voltage | V_{CBO} | 140 | 160 | V |
| Collector-Emitter Voltage | V_{CEO} | 120 | 140 | V |
| Emitter-Base Voltage | V_{EBO} | 5 | | V |
| Peak Pulse Current | I_{CM} | 2 | | A |
| Continuous Collector Current | I_C | 1 | | A |
| Power Dissipation at $T_{amb}=25^{\circ}C$ | P_{tot} | 1 | | W |
| Operating and Storage Temperature Range | $T_j; T_{stg}$ | -55 to +200 | | $^{\circ}C$ |

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}C$).


| PARAMETER | SYMBOL | ZTX454 | | ZTX455 | | UNIT | CONDITIONS. |
|---------------------------------------|----------------|------------------|------------|------------|------|--------------------|---|
| | | MIN. | MAX. | MIN. | MAX. | | |
| Collector-Base Breakdown Voltage | $V_{(BR)CBO}$ | 140 | | 160 | | V | $I_C = 100\mu A$ |
| Collector-Emitter Sustaining Voltage | $V_{CEO(sus)}$ | 120 | | 140 | | V | $I_C = 10mA^*$ |
| Emitter-Base Breakdown Voltage | $V_{(BR)EBO}$ | 5 | | 5 | | V | $I_E = 100\mu A$ |
| Collector Cut-Off Current | I_{CBO} | | 0.1 | | 0.1 | μA μA | $V_{CB} = 140V$ $V_{CE} = 120V$ |
| Emitter Cut-Off Current | I_{EBO} | | 0.1 | | 0.1 | μA | $V_{EB} = 4V$ |
| Collector-Emitter Saturation Voltage | $V_{CE(sat)}$ | | 0.7 1.0 | | 0.7 | V | $I_C = 150mA, I_B = 15mA$ $I_C = 200mA, I_B = 20mA$ |
| Static Forward Current Transfer Ratio | h_{FE} | 100 30 10† | 300 | 100 10† | 300 | | $I_C = 150mA, V_{CE} = 10V^*$ $I_C = 200mA, V_{CE} = 1V^*$ $I_C = 1A, V_{CE} = 10V^*$ |
| Transition Frequency | f_T | 100 | | 100 | | MHz | $I_C = 50mA, V_{CE} = 10V$ $f = 100MHz$ |
| Output Capacitance | C_{obo} | | 15 | | 15 | pF | $V_{CB} = 10V, f = 1MHz$ |

* Measured under pulsed conditions. Pulse width=300 μs . Duty cycle $\leq 2\%$

† Typical


ZTX454 ZTX455

TYPICAL CHARACTERISTICS




I_C - Collector Current (Amps)

$V_{CE(sat)}$ v I_C




I_C - Collector Current (Amps)

Typical Switching Speeds




I_C - Collector Current (Amps)

h_{FE} v I_C




I_C - Collector Current (Amps)

$V_{BE(sat)}$ v I_C



I_C - Collector Current (Amps)

$V_{BE(on)}$ v I_C



Safe Operating Area