


## Application:

Handheld POS terminal  
 Handheld logistic terminal  
 Multi-language Translator  
 Children educator  
 Analyzer terminal  
 Scope meter

**Preliminary Release**  
 Contact us for detail information.



## Dimension

Dot size: W0.48 x H0.48 mm  
 Dot pitch: W0.52 x H0.52 mm  
 Active area: W66.52 x H33.24 mm  
 View area: W70.70 x H38.80 mm  
 Outline: W76.10 x H50.60 mm(not includes FPC)  
 Thickness: 1.90 mm

## Benefits:

- Supply voltage 3.3V
- Low current consumption 0.5mA without B/L
- Low profile, light & thin
- Sample available

Pin No.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
Symbol	CS1	RES	Ao	WR(R/W)	RD(E)	D0	D1	D2	D3	D4	D5	D6	D7	V <sub>DD</sub>	V <sub>SS</sub>	V <sub>OUT</sub>	CAP5-
Pin No.	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34
Symbol	VSP3-	CAP1+	CAP1-	CAP2-	CAP2+	CAP4-	VRS	V1	V2	V3	V4	V5	VR	C86	P/S	HPM	IRS

### Head quarters

PowerTip Technology Corporation  
 8, 6th Road, Taichung Industrial Park,  
 Taichung, 407 Taiwan  
 TEL: 886-4-23558168  
 FAX: 886-4-23558166  
 Http://www.powerTip.com.tw  
 E-mail: sales@mail.powerTip.com.tw

### Manufacturing bases

Taiwan LCM factory  
 Taichung Industrial Park,  
 Taichung, Taiwan  
 China LCM factory  
 Dong Keng,  
 Dung Guan, China  
 Taiwan LCD factory  
 Taichung Industrial Park,  
 Taichung, Taiwan  
 China LCD factory  
 Dong Keng,  
 Dung Guan, China

### Abroad contacts

PowerTip Technology Limited  
 Room 02, 9/F, Block A,  
 Po Lung Centre,  
 11 Wang Chiu Road,  
 Kowloon Bay, Kowloon, H.K.  
 TEL: 852-31070920  
 FAX: 852-31070936  
 PowerTip Technology, Inc.  
 18 Technology Drive, Suite 161,  
 Irvine, CA92618, U.S.A.  
 TEL: 1-(949)585-9888  
 FAX: 1-(949)585-9889  
 Http://www.powerTipusa.com  
 E-mail: sales@powerTipusa.com