


1	VSS	12	DB4
2	VDD	13	DB5
3	VO	14	DB6
4	RS	15	DB7
5	R/W	16	CS1
6	E	17	CS2
7	RST	18	CS3
8	DB0	19	CS4
9	DB1	20	VOUT
10	DB2	21	A
11	DB3	22	K

DETAIL A:



NOTES:

1. DISPLAY TYPE: FSTN
2. VIEWING DIRECTION: 6:00
3. POLARIZER MODE: TRANSFLECTIVE/POSITIVE
4. DRIVE METHOD: 1/64 DUTY 1/9 BIAS
5. LCD OPERATING VOLTAGE: 12.6V
6. OPERATING TEMP: -20°C--+70°C
7. STORAGE TEMP: -30°C--+80°C
8. CONTROLLER: S6B0108A01-COCX(KS0108BPCC)
9. BACKLIGHT: LED
10. BEZEL IS PAINTED WITH ZINC
11. UNMARKED TOLERANCES: ±0.3mm
12. WITH ON-BOARD DC-DC CONVERTER AND TEMP COMPENSATION CIRCUIT

CONNECTOR
SAMTEC:BDL-111-G-E



TIAN-MA MICROELECTRONICS CO.

6/F., CASTIC Building, Shennan Road, Central, Shenzhen, China

DRAWN BY:	TITLE: TM128128CCCW7	
CHECKED BY:	DWG NO: G-1	
APPROVED BY:	DWG NAME: TM128128CCCW7E-1	SCALE: mm
CONFIRMED BY:	SHEET NO: OF	