

# DD313-4

---

**Version** : PRE.002  
**Issue Date** : 2015/11/23  
**File Name** : SP-DD313-4-PRE.002.doc  
**Total Pages** : 15

## 40V Adjustable Current Sink Linear LED Driver



新竹市科學園區展業一路9號4樓之3  
SILICON TOUCH TECHNOLOGY INC.

9-4F-3, Prosperity Road I, Science Based Industrial Park,  
Hsin-Chu, Taiwan 300, R.O.C.

Tel : 886-3-5645656 Fax : 886-3-5645626

---

---

## DD313-4

### 40V Adjustable Current Sink Linear LED Driver

#### General Description

The DD313-4 IC is an economical, versatile, and robust device designed to provide cost-effective solution for regulating constant current in applications such as LED lighting over a 4.5 V to 40 V wide range of supply voltage which allows for single supply voltage operation from industry standard 5V, 12 V, 18 V, 24 V, 36 V power rails. The device is designed to operate as a constant current source.

The output current of DD313-4 (up to 120 mA) is set by an external resistor. The output current can be dimmed by digital PWM duty (up to 1 MHz to prevent flickering).

Provision such as an over temperature shutdown/alarm function insures damage avoidance under an overheated operating condition. The LED open detection function is also included to provide fault detection with a fault status reported through open-drain output ALARM pin. The 40 volt high voltage output is implemented to withstand surges common in automobile, industrial, and commercial lighting applications.

The DD313-4 comes with SOT26 thermally robust packages.

#### Features

- Wide operating voltage range with self-bias power supply (4.5 V to 40 V)
- Constant current regulator
  - Low reference voltage ( $V_{SENSE} = 0.65V$ )
  - Integrated MOSFET with on resistance less than  $2.9 \Omega$
  - Output current: 2mA ~ 120 mA
  - Channel current deviation among devices:  $\pm 3\%$
- PWM dimming up to 1 MHz (invisible flickering)
- Voltage surge (40 V) suppressing for LED protection
- Low temperature drift:  $\pm 5\%$  over  $-40^{\circ}C$  to  $+85^{\circ}C$
- High power supply rejection ratio: -64 dB (A/V)
- LED open circuit detection
- Thermal shutdown and pre-thermal warning
- SOT26 thermal robust package

## Application

- General Illumination, Channel Lettering
- Decorative Lighting, Pool Lighting, Landscaping Lighting
- Instrument and Industrial Instrumentation
- White Goods
- Offline LED Luminaries

## Absolute Maximum Ratings

Over operating free-air temperature range (unless otherwise noted)<sup>1</sup>

CHARACTERISTIC	SYMBOL	MIN	NOM	MAX	UNIT
Voltage <sup>2</sup>	V <sub>CC</sub>	-0.3	-	40	V
	PWM IN	-0.3	-	5.5	V
	IOUT	-0.3	-	40	V
	ALARM OUT	-0.3	-	6	V
Current	IOUT <sup>3</sup>	0	-	120	mA
	ALARM OUT	0	-	3	mA
Temperature	Operating junction T <sub>j</sub>	-40	-	150	°C
	Storage T <sub>STG</sub>	-55	-	150	°C
Electrostatic Discharge Ratings	Human body mode (HBM)	2000	-	-	V
	Machine mode (MM)	200	-	-	V

<sup>1</sup> Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions* is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

<sup>2</sup> All Voltages are with respect to device ground terminal.

<sup>3</sup> The maximum allowable current through IOUT is determined by power dissipation, operating temperature and chip/package reliability. 120 mA is the maximum sink current in IOUT. It is an upper bound solely based on chip/package reliability.

## Thermal Information

PACKAGES	JUNCTION TO AMBIENT ( $\theta_{JA}$ ) - °C/W	CONDITIONS
SOT26	335	Device mounted on FR4 PCB with minimum pad layout
	143	Device mounted on 25mm x 25mm 2oz copper board
	120	Device mounted on 50mm x 50mm 2oz copper board

## Recommended Operating Conditions

At  $T_A = -40^{\circ}\text{C}$  to  $110^{\circ}\text{C}$ , unless otherwise noted

PARAMETER		SYMBOL	TEST CONDITIONS	MIN	NOM	MAX	UNIT
<b>DC Characteristics</b> $V_{CC} = 4.5$ to $40$ V	Supply Voltage	$V_{CC}$	-	4.5		40	V
	Output Voltage	$V_O$	Drive turned on			$V_{CC}$	V
			Drive turned off			$V_{CC}$	V
			ALARM OUT	-0.3		6	V
	Open drain sink current	$I_{OUT}$	ALARM OUT		1	3	mA
	Output sink current (IOUT)	$I_{OUT}$		1		120	mA
	High level input voltage	$V_{IH}$	PWM IN	2.3		5.5	V
Low level input voltage	$V_{IL}$	PWM IN	-0.3		1.0	V	
<b>AC Characteristics</b> $V_{CC} = 4.5$ to $40$ V	PWM dimming frequency	$f_{PWM}$	PWM IN			1	MHz

## Electrical Characteristics

At  $V_{CC} = 4.5$  to  $40$  V,  $T_A = -40^\circ\text{C}$  to  $85^\circ\text{C}$ . Typical values at  $V_{CC} = 24$  V and  $T_A = 25^\circ\text{C}$ , unless otherwise noted.

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
<b>Driver Characteristic</b>						
Leakage output current	$I_{OL}$	IOUT = 40V, driver off			0.36	$\mu\text{A}$
Constant current error (device-to-device)	$\Delta I_{OL1}$	IOUT, 100% PWM duty, $V_{OUT} = 1.0$ V, $R_{EXT} = 33 \Omega$ (~ 20 mA)		3		%
Line regulation	$\Delta I_{OL2}$	IOUT, 100% PWM duty, $V_{OUT} = 1.0$ V, $R_{EXT} = 33 \Omega$ (~ 20 mA)		0.01		%/V
Load regulation	$\Delta I_{OL3}$	IOUT, 100% PWM duty, $V_{OUT} = 1.0 \sim 10$ V, $R_{EXT} = 33 \Omega$ (~ 20 mA)		0.01		%/V
Temperature drift	$\Delta I_{OL4}$	Junction temperature < $125^\circ\text{C}$	-5		5	%
<b>Current Sensing</b>						
Current sensing voltage	$V_{SENSE}$			650		mV
<b>Regulated Supply</b>						
PSRR	$V_{PSRR}$	DC to 1MHz ( $V_{CC} = 24$ V), IOUT = 20mA		-64		dB (A/V)
PSRR	$V_{PSRR}$	DC to 1MHz ( $V_{CC} = 36$ V), IOUT = 20mA		-64		
Turn on time	$t_{ON}$				500	$\mu\text{s}$
<b>Temperature Sensor</b>						
Thermal alarm threshold	$T_{ALM}$	Junction temperature ( $T_J$ )	100	115	130	$^\circ\text{C}$
Thermal shutdown threshold	$T_{SHD}$	Junction temperature ( $T_J$ )	150	165	175	$^\circ\text{C}$
Thermal error hysteresis	$T_{HYS}$	Junction temperature ( $T_J$ )	5	10	20	$^\circ\text{C}$
<b>PWM Function</b>						
Pull-high resistor	$R_{PH}$	Connected between internal supply (4.4 V) and PWM IN pin	4.0			K $\Omega$
<b>LED Open Detection</b>						
LED open detection threshold	$V_{LO}$				0.3	V
<b>ALARM Function</b>						
Pull-high resistor	$R_{PH}$	Connected between internal supply (4.4 V) and ALARM OUT pin	90			K $\Omega$
Open drain current	$I_{OD}$	$V_{out} = 0.4$ V		2.3		mA
<b>Supply Current</b>						
Supply current	$I_{CC}$	100% PWM duty, $R_{EXT} = 33 \Omega$ (~ 20 mA)		1.1		mA
		100% PWM duty, $R_{EXT} = 13 \Omega$ (~ 50 mA)		1.1		
		100% PWM duty, $R_{EXT} = 6.5 \Omega$ (~ 100 mA)		1.1		

## Switching Characteristics<sup>4</sup>

At  $V_{CC} = 6\text{ V to }40\text{ V}$ ,  $T_A = -40^\circ\text{C to }85^\circ\text{C}$ ,  $C_L = 15\text{ pF}$ ,  $R_L = 82\ \Omega$

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
Propagation delay	$t_{D0}$	PWM IN to IOOUT (rising edge)		73		ns
	$t_{D1}$	PWM IN to IOOUT (falling edge)		28		ns
Rise time	$t_{R0}$	$V_{OUT} = 1\text{ V}; I_{OUT} = 20\text{ mA}$		77		ns
	$t_{R1}$	$V_{OUT} = 1.1\text{ V}; I_{OUT} = 50\text{ mA}$		101		ns
		$V_{OUT} = 1.25\text{ V}; I_{OUT} = 100\text{ mA}$		128		ns
Fall time	$t_{F0}$	$V_{OUT} = 1\text{ V}; I_{OUT} = 20\text{ mA}$		78		ns
	$t_{F1}$	$V_{OUT} = 1.1\text{ V}; I_{OUT} = 50\text{ mA}$		111		ns
		$V_{OUT} = 1.25\text{ V}; I_{OUT} = 100\text{ mA}$		139		ns

## Parameter Measurement Information

### Test Circuits




Figure 1. Rise and fall time test circuit for IOOUT




Figure 2. Constant current test circuit for IOOUT

<sup>4</sup> IOOUT switching characteristics are given in configuration register section

## Timing Diagram





Figure 3. Output timing

## Pin Description

PIN NAME	I/O	DESCRIPTIONS
IOUT	O	Low output voltage constant current sink output
VCC	-	Supply voltage
REXT	I/O	A resistor between REXT and GND sets maximum current
PWM IN	I	PWM input
GND	-	Ground
ALARM OUT	O	Open drain output for reporting LED open circuit and driver thermal issue

**SOT26**



**Typical Characteristics**




Figure 4. Reference resistor vs. output current





Figure 5. IOOUT vs. output voltage (V<sub>cc</sub> = 4.5 ~ 40 V)

## Functional Block Diagram



## Detailed Description

### PWM Dimming

The DD313-4 supports PWM dimming. The dimming information is retrieved from PWM IN into which a microcontroller sends a PWM signal with allowable frequency up to 1 MHz. If the PWM IN pin is floating, the driver is always on. Otherwise the driver is modulated by patterns appearing in the PWM IN pin.

### Constant Current Setting

The maximum constant current for is determined by an external resistor,  $R_{EXT}$ , placed between the  $R_{EXT}$  and GND pins. The  $R_{EXT}$  resistor value is calculated with the equation below.

$$I_{OUT} (A) = V_{REXT} (V) / R_{EXT} (\Omega)$$

where  $V_{REXT}$  is the internal reference voltage on the  $R_{EXT}$  pin (typical 0.65 V)

### LED Open Detection

The DD313-4 can detect LED open circuit (LO) by comparing with open circuit threshold when  $I_{OUT}$  is on. LO will result in ALARAM signal pulled low. Figure 6 illustrates LO detection circuit. The table below shows a truth table for LO.

LO	Alarm
LED is not open circuit ( $V_{OUT} > V_{LO}$ )	0
LED is open circuit ( $V_{OUT} < V_{LO}$ )	1




Figure 6. LED Open Circuit Detection Circuit

### Thermal Alarm and Shutdown

The DD313-4 has an on-chip temperature sensor for thermal alarm (TA) and shutdown (TS) protection. If the junction temperature of a device exceeds the thermal alarm threshold, ALARM output will be set to high. If the junction temperature reaches to a TS threshold, the device will turn off outputs with ALARM remaining high until the junction temperature falls below thermal error hysteresis of TA threshold. If the junction temperature is lower than a thermal error hysteresis of TA threshold, the device will turn back on automatically.

## Power Dissipation Calculation

The device power dissipation must be lower than the power dissipation rate of the device package material as illustrated in Figure 7 to ensure a correct operation. The equation below calculates the power dissipation of a device.

$$P_D = I_{CC} \times V_{CC} + [I_{MAX} \times V_{OUT} \times D_{PWM}]$$

Where:

$V_{CC}$  = device supply voltage

$I_{CC}$  = device supply current

$V_{OUT}$  = IOOUT voltage when driving LED current

$I_{MAX}$  = LED current adjusted by REXT resistor

$D_{PWM}$  = average duty ratio defined by scaled PWM duty





Figure 7. Power dissipation vs. temperature

## Application Circuits


The application circuits below show the versatility of DD313-4 platform for building applications with desirable features in LED lighting.

### Linear Constant Current Driver


Lighting LED String




Basic AC Application



Constant Current Regulator Charging Circuit



## Package Dimension



VARIATION(ALL DIMENSIONS SHOWN IN MM)

SYMBOL	MIN.	NOM.	MAX.
A	-	-	1.45
A1	0.00	-	0.15
A2	0.90	1.15	1.30
b	0.30	-	0.50
c	0.08	-	0.22
D	2.90 BSC.		
E	2.80 BSC.		
E1	1.60 BSC.		
e	0.95 BSC.		
e1	1.90 BSC.		
L	0.30	0.45	0.60
L1	0.60 REF.		
L2	0.25 BSC.		
R	0.10	-	-
R1	0.10	-	0.25
$\theta$	0°	4°	8°
$\theta 1$	5°	10°	15°

NOTE :

1. JEDEC OUTLINE : MO-178 AB.

The products listed herein are designed for ordinary electronic applications, such as electrical appliances, audio-visual equipment, communications devices and so on. Hence, it is advisable that the devices should not be used in medical instruments, surgical implants, aerospace machinery, nuclear power control systems, disaster/crime-prevention equipment and the like. Misusing those products may directly or indirectly endanger human life, or cause injury and property loss.

Silicon Touch Technology, Inc. will not take any responsibilities regarding the misuse of the products mentioned above. Anyone who purchases any products described herein with the above-mentioned intention or with such misused applications should accept full responsibility and indemnify. Silicon Touch Technology, Inc. and its distributors and all their officers and employees shall defend jointly and severally against any and all claims and litigation and all damages, cost and expenses associated with such intention and manipulation.

Silicon Touch Technology, Inc. reserve the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete.