

TENTATIVE DATA

Heater	Vf	=	6.3 V
	If	=	0.3 A

Capacities	Ca	=	7.7 uuF
	Cg1	=	7.7 uuF
	Cag1	=	< 0.005 uuF

Operating Conditions

Va		250	V
Vg2		250	V
Vk2		150	V
-Vg1		3	V
Ia		10	mA
Ig2		0.6	mA
-Ik2		8	mA
S (Ia = 10 mA)		14	mA/V
R1 (Ia = 10 mA)		0.25	megohm

Limiting Values


Vao max		550	V
Va max		250	V
Wa max		2.5	W
Vg2o max		550	V
Vg2 max		250	V
Wg2 max		0.2	W
Vk2o max		550	V
Vk2 max		150	V
Wk2 max		1.5	W
Ik max		5	mA
Vg1 max (Igl = + 0.3 uA)		-1.3	V
Rg1 max		0.7	megohm
Vfk max		50	V
Rfk max		20,000	ohms

EE50




Mullard

SINGLE ENDED TELEVISION SECONDARY EMISSION VALVE

CIRCUIT DIAGRAM



Arrangement of electrodes and base connections




EE 50

Mullard

SINGLE ENDED TELEVISION SECONDARY EMISSION VALVE


EE50



EE50

Mullard


SINGLE ENDED TELEVISION SECONDARY EMISSION VALVE



Mullard

SINGLE ENDED TELEVISION SECONDARY EMISSION VALVE


EE50



EE50

Mullard


SINGLE ENDED TELEVISION SECONDARY EMISSION VALVE



Mullard

SINGLE ENDED TELEVISION SECONDARY EMISSION VALVE


EE50



EE50

Mullard


SINGLE ENDED TELEVISION SECONDARY EMISSION VALVE



Mullard

SINGLE ENDED TELEVISION SECONDARY EMISSION VALVE


EE50



EE50

Mullard

SINGLE ENDED TELEVISION SECONDARY EMISSION VALVE



Mullard

SINGLE ENDED TELEVISION SECONDARY EMISSION VALVE

EE50

