

7717/6CY5

Sharp-Cutoff Tetrode

7-PIN MINIATURE TYPE
For Mobile-Communications Equipment

GENERAL DATA

Electrical:

Heater Characteristics and Ratings (*Design-Maximum Values*):

Voltage (AC or DC)	6.3	^{+1.2} _{-0.3}	volts
Current at heater volts = 6.3	0.200		amp
Peak heater-cathode voltage:			
Heater negative with			
respect to cathode.	100	max.	volts
Heater positive with			
respect to cathode.	100 ^a	max.	volts

Direct Interelectrode Capacitances:^b

Grid No.1 to plate.	0.03	max.	μμf
Grid No.1 to cathode & internal shield,			
grid No.2, and heater	4.4		μμf
Plate to cathode & internal shield,			
grid No.2, and heater	2.74		μμf


Characteristics, Class A₁ Amplifier:

Plate Voltage	125	volts
Grid-No.2 Voltage	80	volts
Grid-No.1 Voltage	-1	volt
Plate Resistance (Approx.)	0.125	megohm
Transconductance.	8000	μmhos
Plate Current	10	ma
Grid-No.2 Current	1.4	ma
Grid-No.1 Voltage (Approx.) for		
transconductance (μmhos) = 100.	-5	volts

Mechanical:

Operating Position.	Any
Type of Cathode	Coated Unipotential
Maximum Overall Length.	2-1/8"
Maximum Seated Length	1-7/8"
Length, Base Seat to Bulb Top (Excluding tip).	1-1/2" ± 3/32"
Diameter.	0.650" to 0.750"
Dimensional Outline	See <i>General Section</i>
Bulb.	T5-1/2
Base.	Small-Button Miniature 7-Pin (JEDEC No.E7-1)
Basing Designation for BOTTOM VIEW.	7EW

Pin 1 - Grid No.1
Pin 2 - Cathode,
 Internal
 Shield
Pin 3 - Heater
Pin 4 - Heater



Pin 5 - Plate
Pin 6 - Grid No.2
Pin 7 - Cathode,
 Internal
 Shield



RADIO CORPORATION OF AMERICA
Electron Tube Division
Harrison, N. J.

DATA
5-62

7717/6CY5

AMPLIFIER — Class A₁

Maximum Ratings, Design-Maximum Values:

PLATE VOLTAGE 180 max. volts
GRID-No.2 (SCREEN-GRID) SUPPLY VOLTAGE. . . 180 max. volts
GRID-No.2 VOLTAGE See *Grid-No.2 Input Rating Chart*
at front of Receiving Tube Section
GRID-No.1 (CONTROL-GRID) VOLTAGE:
Positive-bias value 0 max. volts
CATHODE CURRENT 20 max. ma
GRID-No.2 INPUT:
For grid-No.2 voltages up
to 90 volts 0.5 max. watt
For grid-No.2 voltages be-
tween 90 and 180 volts. . See *Grid-No.2 Input Rating Chart*
at front of Receiving Tube Section
PLATE DISSIPATION 2 max. watts

Maximum Circuit Values:

Grid-No.1-Circuit Resistance. 0.5 max. megohm

SPECIAL RATINGS & PERFORMANCE DATA

Heater-Cycling:

Cycles of Intermittent Operation. 2000 min. cycles

This test is performed on a sample lot of tubes from each production run under the following conditions: heater volts = 7.5 cycled one minute on and one minute off, heater 135 volts positive with respect to cathode and all other elements connected to ground. At the end of this test, tubes are checked for heater-cathode shorts and open circuits.

Transconductance at Reduced Heater Voltage:

Average Value 5900 μ mos

With heater volts = 5.0, plate volts = 125, grid-No.2 volts = 80, grid-No.1 volts = -1.

^a The dc component must not exceed 50 volts.

^b With external shield JEDEC No.316 connected to cathode.

