

NEW!

Ultra Low Profile Common Mode Choke 0805



- For noise suppression in super high speed signal lines: USB 3.x, HDMI 2.0, HDBaseT™, DisplayPort, DVI, etc.; and in high speed differential signal lines: USB 2.0, IEEE1394, LVDS, etc.
- Up to 6.5 GHz differential mode 3 dB cutoff frequency; up to 35 dB common mode noise attenuation in GHz range
- Lowest profile 0805 common mode choke – 0.93 mm tall

Core material Ferrite**Environmental** RoHS compliant**Terminations** Matte tin over nickel over silver-platinum-glass frit.**Weight** 9.0 – 13.0 mg**Ambient temperature** –40°C to +125°C with Irms current.**Maximum part temperature** 140°C**Storage temperature** Component: –40°C to +155°C.

Tape and reel packaging: –40°C to +80°C

Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles**Moisture Sensitivity Level (MSL)** 1 (unlimited floor life at <30°C / 85% relative humidity)**Failures in Time (FIT) / Mean Time Between Failures (MTBF)**

38 per billion hours / 26,315,789 hours, calculated per Telcordia SR-332

Packaging 2000/7" reel; 7500/13" reel; Plastic tape: 8 mm wide, 0.23 mm thick, 4 mm pocket spacing, 1.07 mm pocket depth**PCB washing** Tested to MIL-STD-202 Method 215 plus an additional aqueous wash. See [Doc787_PCB_Washing.pdf](#).

Part number ¹	Common mode impedance typ (Ohms)			Common mode attenuation typ (dB)			Inductance ² min (nH)	DCR max ³ (Ohms)	Isolation ⁴ (Vrms)	Irms ⁵ (mA)
	10 MHz	100 MHz	500 MHz	10 MHz	100 MHz	500 MHz				
0805USBN-121MR_	2	12	57	0.04	0.5	5.0	14	0.11	250	500
0805USBN-271MR_	3	27	125	0.09	1.4	10.0	30	0.14	250	500
0805USBN-481MR_	5	48	231	0.13	3.5	14.7	53	0.22	250	500
0805USBN-701MR_	7	70	342	0.18	5.3	17.4	77	0.235	250	500
0805USBN-941MR_	10	94	493	0.30	7.6	21.1	105	0.27	250	500
0805USBN-132MR_	13	130	697	0.50	10.0	24.4	140	0.32	250	500
0805USBN-162MR_	17	165	955	0.78	12.1	27.3	182	0.37	250	450
0805USBN-222MR_	24	225	1310	1.14	14.0	30.0	252	0.63	250	350

1. When ordering, please specify **packaging** code:**0805USBN-222MRC****Packaging:** C = 7" machine-ready reel. EIA-481 embossed plastic tape (2000 parts per full reel).**B** = Less than full reel. In tape, but not machine ready. To have a leader and trailer added (\$25 charge), use code letter C instead.**D** = 13" machine-ready reel. EIA-481 embossed plastic tape (7500 parts per full reel).

2. Inductance measured at 100 MHz using an Agilent/HP 4286A impedance analyzer and a Coilcraft SMD-A fixture.





3. DCR is specified per winding.

4. Winding to winding isolation (hipot) tested for one minute.

5. Current per winding that causes a 15°C rise from 25°C ambient.

5. Electrical specifications at 25°C.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.

Dimensions are in $\frac{\text{inches}}{\text{mm}}$ **Recommended Land Pattern****US** +1-847-639-6400 sales@coilcraft.com**UK** +44-1236-730595 sales@coilcraft-europe.com**Taiwan** +886-2-2264 3646 sales@coilcraft.com.tw**China** +86-21-6218 8074 sales@coilcraft.com.cn**Singapore** + 65-6484 8412 sales@coilcraft.com.sg

Document 1304-1 Revised 05/11/16


© Coilcraft Inc. 2016

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.


NEW!

Ultra Low Profile Common Mode Choke – 0805

Typical Differential Mode Attenuation (Ref: 50 Ohms)



Typical Common Mode Attenuation (Ref: 50 Ohms)



Typical Impedance vs Frequency

