


Silicon N-Channel MOSFET


Features

- 4.5A,800V, $R_{DS(on)}$ (Max2.5 Ω)@ $V_{GS}=10V$
- Ultra-low Gate charge(Typical 14nC)
- Fast Switching Capability
- 100%Avalanche Tested
- Maximum Junction Temperature Range(150 $^{\circ}C$)



General Description

This Power MOSFET is produced using Winsemi's advanced planar stripe,VDMOS technology.this latest technology has been especially designed to minimize on-state resistance, have a high rugged avalanche characteristics .This devices is specially well suited for half bridge and full bridge resonant topology line a electronic lamp ballast, high efficiency switched mode power supplies, active power factor correction.



Absolute Maximum Ratings

Symbol	Parameter	Value	Units
V_{DSS}	Drain Source Voltage	800	V
I_D	Continuous Drain Current(@ $T_c=25^{\circ}C$)	4.5*	A
	Continuous Drain Current(@ $T_c=100^{\circ}C$)	2.5*	A
I_{DM}	Drain Current Pulsed (Note1)	16*	A
V_{GS}	Gate to Source Voltage	± 30	V
E_{AS}	Single Pulsed Avalanche Energy (Note2)	230	mJ
I_{AR}	Avalanche Current (Note1)	4	
E_{AR}	Repetitive Avalanche Energy (Note1)	11	mJ
dv/dt	Peak Diode Recovery dv /dt (Note3)	4.5	V/ns
P_D	Total Power Dissipation(@ $T_c=25^{\circ}C$)	33	W
	Derating Factor above 25 $^{\circ}C$	0.43	W/ $^{\circ}C$
T_J	Junction Temperature	150	$^{\circ}C$
T_{stg}	Storage Temperature	-55~150	
T_L	Channel Temperature	300	$^{\circ}C$

*Drain current limited by maximum junction temperature

Thermal Characteristics

Symbol	Parameter	Value			Units
		Min	Typ	Max	
R_{QJC}	Thermal Resistance , Junction -to -Case	-	-	3.79	$^{\circ}C/W$
R_{QJA}	Thermal Resistance , Junction-to-Ambient	-	-	62.5	$^{\circ}C/W$

Electrical Characteristics(Tc=25°C)

Characteristics		Symbol	Test Condition	Min	Type	Max	Unit
Gate leakage current		I _{GSS}	V _{GS} =±30V,V _{DS} =0V	-	-	±100	nA
Gate-source breakdown voltage		V _{(BR)GSS}	I _G =±10 μA,V _{DS} =0V	±30	-	-	V
Drain Cut -off current		I _{DSS}	V _{DS} =800V,V _{GS} =0V,Tc=25°C	-	-	10	μA
			V _{DS} =640V,Tc=125°C	-	-	100	μA
Drain -source breakdown voltage		V _{(BR)DSS}	I _D =250 μA,V _{GS} =0V	800	-	-	V
Breakdown Voltage Temperature		ΔBV _{DSS} /ΔT _J	I _D =250μA,referenced to25°C	-	0.65	-	V/°C
Gate threshold voltage		V _{GS(th)}	V _{DS} =V _{GS} ,I _D =250 μA	2	-	4	V
Drain -source ON resistance		R _{DS(ON)}	V _{GS} =10V,I _D =2.25A	-	2.0	2.5	Ω
Forward Transconductance		g _{fs}	V _{DS} =40V,I _D =2.25A	-	4.6	-	S
Input capacitance		C _{iss}	V _{DS} =25V,	-	1320	1716	pF
Reverse transfer capacitance		C _{rss}	V _{GS} =0V,	-	9	12	
Output capacitance		C _{oss}	f=1MHz	-	105	136	
Switching time	Turn-on Rise time	t _r	V _{DD} =400V,	-	85	155	ns
	Turn-on delay time	T _{d(on)}	I _D =4.5A	-	34	75	
	Turn-off Fall time	t _f	R _G =25Ω	-	59	118	
	Turn-off delay time	T _{d(off)}	(Note4,5)	-	56	113	
Total gate charge(gate-source plus gate-drain)		Q _g	V _{DD} =640V, V _{GS} =10V,	-	14	19	nC
Gate-source charge		Q _{gs}	I _D =4.5A	-	5	-	
Gate-drain("miller") Charge		Q _{gd}	(Note,5)	-	6	-	

Source-Drain Ratings and Characteristics(Ta=25°C)

Characteristics	Symbol	Test Condition	Min	Type	Max	Unit
Continuous drain reverse current	I _{DR}	-	-	-	4.5	A
Pulse drain reverse current	I _{DRP}	-	-	-	16	A
Forward voltage(diode)	V _{DSF}	I _{DR} =4.5A,V _{GS} =0V	-	-	1.4	V
Reverse recovery time	t _{rr}	I _{DR} =4.5A,V _{GS} =0V,	-	625	-	ns
Reverse recovery charge	Q _{rr}	dI _{DR} /dt =100 A /μs	-	6.71	-	μC

Note 1.Repeativity rating :pulse width limited by junction temperature

2.L=40mH I_{AS}=4.5A,V_{DD}=50V,R_G=25Ω,Starting T_J=25°C

3.I_{SD}≤4.5A,di/dt≤200A/us,V_{DD}<BV_{DSS},STARTING T_J=25°C

4.Pulse Test:Pulse Width≤300us,Duty Cycle≤2%

5. Essentially independent of operating temperature.

This transistor is an electrostatic sensitive device

Please handle with caution




Fig.1 On-State characteristics




Fig.2 Transfer characteristics




Fig.3 On-Resistance Variation vs Drain Current and Gate Voltage




Fig.4 Body Diode Forward Voltage Variation with Source Current and Temperature




Fig.5 Capacitance Characteristics




Fig.6 Gate Charge Characteristics




Fig.7 Breakdown Voltage Variation vs. Temperature




Fig.8 On-Resistance Variation vs. Temperature




Fig.9 Maximum Safe Operation Area




Fig.10 Maximum Drain Current vs Case Temperature




Fig.11 Transient Thermal Response Curve




Fig.12 Gate Test Circuit & Waveform




Fig.13 Resistive Switching Test Circuit & Waveform




Fig.14 Unclamped Inductive Switching Test Circuit & Waveform




Fig.15 Peak Diode Recovery dv/dt Test Circuit & Waveform

TO-220F Package Dimension

