

## Small Signal Zener Diodes



### FEATURES

- Silicon planar power Zener diodes
- Standard Zener voltage tolerance is  $\pm 5\%$  with a "B" suffix in the ordering code (e.g.: 1N5221B), suffix "C" is  $\pm 2\%$  tolerance
- These diodes are also available in MiniMELF case with the type designation TZM5221 to TZM5267, SOT-23 case with the type designations MMBZ5225 to MMBZ5267 and SOD-123 case with the types designations MMSZ5225 to MMSZ5267
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**

### LINKS TO ADDITIONAL RESOURCES



| PRIMARY CHARACTERISTICS |                     |      |
|-------------------------|---------------------|------|
| PARAMETER               | VALUE               | UNIT |
| $V_Z$ range nom.        | 2.4 to 75           | V    |
| Test current $I_{ZT}$   | 1.7 to 20           | mA   |
| $V_Z$ specification     | Thermal equilibrium |      |
| Circuit configuration   | Single              |      |

### APPLICATIONS

- Voltage stabilization

| ORDERING INFORMATION |                               |                                 |                        |
|----------------------|-------------------------------|---------------------------------|------------------------|
| DEVICE NAME          | ORDERING CODE                 | TAPED UNITS PER REEL            | MINIMUM ORDER QUANTITY |
| 1N5221B to 1N5267B   | 1N5221B to 1N5267B-series-TR  | 10 000 per 13" reel             | 30 000/box             |
| 1N5221C to 1N5267C   | 1N5221C to 1N5267C-series-TR  |                                 |                        |
| 1N5221B to 1N5267B   | 1N5221B to 1N5267B-series-TAP | 10 000 per ammpack (52 mm tape) |                        |
| 1N5221C to 1N5267C   | 1N5221C to 1N5267C-series-TAP |                                 |                        |

| PACKAGE          |        |                                      |                                   |                              |
|------------------|--------|--------------------------------------|-----------------------------------|------------------------------|
| PACKAGE NAME     | WEIGHT | MOLDING COMPOUND FLAMMABILITY RATING | MOISTURE SENSITIVITY LEVEL        | SOLDERING CONDITIONS         |
| DO-35 (DO-204AH) | 125 mg | UL 94 V-0                            | MSL level 1 (according J-STD-020) | Peak temperature max. 260 °C |

| ABSOLUTE MAXIMUM RATINGS ( $T_{amb} = 25\text{ °C}$ , unless otherwise specified) |   |            |               |      |
|---|---|------------|---------------|------|
| PARAMETER   | TEST CONDITION                              | SYMBOL     | VALUE         | UNIT |
| Power dissipation   | $T_L \leq 25\text{ °C}$                     | $P_{tot}$  | 500           | mW   |
| Zener current   |   | $I_Z$      | $P_{tot}/V_Z$ | mA   |
| Thermal resistance junction to ambient air  | $l = 4\text{ mm}$ , $T_L = \text{constant}$ | $R_{thJA}$ | 300           | K/W  |
| Junction temperature  |   | $T_j$      | 175           | °C   |
| Storage temperature range   |   | $T_{stg}$  | -65 to +175   | °C   |
| Forward voltage (max.)  | $I_F = 200\text{ mA}$                       | $V_F$      | 1.1           | V    |



| ELECTRICAL CHARACTERISTICS (T <sub>amb</sub> = 25 °C, unless otherwise specified) |                                    |                  |                  |                                  |     |   |                                     |                         |
|---|------------------------------------|------------------|------------------|----------------------------------|-----|---|-------------------------------------|-------------------------|
| PART NUMBER   | ZENER VOLTAGE RANGE <sup>(1)</sup> | TEST CURRENT     |                  | REVERSE LEAKAGE CURRENT          |     | DYNAMIC RESISTANCE f = 1 kHz                      |                                     | TEMPERATURE COEFFICIENT |
|   | V <sub>Z</sub> at I <sub>ZT1</sub> | I <sub>ZT1</sub> | I <sub>ZT2</sub> | I <sub>R</sub> at V <sub>R</sub> |     | Z <sub>Z</sub> at I <sub>ZT1</sub> <sup>(1)</sup> | Z <sub>ZK</sub> at I <sub>ZT2</sub> | α <sub>VZ</sub>         |
|   | V                                  | mA               |                  | μA                               | V   | Ω   |                                     | %/K                     |
|   | NOM.                               |                  |                  | MAX.                             |     | MAX.  | MAX.                                | TYP.                    |
| 1N5221  | 2.4                                | 20               | 0.25             | 100                              | 1   | 30  | 1200                                | - 0.085                 |
| 1N5222  | 2.5                                | 20               | 0.25             | 100                              | 1   | 30  | 1250                                | - 0.085                 |
| 1N5223  | 2.7                                | 20               | 0.25             | 75                               | 1   | 30  | 1300                                | - 0.08                  |
| 1N5224  | 2.8                                | 20               | 0.25             | 75                               | 1   | 30  | 1400                                | - 0.08                  |
| 1N5225  | 3                                  | 20               | 0.25             | 50                               | 1   | 29  | 1600                                | - 0.075                 |
| 1N5226  | 3.3                                | 20               | 0.25             | 25                               | 1   | 28  | 1600                                | - 0.07                  |
| 1N5227  | 3.6                                | 20               | 0.25             | 15                               | 1   | 24  | 1700                                | - 0.065                 |
| 1N5228  | 3.9                                | 20               | 0.25             | 10                               | 1   | 23  | 1900                                | - 0.06                  |
| 1N5229  | 4.3                                | 20               | 0.25             | 5                                | 1   | 22  | 2000                                | 0.055                   |
| 1N5230  | 4.7                                | 20               | 0.25             | 5                                | 2   | 19  | 1900                                | 0.03                    |
| 1N5231  | 5.1                                | 20               | 0.25             | 5                                | 2   | 17  | 1600                                | 0.03                    |
| 1N5232  | 5.6                                | 20               | 0.25             | 5                                | 3   | 11  | 1600                                | 0.038                   |
| 1N5233  | 6                                  | 20               | 0.25             | 5                                | 3.5 | 7   | 1600                                | 0.038                   |
| 1N5234  | 6.2                                | 20               | 0.25             | 5                                | 4   | 7   | 1000                                | 0.045                   |
| 1N5235  | 6.8                                | 20               | 0.25             | 3                                | 5   | 5   | 750                                 | 0.05                    |
| 1N5236  | 7.5                                | 20               | 0.25             | 3                                | 6   | 6   | 500                                 | 0.058                   |
| 1N5237  | 8.2                                | 20               | 0.25             | 3                                | 6.5 | 8   | 500                                 | 0.062                   |
| 1N5238  | 8.7                                | 20               | 0.25             | 3                                | 6.5 | 8   | 600                                 | 0.065                   |
| 1N5239  | 9.1                                | 20               | 0.25             | 3                                | 7   | 10  | 600                                 | 0.068                   |
| 1N5240  | 10                                 | 20               | 0.25             | 3                                | 8   | 17  | 600                                 | 0.075                   |
| 1N5241  | 11                                 | 20               | 0.25             | 2                                | 8.4 | 22  | 600                                 | 0.076                   |
| 1N5242  | 12                                 | 20               | 0.25             | 1                                | 9.1 | 30  | 600                                 | 0.077                   |
| 1N5243  | 13                                 | 9.5              | 0.25             | 0.5                              | 9.9 | 13  | 600                                 | 0.079                   |
| 1N5244  | 14                                 | 9                | 0.25             | 0.1                              | 10  | 15  | 600                                 | 0.082                   |
| 1N5245  | 15                                 | 8.5              | 0.25             | 0.1                              | 11  | 16  | 600                                 | 0.082                   |
| 1N5246  | 16                                 | 7.8              | 0.25             | 0.1                              | 12  | 17  | 600                                 | 0.083                   |
| 1N5247  | 17                                 | 7.4              | 0.25             | 0.1                              | 13  | 19  | 600                                 | 0.084                   |
| 1N5248  | 18                                 | 7                | 0.25             | 0.1                              | 14  | 21  | 600                                 | 0.085                   |
| 1N5249  | 19                                 | 6.6              | 0.25             | 0.1                              | 14  | 23  | 600                                 | 0.086                   |
| 1N5250  | 20                                 | 6.2              | 0.25             | 0.1                              | 15  | 25  | 600                                 | 0.086                   |
| 1N5251  | 22                                 | 5.6              | 0.25             | 0.1                              | 17  | 29  | 600                                 | 0.087                   |
| 1N5252  | 24                                 | 5.2              | 0.25             | 0.1                              | 18  | 33  | 600                                 | 0.088                   |
| 1N5253  | 25                                 | 5                | 0.25             | 0.1                              | 19  | 35  | 600                                 | 0.089                   |
| 1N5254  | 27                                 | 4.6              | 0.25             | 0.1                              | 21  | 41  | 600                                 | 0.09                    |
| 1N5255  | 28                                 | 4.5              | 0.25             | 0.1                              | 21  | 44  | 600                                 | 0.091                   |
| 1N5256  | 30                                 | 4.2              | 0.25             | 0.1                              | 23  | 49  | 600                                 | 0.091                   |
| 1N5257  | 33                                 | 3.8              | 0.25             | 0.1                              | 25  | 58  | 700                                 | 0.092                   |
| 1N5258  | 36                                 | 3.4              | 0.25             | 0.1                              | 27  | 70  | 700                                 | 0.093                   |
| 1N5259  | 39                                 | 3.2              | 0.25             | 0.1                              | 30  | 80  | 800                                 | 0.094                   |
| 1N5260  | 43                                 | 3                | 0.25             | 0.1                              | 33  | 93  | 900                                 | 0.095                   |
| 1N5261  | 47                                 | 2.7              | 0.25             | 0.1                              | 36  | 105   | 1000                                | 0.095                   |
| 1N5262  | 51                                 | 2.5              | 0.25             | 0.1                              | 39  | 125   | 1100                                | 0.096                   |
| 1N5263  | 56                                 | 2.2              | 0.25             | 0.1                              | 43  | 150   | 1300                                | 0.096                   |
| 1N5264  | 60                                 | 2.1              | 0.25             | 0.1                              | 46  | 170   | 1400                                | 0.097                   |
| 1N5265  | 62                                 | 2                | 0.25             | 0.1                              | 47  | 185   | 1400                                | 0.097                   |
| 1N5266  | 68                                 | 1.8              | 0.25             | 0.1                              | 52  | 230   | 1600                                | 0.097                   |
| 1N5267  | 75                                 | 1.7              | 0.25             | 0.1                              | 56  | 270   | 1700                                | 0.098                   |

**Note**

<sup>(1)</sup> Based on DC measurement at thermal equilibrium; lead length = 9.5 (3/8"); thermal resistance of heat sink = 30 K/W

**BASIC CHARACTERISTICS** ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)




Fig. 1 - Thermal Resistance vs. Lead Length




Fig. 4 - Total Power Dissipation vs. Ambient Temperature




Fig. 2 - Typical Change of Working Voltage under Operating Conditions at  $T_{amb} = 25\text{ }^{\circ}\text{C}$




Fig. 5 - Temperature Coefficient of  $V_Z$  vs. Z-Voltage




Fig. 3 - Typical Change of Working Voltage vs. Junction Temperature




Fig. 6 - Diode Capacitance vs. Z-Voltage




Fig. 7 - Forward Current vs. Forward Voltage




Fig. 9 - Z-Current vs. Z-Voltage




Fig. 8 - Z-Current vs. Z-Voltage




Fig. 10 - Differential Z-Resistance vs. Z-Voltage





Fig. 11 - Thermal Response



**PACKAGE DIMENSIONS** in millimeters (inches): **DO-35 (DO-204AH)\_1N52xx**



Rev. 1 - Date: 19. December 2011  
Document no.: S8-V-3906.04-031(4)  
94 12648



## **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.