

# MM420 MM421

CASE 79-02, STYLE 1  
TO-39 (TO-205AD)

TRANSISTOR

NPN SILICON

4

## MAXIMUM RATINGS

Rating	Symbol	MM420	MM421	Unit
Collector-Emitter Voltage	$V_{CEO}$	250	325	Vdc
Collector-Base Voltage	$V_{CBO}$	275	350	Vdc
Emitter-Base Voltage	$V_{EBO}$	6.0	6.0	Vdc
Base Current	$I_B$	100	100	mA
Collector Current — Continuous	$I_C$	100	500	mA
Total Device Dissipation @ $T_A = 25^\circ\text{C}$ Derate above $25^\circ\text{C}$	$P_D$	800 5.3		mW mW/ $^\circ\text{C}$
Total Device Dissipation @ $T_A = 75^\circ\text{C}$ Derate above $75^\circ\text{C}$	$P_D$	2.5 25		Watts mW/ $^\circ\text{C}$
Operating and Storage Junction Temperature Range	$T_J, T_{stg}$	-65 to +175		$^\circ\text{C}$

Refer to 2N3439 for graphs.

## ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise noted.)

Characteristic	Symbol	Min	Max	Unit
<b>OFF CHARACTERISTICS</b>				
Collector-Emitter Sustaining Voltage(1) ( $I_C = 10\text{ mA}, I_B = 0$ )	$V_{CEO(sus)}$	250 325	— —	Vdc
Collector-Base Breakdown Voltage ( $I_C = 100\ \mu\text{Adc}$ )	$V_{(BR)CBO}$	275 350	— —	Vdc
Emitter-Base Breakdown Voltage ( $I_E = 100\ \mu\text{Adc}$ )	$V_{(BR)EBO}$	6	—	Vdc
Collector Cutoff Current ( $V_{CE} = 250\text{ Vdc}, I_B = 0$ ) ( $V_{CE} = 325\text{ Vdc}, I_B = 0$ )	$I_{CEO}$	— —	1.0 1.0	mAdc
Collector Cutoff Current ( $V_{BE} = 275\text{ Vdc}, I_E = 0$ ) ( $V_{BE} = 350\text{ Vdc}, I_E = 0$ )	$I_{CBO}$	— —	100 100	$\mu\text{Adc}$
<b>ON CHARACTERISTICS</b>				
DC Current Gain ( $I_C = 1.0\text{ mAdc}, V_{CE} = 20\text{ Vdc}$ ) ( $I_C = 10\text{ mAdc}, V_{CE} = 20\text{ Vdc}$ ) ( $I_C = 30\text{ mAdc}, V_{CE} = 20\text{ Vdc}$ )	$h_{FE}$	15 25 25	— — 250	—
Collector-Emitter Saturation Voltage ( $I_C = 30\text{ mAdc}, I_B = 3.0\text{ mAdc}$ )	$V_{CE(sat)}$	—	5.0	Vdc
Base-Emitter On Voltage ( $I_C = 30\text{ mA}, V_{CE} = 20\text{ V}$ )	$V_{BE(on)}$	—	1.0	V
<b>SMALL SIGNAL CHARACTERISTICS</b>				
Current-Gain — Bandwidth Product ( $I_C = 10\text{ mA}, V_{CE} = 20\text{ V}, f = 10\text{ MHz}$ )	$f_T$	15	—	MHz
Output Capacitance ( $V_{CB} = 20\text{ V}, f = 100\text{ kHz}$ )	$C_{obo}$	—	12	pF

(1)  $PW \leq 300\ \mu\text{sec}$ , Duty Cycle  $\leq 2.0\%$ .