


Main Product Characteristics:

V_{DS}	30V
$R_{DS(on)}$	5.0mohm(typ.)
I_D	50A


TO252

**Marking and pin
Assignment**

Schematic diagram
Features and Benefits:

- Advanced trench MOSFET process technology
- Special designed for PWM, load switching and general purpose applications
- Ultra low on-resistance with low gate charge
- Fast switching and reverse body recovery
- 175°C operating temperature


Description:

It utilizes the latest FRRMOS (fast reverse recovery MOS) trench processing techniques to achieve the high cell density and reduces the on-resistance, fast switching and soft reverse recovery time. These features combine to make this design an extremely efficient and reliable device for use in power switching application and a wide variety of other applications

Absolute max Rating:

Symbol	Parameter	Max.	Units
I_D @ TC = 25°C	Continuous Drain Current, V_{GS} @ 10V①	50	A
I_D @ TC = 100°C	Continuous Drain Current, V_{GS} @ 10V①	40	
I_{DM}	Pulsed Drain Current②	200	
P_D @ TC = 25°C	Power Dissipation③	100	W
	Linear Derating Factor	0.55	W/°C
V_{DS}	Drain-Source Voltage	30	V
V_{GS}	Gate-to-Source Voltage	± 20	V
E_{AS}	Single Pulse Avalanche Energy @ L=0.1mH	100	mJ
I_{AS}	Avalanche Current @ L=0.1mH	44	A
T_J T_{STG}	Operating Junction and Storage Temperature Range	-55 to + 175	°C


Thermal Resistance

Symbol	Characterizes	Typ.	Max.	Units
$R_{\theta JC}$	Junction-to-case ^③	—	1.5	°C/W
$R_{\theta JA}$	Junction-to-ambient ($t \leq 10s$) ^④	—	45	°C/W
	Junction-to-Ambient (PCB mounted, steady-state) ^④	—	20	°C/W





Electrical Characterizes @ $T_A=25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter	Min.	Typ.	Max.	Units	Conditions
$V_{(BR)DSS}$	Drain-to-Source breakdown voltage	30	36.5	—	V	$V_{GS} = 0V, I_D = 250\mu A$
$R_{DS(on)}$	Static Drain-to-Source on-resistance	—	5.0	8	m Ω	$V_{GS}=10V, I_D=20A$
		—	7.5	10	m Ω	$V_{GS}=4.5V, I_D=10A$
$V_{GS(th)}$	Gate threshold voltage	1	—	3	V	$V_{DS} = V_{GS}, I_D = 250\mu A$
I_{DSS}	Drain-to-Source leakage current	—	—	10	μA	$V_{DS} = 30V, V_{GS} = 0V$
I_{GSS}	Gate-to-Source forward leakage	—	—	100	nA	$V_{GS} = 20V$
		-100	—	—		$V_{GS} = -20V$
Q_g	Total gate charge	—	35	—	nC	$V_{DS}=15V,$ $I_D=20A,$ $V_{GS}=10V$
Q_{gs}	Gate-to-Source charge	—	7.9	—		
Q_{gd}	Gate-to-Drain("Miller") charge	—	8.7	—		
$t_{d(on)}$	Turn-on delay time	—	11.5	—	ns	$V_{GS}=10V, V_{DS}=15V,$ $R_{GEN}=3\Omega, I_D=20A$
t_r	Rise time	—	46.5	—		
$t_{d(off)}$	Turn-Off delay time	—	25.8	—		
t_f	Fall time	—	6.5	—		
C_{iss}	Input capacitance	—	2055	—	pF	$V_{GS} = 0V$ $V_{DS} = 15V$ $f = 1MHz$
C_{oss}	Output capacitance	—	356	—		
C_{rss}	Reverse transfer capacitance	—	226	—		

Source-Drain Ratings and Characteristics

Symbol	Parameter	Min.	Typ.	Max.	Units	Conditions
I_S	Continuous Source Current	—	—	50	A	MOSFET symb showing the integral reverse p-n junction diode. 
I_{SM}	Pulsed Source Current	—	—	200	A	
V_{SD}	Diode Forward Voltage	—	0.5	1.0	V	$I_S=1.0A, V_{GS}=0V$
t_{rr}	Reverse Recovery Time	—	12.4	—	ns	$T_J = 25^\circ\text{C}, I_F = 20A, di/dt$ $= 300A/\mu s$
Q_{rr}	Reverse Recovery Charge	—	11.7	—	nC	

Test circuits and Waveforms

EAS test circuits:

Gate charge test circuit:

Switch Time Test Circuit:

Waveforms:


Notes:

- ① The maximum current rating is limited by bond-wires.
- ② Repetitive rating; pulse width limited by max. junction temperature.
- ③ The power dissipation P_D is based on max. junction temperature, using junction-to-case thermal resistance.
- ④ The value of $R_{\theta JA}$ is measured with the device mounted on 1in 2 FR-4 board with 2oz. Copper, in a still air environment with $T_A = 25^\circ\text{C}$
- ⑤ These curves are based on the junction-to-case thermal impedance which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of $T_{J(MAX)} = 175^\circ\text{C}$.

Typical electrical characteristics




Figure 1: Typical Output Characteristics




Figure 2: Typical Transfer Characteristics




Figure 3: On-Resistance vs. Gate-Source Voltage




Figure 4: Body-Diode Characteristics




Figure 5: Gate-Charge Characteristics




Figure 6: Capacitance Characteristics

Typical thermal characteristics




Figure 7: Maximum Forward Biased Safe Operating Area




Figure 8: Single Pulse Power Rating Junction-to-Case




Figure 9: Power De-rating




Figure 10: Current De-rating






Figure 11: Normalized Thermal transient Impedance Curve

Mechanical Data:
TO-252E-2-M PACKAGE INFORMATION
Dimensions in Millimeters


SYMBOL	MIN	NOM	MAX
A	2.20	2.30	2.38
A1	0	—	0.10
A2	0.90	1.01	1.10
b	0.72	—	0.85
b1	0.71	0.76	0.81
b2	0.72	—	0.90
b3	5.13	5.33	5.46
c	0.47	—	0.60
c1	0.46	0.51	0.56
c2	0.47	—	0.60
D	6.00	6.10	6.20
D1	5.25	—	—
E	6.50	6.60	6.70
E1	4.70	—	—
e	2.186	2.286	2.386
H	9.80	10.10	10.40
L	1.40	1.50	1.70
L1	2.90REF		
L2	0.51BSC		
L3	0.90	—	1.25
L4	0.60	0.80	1.00
L5	0.15	—	0.75
L6	1.80REF		
θ	0°	—	8°
θ 1	5°	7°	9°
θ 2	5°	7°	9°



Ordering and Marking Information**Device Marking: SSFM3008L****Package (Available)****TO252****Operating Temperature Range****C : -55 to 175 °C****Devices per Unit**

Package Type	Units/ Tube	Tubes/Inner Box	Units/Inner Box	Inner Boxes/Carton Box	Units/Carton Box
TO-252	80	50	4000	10	40000

Reliability Test Program

Test Item	Conditions	Duration	Sample Size
High Temperature Reverse Bias(HTRB)	$T_J=125^{\circ}\text{C}$ to 175°C @ 80% of Max $V_{DSS}/V_{CES}/V_R$	168 hours 500 hours 1000 hours	3 lots x 77 devices
High Temperature Gate Bias(HTGB)	$T_J=125^{\circ}\text{C}$ to 175°C @ 100% of Max V_{GSS}	168 hours 500 hours 1000 hours	3 lots x 77 devices

ATTENTION:

- Any and all Silikron products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your Silikron representative nearest you before using any Silikron products described or contained herein in such applications.
- Silikron assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all Silikron products described or contained herein.
- Specifications of any and all Silikron products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- Silikron Semiconductor CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all Silikron products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of Silikron Semiconductor CO.,LTD.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. Silikron believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the Silikron product that you intend to use.
- This catalog provides information as of Dec, 2008. Specifications and information herein are subject to change without notice.

Customer Service**Worldwide Sales and Service:**

Sales@silikron.com

Technical Support:

Technical@silikron.com

Suzhou Silikron Semiconductor Corp.

Building 11A Suchun Industrial Square, 428# Xinglong Street, Suzhou P.R. China

TEL: (86-512) 62560688

FAX: (86-512) 65160705

E-mail: Sales@silikron.com