



Features

- Small surface mounting type
- High speed
- Suitable for high packing density
- RoHS compliant with Halogen-free

HF



SOD-323

Mechanical Data

- Case: SOD-323
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
1SS380	SOD-323	3000 pcs / Tape & Reel	6D

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Reverse Voltage	V _{RM}	40	V
DC Blocking Voltage	V _R	35	V
Forward Continuous Current	I _F	100	mA
Peak Forward Current	I _{FM}	225	mA
Peak Forward Surge Current, t _p = 1s	I _{FSM}	0.4	A
Power Dissipation	P _D	200	mW
Operating Junction Temperature Range	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-55 ~ +150	°C


Thermal Characteristics

Parameter	Symbol	Value	Unit
Thermal Resistance Junction-to-Air *1	R _{θJA}	350	°C/W
Thermal Resistance Junction-to-Case *1	R _{θJC}	220	°C/W
Thermal Resistance Junction-to-Lead *1	R _{θJL}	240	°C/W


Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Reverse Breakdown Voltage	$V_{(BR)R}$	$I_R = 100\mu\text{A}$	35	-	-	V
Forward Voltage	V_F	$I_F = 100\text{mA}$	-	-	1.2	V
Maximum Peak Reverse Current	I_R	$V_R = 20\text{V}$	-	-	10	nA
Total Capacitance	C_J	$V_R = 0.5\text{V}, f = 1.0\text{MHz}$	-	-	5	pF

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)



Package Outline Dimensions (Unit: mm)



Mounting Pad Layout (Unit: mm)

