


Features

- Fast switching speed
- High conductance
- RoHS compliant with Halogen-free

HF



SOD-323

Mechanical Data

- Case: SOD-323
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
BAS21H	SOD-323	3000 pcs / Tape & Reel	JS

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Repetitive Peak Reverse Voltage	V _{RRM}	250	V
DC Blocking Voltage	V _R	250	V
Average Rectified Output Current	I _F	200	mA
Non-Repetitive Peak Forward Surge Current, t _p = 1ms	I _{FSM}	2.5	A
Repetitive Peak Forward Surge Current	I _{FRM}	625	mA

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P _D	200	mW
Thermal Resistance Junction-to-Air ^{*1}	R _{θJA}	440	°C/W
Thermal Resistance Junction-to-Case ^{*1}	R _{θJC}	260	°C/W
Thermal Resistance Junction-to-Lead ^{*1}	R _{θJL}	290	°C/W
Operating Junction Temperature Range	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-55 ~ +150	°C

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Reverse Breakdown Voltage	$V_{(BR)R}$	$I_R = 100\mu\text{A}$	250	-	-	V
Forward Voltage	V_F	$I_F = 100\text{mA}$	-	-	1	V
		$I_F = 200\text{mA}$	-	-	1.25	V
Maximum Peak Reverse Current	I_R	$V_R = 200\text{V}, T_J = 25^\circ\text{C}$	-	-	0.1	μA
		$V_R = 200\text{V}, T_J = 150^\circ\text{C}$	-	-	100	μA
Total Capacitance	C_J	$V_R = 0\text{V}, f = 1.0\text{MHz}$	-	-	5	pF
Reverse Recovery Time	t_{rr}	$I_F = I_R = 30\text{mA}$ $I_{rr} = 0.1 \times I_R, R_L = 100\Omega$	-	-	50	ns

Note 1: The data tested by surface mounted on a minimum recommended FR-4 board

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Typical Reverse Characteristic




Fig 2 Typical Forward Characteristics




Fig 3 Capacitance vs. Reverse Voltage





Fig 4 Power Derating Curve

Package Outline Dimensions (Unit: mm)



SOD-323		
Dimension	Min.	Max.
A	1.60	1.80
B	1.20	1.40
C	0.80	0.90
D	0.25	0.35
E	0.22	0.42
H	0.02	0.10
J	0.05	0.15
K	2.55	2.75

Mounting Pad Layout (Unit: mm)

SOD-323

