


NPN/NPN Multi-Chip Transistor

FEATURES

- Ideal for low power amplification and switching

MECHANICAL DATA

- Case: SOT-363 Plastic
- Case material: "Green" molding compound, UL flammability classification 94V-0, (No Br. Sb. Cl)
- Lead Free in RoHS 2002/95/EC Compliant






Maximum Ratings @ T_A = 25°C

Characteristic	Symbol	Value	Unit
Collector-Base Voltage	V _{CB0}	60	V
Collector-Emitter Voltage	V _{CEO}	40	V
Emitter-Base Voltage	V _{EBO}	5	V
Collector Current -Continuous	I _C	200	mA
Collector Power Dissipation	P _C	200	mW
Junction Temperature	T _J	150	°C
Storage Temperature Range	T _{STG}	-55~+150	°C

Electrical Characteristics @ T_A = 25°C unless otherwise specified

Characteristic	Test Condition	Symbol	Min.	Typ.	Max.	Unit
Collector-base breakdown voltage	I _C =10μA, I _E =0	V _{CB0}	60			V
Collector-emitter breakdown voltage	I _C =1mA, I _B =0	V _{CEO}	40			V
Emitter-base breakdown voltage	I _E =10μA, I _C =0	V _{EBO}	5			V
Collector-base cut-off current	V _{CB} =30V, I _E =0	I _{CB0}			0.05	uA
Emitter-base cut-off current	V _{EB} =5V, I _C =0	I _{EBO}			0.05	uA
DC current gain	V _{CE} =1V, I _C =0.1mA	h _{FE1}	40			
	V _{CE} =1V, I _C =1mA	h _{FE2}	70			
	V _{CE} =1V, I _C =10mA	h _{FE3}	100		300	
	V _{CE} =1V, I _C =50mA	h _{FE4}	60			
	V _{CE} =1V, I _C =100mA	h _{FE5}	30			
Collector-emitter saturation voltage	I _C =10mA, I _B =1mA	V _{CE(sat)1}			0.2	V
	I _C =50mA, I _B =5mA	V _{CE(sat)2}			0.3	V
Base-emitter saturation voltage	I _C =10mA, I _B =1mA	V _{BE(sat)1}	0.65		0.85	V
	I _C =50mA, I _B =5mA	V _{BE(sat)2}			0.95	V
Transition frequency	V _{CE} =20V, I _C =10mA, f=100MHz	f _T	300			MHz
Collector output capacitance	V _{CB} =5V, I _E =0, f=1MHz	Cob			4	pF
Noise figure	V _{CE} =5V, I _C =0.1mA, f=1kHz, R _S =1KΩ	NF			5	dB
Delay time	V _{CC} =3V, V _{BE} =-0.5V	T _d			35	nS
Rise time	I _C =10mA, I _{B1} =-I _{B2} =1mA	T _r			35	nS
Storage time	V _{CC} =3V, I _C =10mA	T _s			200	nS
Fall time	I _{B1} =-I _{B2} =1mA	T _f			50	nS

SOT-363 Outline Dimension



Symbol	Dimension In Millimeters	
	Min	Max.
A	1.89	2.20
B	1.15	1.35
C	0.80	1.10
D	0.10	0.30
G	0.65 BSC	
H	---	0.10
J	0.10	0.25
K	0.10	0.30
N	0.20 REF	
S	2.00	2.20

Device Marking :

Device P/N	Marking code
MMDT3904	MA

Figure 1. Capacitance




Figure 2. Charge Data




Figure 3. Turn-On Time




Figure 4. Rise Time




Figure 5. Storage Time




Figure 6. Fall Time




Figure 7. Noise Figure




Figure 8. Noise Figure




Figure 9. Current Gain




Figure 10. Output Admittance




Figure 11. Input Impedance




Figure 12. Voltage Feedback Ratio




Fig.13 DC Current Gain




Fig.14 Collector Saturation Region






Figure 15. "ON" VoltagesFigure



16. Temperature Coefficients



Important Notice and Disclaimer

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.

New Marking Rule Notification

Range: In order to have well management in process control, the new marking rule is applied to small signal device including Switching Diode, Transistor and Schottky Diode.

Package: SOT-363

