



Micro Commercial Components



Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311

Phone: (818) 701-4933

Fax: (818) 701-4939

MMDT3904V

Features

- Halogen free available upon request by adding suffix "-HF"
- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Epitaxial Die Construction
- Ideal for Low Power Amplification and Switching
- Ultra-small Surface Mount Package
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Marking:KAP

Maximum Ratings @ 250C Unless Otherwise Specified


Symbol	Rating	Rating	Unit
V_{CE0}	Collector-Emitter Voltage	40	V
V_{CBO}	Collector-Base Voltage	60	V
V_{EBO}	Emitter-Base Voltage	6	V
I_C	Collector Current-Continuous	0.2	A
P_C	Collector Dissipation	0.2	W
R_{JA}	Thermal Resistance Junction to Ambient	625	$^{\circ}C/W$
T_J	Operating Junction Temperature	-55 to +150	$^{\circ}C$
T_{STG}	Storage Temperature	-55 to +150	$^{\circ}C$

Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Typ	Max	Units
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage ($I_C=1mA$, $I_B=0$)	40	---	---	Vdc
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage ($I_C=10uA$, $I_E=0$)	60	---	---	Vdc
$V_{(BR)EBO}$	Collector-Emitter Breakdown Voltage ($I_E=10uA$, $I_C=0$)	6	---	---	Vdc
I_{CEX}	Collector Cutoff Current ($V_{CE}=60Vdc$, $V_{EB(OFF)}=3Vdc$)	---	---	50	nAdc
I_{BL}	Base Cutoff Current ($V_{CE}=60Vdc$, $V_{EB(OFF)}=3Vdc$)	---	---	50	nAdc
h_{FE}	DC Current Gain ($I_C=0.1mA$, $V_{CE}=1Vdc$) ($I_C=1mA$, $V_{CE}=1Vdc$) ($I_C=10mA$, $V_{CE}=1Vdc$) ($I_C=50mA$, $V_{CE}=1Vdc$) ($I_C=100mA$, $V_{CE}=1Vdc$)	40 70 100 60 30	---	---	---
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage ($I_C=10mA$, $I_B=1mA$) ($I_C=50mA$, $I_B=5mA$)	---	---	0.2 0.3	Vdc
$V_{BE(sat)}$	Base-Emitter Saturation Voltage ($I_C=10mA$, $I_B=1mA$) ($I_C=50mA$, $I_B=5mA$)	0.65 ---	---	0.85 0.95	Vdc

NPN Plastic-Encapsulate Transistors

SOT-563



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.006	.011	0.15	0.30	
B	.043	.049	1.10	1.25	
C	.061	.067	1.55	1.70	
D	.020		0.50		
G	.035	.043	0.90	1.10	
H	.059	.067	1.50	1.70	
K	.022	.023	0.56	0.60	
L	.004	.011	0.10	0.30	
M	.004	.007	0.10	0.18	

MMDT3904V

Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter		Min	Typ	Max	Units
f_T	Transition Frequency ($V_{CE}=20V_{dc}$, $I_C=10mA_{dc}$, $f=100MHz$)		300	---	---	MHz
C_{ob}	Output Capacitance ($V_{CB}=5V_{dc}$, $f=1.0MHz$, $I_E=0$)		---	---	4	pF
NF	Noise Figure ($V_{CE}=5V$, $I_C=0.1mA$, $f=1KHz$, $R_S=1k\Omega$)		---	---	5	dB
t_d	Delay Time	$V_{CC}=3V$, $I_C=10mA$, $V_{BE(off)}=-0.5V$, $I_{B1}=-I_{B2}=1mA$	---	---	35	ns
t_r	Rise Time		---	---	35	ns
t_s	Storage Time	$V_{CC}=3V$, $I_C=10mA$, $I_{B1}=I_{B2}=1mA$	---	---	200	ns
t_f	Fall Time		---	---	50	ns




Fig. 1, Derating Curve - Total




Fig. 2, Input and Output Capacitance vs. Collector-Base Voltage




Fig. 3, Typical DC Current Gain vs Collector Current





Fig. 4, Typical Collector-Emitter Saturation Voltage vs. Collector Current

MMDT3904V



Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel; 3Kpcs/Reel

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.