

MSS39,000 Series P-Type Silicon Schottky Diodes



Description

The Aeroflex / Metelics MSS39,000 series of Schottky diodes is fabricated on P-Type epitaxial substrates for superior 1/f noise performance in microwave biased-detector applications up to 40 GHz.

Features

- Very low 1/f Noise
- Detector applications to 40 GHz
- Chip, beam lead or packaged devices

Absolute Maximum Ratings

Parameters	Rating
Reverse Voltage	Rated V_{BR}
Forward Current	50 mA
Operation Temperature	-65 °C to +150 °C
Storage Temperature	-65 °C to +150 °C
Power Dissipation	100 mW, derated linearly to zero at $T_A = +150$ °C
Soldering Temperature (Packaged)	+ 230 °C for 5 sec.
Beam Lead Pull Strength, Min	4 grams

Chip

Electrical Specifications, $T_A = 25$ °C

Model	V_{BR} MIN V	V_F TYP V	C_J MAX pF	T_{SS} TYP dBm	γ TYP mV / mW	Frequency MAX GHz	Outline
MSS39,045-C15	5.0	0.40	0.10	-58	5,000	18	C15
MSS39,048-C15	5.0	0.39	0.15	-58	5,000	12	C15
Test Conditions	$I_R = 10 \mu A$	$I_F = 1 mA$	$V_R = 0 V$ $F = 1 MHz$	DC Bias = 10 μA $R_L = 100 K\Omega$	$F = 10 GHz$ Video BW = 2 MHz		



Beam Lead

Electrical Specifications, $T_A = 25\text{ }^\circ\text{C}$

Model	V_{BR} MIN V	V_F TYP V	C_J MAX pF	T_{SS} TYP dBm	γ TYP mV / mW	Frequency MAX GHz	Outline
MSS39,144-B10B	3.5	0.38	0.08	-58	5,000	40	B10B
MSS39,146-B10B	3.5	0.38	0.10	-58	5,000	26	B10B
MSS39,148-B10B	3.5	0.39	0.12	-58	5,000	18	B10B
MSS39,152-B10B	3.5	0.38	0.18	-58	5,000	12	B10B
Test Conditions	$I_R = 10\text{ }\mu\text{A}$	$I_F = 1\text{ mA}$	$V_R = 0\text{ V}$ $F = 1\text{ MHz}$	DC Bias = $10\text{ }\mu\text{A}$ $F = 10\text{ GHz}$ $R_L = 100\text{ K}\Omega$ Video BW = 2 MHz			

Packaged

Electrical Specifications, $T_A = 25\text{ }^\circ\text{C}$

Model	V_{BR} MIN V	V_F TYP V	C_T MAX pF	T_{SS} TYP dBm	γ TYP mV / mW	Frequency MAX GHz	Outline
MSS39,045-P55	5.0	0.40	0.25	-58	5000	18	P55
MSS39,045-P86	5.0	0.40	0.27	-58	5000	18	P86
MSS39,048-P55	5.0	0.39	0.30	-58	5000	12	P55
MSS39,048-P86	5.0	0.39	0.32	-58	5000	12	P86
MSS39,148-E25	3.5	0.39	0.22	-58	5000	18	E25
MSS39,148-H20	3.5	0.39	0.30	-58	5000	12	H20
MSS39,152-E25	3.5	0.38	0.28	-58	5000	12	E25
MSS39,152-H20	3.5	0.38	0.36	-58	5000	18	H20
Test Conditions	$I_R = 10\text{ }\mu\text{A}$	$I_F = 1\text{ mA}$	$V_R = 0\text{ V}$ $F = 1\text{ MHz}$	DC Bias = $10\text{ }\mu\text{A}$ $F = 10\text{ GHz}$ $R_L = 100\text{ K}\Omega$ Video BW = 2 MHz			

MSS39,000 Series P-Type Silicon Schottky Diodes

Typical Performance, $T_A = 25^\circ\text{C}$



Figure 1.




Figure 2.











Figure 4.



Outline Drawings



Outline Drawings



Aeroflex / Metelics Inc.

Aeroflex Microelectronic Solutions
975 Stewart Drive
Sunnyvale, CA 94085
TEL: 408-737-8181

54 Grenier Field Road
Londonderry, NH 03053
TEL: 603-641-3800

Sales

888-641-SEMI (7364)
metelics-sales@aeroflex.com

www.aeroflex.com/Microwave www.aeroflex.com/Metelics

Aeroflex / Metelics, Inc. reserves the right to make changes to any products and services herein at any time without notice. Consult Aeroflex or an authorized sales representative to verify that the information in this data sheet is current before using this product. Aeroflex does not assume any responsibility or liability arising out of the application or use of any product or service described herein, except as expressly agreed to in writing by Aeroflex; nor does the purchase, lease, or use of a product or service from Aeroflex convey a license under any patent rights, copyrights, trademark rights, or any other of the intellectual rights of Aeroflex or of third parties.

Copyright 2010 Aeroflex / Metelics. All rights reserved.

ISO 9001:2008 certified companies



Our passion for performance is defined by three attributes represented by these three icons: solution-minded, performance-driven and customer-focused.