

**FEATURES**


- ❑ Originative New Design
- ❑ 100% EAS Test
- ❑ Rugged Gate Oxide Technology
- ❑ Extremely Low Intrinsic Capacitances
- ❑ Remarkable Switching Characteristics
- ❑ Unequalled Gate Charge : 40 nC (Typ.)
- ❑ Extended Safe Operating Area
- ❑ Lower  $R_{DS(ON)}$  : 0.48  $\Omega$  (Typ.) @  $V_{GS}=10V$

**APPLICATION**

- ❑ High current, High speed switching
- ❑ Suitable for power supplies, adaptors and PFC
- ❑ SMPS (Switched Mode Power Supplies)

## PFP12N65E/PFF12N65E

### 650V N-Channel MOSFET

 $BV_{DSS} = 650 V$ 
 $R_{DS(on) typ} = 0.48 \Omega$ 
 $I_D = 12.2 A$ 

**TO-220**


1.Gate 2. Drain 3. Source

**TO-220F**


1.Gate 2. Drain 3. Source

**Absolute Maximum Ratings**  $T_C=25^\circ C$  unless otherwise specified

Symbol	Parameter	PFP12N65E	PFF12N65E	Units
$V_{DSS}$	Drain-Source Voltage	650		V
$I_D$	Drain Current – Continuous ( $T_C = 25^\circ C$ )	12.2	12.2*	A
	Drain Current – Continuous ( $T_C = 100^\circ C$ )	7.7	7.7*	A
$I_{DM}$	Drain Current – Pulsed (Note 1)	48.8	48.8*	A
$V_{GS}$	Gate-Source Voltage	$\pm 30$		V
$E_{AS}$	Single Pulsed Avalanche Energy (Note 2)	950		mJ
$I_{AR}$	Avalanche Current (Note 1)	12		A
$E_{AR}$	Repetitive Avalanche Energy (Note 1)	22		mJ
dv/dt	Peak Diode Recovery dv/dt (Note 3)	5.5		V/ns
$P_D$	Power Dissipation ( $T_C = 25^\circ C$ ) - Derate above $25^\circ C$	223	51	W
		1.78	0.41	W/ $^\circ C$
$T_J, T_{STG}$	Operating and Storage Temperature Range	-55 to +150		$^\circ C$
$V_{ISO}$	Insulation withstand voltage (DC)	-	3000	V
$T_L$	Maximum lead temperature for soldering purposes, 1/8" from case for 5 seconds	300		$^\circ C$

\* Drain current limited by maximum junction temperature

**Thermal Resistance Characteristics**

Symbol	Parameter	PFP12N65E	PFF12N65E	Units
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	0.56	2.43	$^\circ C/W$
$R_{\theta CS}$	Thermal Resistance, Case-to-Sink	0.5	--	
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	62.5	62.5	

**Electrical Characteristics**  $T_C=25^\circ\text{C}$  unless otherwise specified

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
<b>On Characteristics</b>						
$V_{GS}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = 250\ \mu\text{A}$	2.0	--	4.0	V
$R_{DS(ON)}$	Static Drain-Source On-Resistance	$V_{GS} = 10\ \text{V}, I_D = 6.0\ \text{A}$	--	0.48	0.60	$\Omega$

**Off Characteristics**

$BV_{DSS}$	Drain-Source Breakdown Voltage	$V_{GS} = 0\ \text{V}, I_D = 250\ \mu\text{A}$	650	--	--	V
$\Delta BV_{DSS} / \Delta T_J$	Breakdown Voltage Temperature Coefficient	$I_D = 250\ \mu\text{A}$ , Referenced to $25^\circ\text{C}$	--	0.5	--	$\text{V}/^\circ\text{C}$
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{DS} = 650\ \text{V}, V_{GS} = 0\ \text{V}$	--	--	10	$\mu\text{A}$
		$V_{DS} = 520\ \text{V}, T_C = 125^\circ\text{C}$	--	--	100	$\mu\text{A}$
$I_{GSSF}$	Gate-Body Leakage Current, Forward	$V_{GS} = 30\ \text{V}, V_{DS} = 0\ \text{V}$	--	--	100	nA
$I_{GSSR}$	Gate-Body Leakage Current, Reverse	$V_{GS} = -30\ \text{V}, V_{DS} = 0\ \text{V}$	--	--	-100	nA

**Dynamic Characteristics**

$C_{iss}$	Input Capacitance	$V_{DS} = 25\ \text{V}, V_{GS} = 0\ \text{V},$ $f = 1.0\ \text{MHz}$	--	2630	3420	pF
$C_{oss}$	Output Capacitance		--	200	260	pF
$C_{rss}$	Reverse Transfer Capacitance		--	45	60	pF
$R_g$	Gate Input Resistance		$f = 1.0\ \text{MHz}$ , open drain	--	1.5	--

**Switching Characteristics**

$t_{d(on)}$	Turn-On Time	$V_{DS} = 325\ \text{V}, I_D = 12.0\ \text{A},$ $R_G = 25\ \Omega, R_L = 27\ \Omega$  (Note 4,5)	--	45	65	ns
$t_r$	Turn-On Rise Time		--	65	100	ns
$t_{d(off)}$	Turn-Off Delay Time		--	40	60	ns
$t_f$	Turn-Off Fall Time		--	20	30	ns
$Q_g$	Total Gate Charge	$V_{DS} = 520\ \text{V}, I_D = 12.0\ \text{A},$ $V_{GS} = 10\ \text{V}$  (Note 4,5)	--	41	52	nC
$Q_{gs}$	Gate-Source Charge		--	15	--	nC
$Q_{gd}$	Gate-Drain Charge		--	7	--	nC

**Source-Drain Diode Maximum Ratings and Characteristics**

$I_S$	Continuous Source-Drain Diode Forward Current	--	--	12.2	A	
$I_{SM}$	Pulsed Source-Drain Diode Forward Current	--	--	48.8		
$V_{SD}$	Source-Drain Diode Forward Voltage	$I_S = 12\ \text{A}, V_{GS} = 0\ \text{V}$	--	--	1.5	V
$t_{rr}$	Reverse Recovery Time	$I_S = 12\ \text{A}, V_{GS} = 0\ \text{V}$ $di_f/dt = 100\ \text{A}/\mu\text{s}$ (Note 4)	--	390	--	$\mu\text{s}$
$Q_{rr}$	Reverse Recovery Charge		--	4.5	--	$\mu\text{C}$

**Notes ;**

1. Repetitive Rating : Pulse width limited by maximum junction temperature
2.  $I_{AS}=12\text{A}, V_{DD}=50\text{V}, R_G=25\Omega$ , Starting  $T_J=25^\circ\text{C}$
3.  $I_{SD}\leq 12\text{A}, di/dt\leq 300\text{A}/\mu\text{s}, V_{DD}\leq BV_{DSS}$ , Starting  $T_J=25^\circ\text{C}$
4. Pulse Test : Pulse Width  $\leq 300\mu\text{s}$ , Duty Cycle  $\leq 2\%$
5. Essentially Independent of Operating Temperature

# Typical Characteristics

Figure 1. On Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. Static Drain-Source On Resistance




Figure 4. Body Diode Forward Voltage




Figure 5. Capacitance Characteristics





Figure 6. Gate Charge Characteristics



Typical Characteristics (continued)

Figure 7. Breakdown Voltage Variation vs. Temperature




Figure 8. On-Resistance Variation vs. Temperature




Figure 9-1. Safe Operation Area for PFP12N65E




Figure 9-2. Safe Operation Area for PFF12N65E





Figure 10. Maximum Drain Current vs. Case Temperature



Typical Characteristics (continued)

Figure 11-1. Transient Thermal Response Curve for PFP12N65E





Figure 11-2. Transient Thermal Response Curve for PFF12N65E



Characteristics Test Circuit & Waveform




Fig 14. Resistive Switching Test Circuit & Waveforms





Fig 15. Gate Charge Test Circuit & Waveform





Fig 16. Unclamped Inductive Switching Test Circuit & Waveforms

Characteristics Test Circuit & Waveform (continued)





Fig 17. Peak Diode Recovery  $dv/dt$  Test Circuit & Waveforms

Package Dimension

TO-220

