

FEATURES

- ▶ **Ultra Compact Size**
1.0 x 1.0 x 0.64" (25.4 x 25.4 x 16.3 mm)
- ▶ **Fully encapsulated Module with Solder Pins for PC Mount**
- ▶ **Regulated Single Outputs from 3.3 to 24VDC**
- ▶ **Universal Input 85 – 264 VAC**
- ▶ **EcoDesign, stand-by power consumption 150 mW max.**
- ▶ **Overvoltage and Short Circuit Protection**
- ▶ **Operating Temp. Range -25°C to +70°C**
- ▶ **Protection Class II as per IEC/EN 60536**
- ▶ **Safety Approval to UL/cUL/IEC/EN 60950-1, TUV IEC/EN 60335-1**
- ▶ **3 Year Product Warranty**



PRODUCT OVERVIEW

The new AAF-03 Series from MINMAX is a range of ultra-small, fully encapsulated 3 Watt AC/DC power supply modules. They are designed for easy PCB mounting with solder pins. The modules feature EMI-filter to meet EN 55011/55012, class B and EN 55014. EMC immunity complies with EN 61000-6-1. The low stand-by power consumption complies with European ErP Directive 2009/125/EC.

Universal input voltage range of 85-264VAC and an International safety approval package qualifies the power modules for worldwide markets.

The AAF-03 series provide a cost effective solution for space critical applications in consumer appliances and instrumentation and communication equipment.

Model Selection Guide

Model Number	Output Voltage	Output Current		Input Current	Max. capacitive Load	Efficiency (typ.)
		Max.	Peak ₍₁₎	@Max. Load		@Max. Load
	VDC	mA	mA	mA(typ.)	µF	%
AAF-03S03	3.3	900	1170	62	1200	70
AAF-03S05	5	600	780	61	800	72
AAF-03S09	9	333	430	57	440	77
AAF-03S12	12	250	320	56	330	78
AAF-03S15	15	200	260	56	260	78
AAF-03S24	24	125	160	56	160	78

Input Specifications

Parameter	Model	Min.	Typ.	Max.	Unit
Input Voltage Range	All Models	85	---	264	VAC
Input Frequency Range		47	---	63	Hz
Input Voltage Range		120	---	370	VDC
No-Load Power Consumption		---	---	150	mW
Inrush Current (Cold Start at 25°C)	115VAC	---	---	15	A
	230VAC	---	---	25	A

Output Specifications

Parameter	Conditions	Min.	Typ.	Max.	Unit
Output Voltage Accuracy		---	---	±2.0	%
Line Regulation		---	---	±1.0	%
Load Regulation		---	---	±1.0	%
Ripple & Noise	0-20 MHz Bandwidth	---	---	70	mV _{P-P}
Min. Load	No min. Load required				
Over Voltage Protection	Zener Diode Clamp	---	125	190	% of Vo
Temperature Coefficient		---	---	±0.05	%/°C
Overshoot		---	---	5	%Vout
Current Limitation	Foldback, auto-recovery	135	150	---	%Inom.
	(long term overload condition may cause damage)				
Short Circuit Protection	Hiccup mode, indefinite (automatic recovery)				

General Specifications

Parameter	Conditions	Min.	Typ.	Max.	Unit
I/O Isolation Voltage	Input to Output, 60 Seconds	3000	---	---	VAC
I/O Isolation Resistance	500 VDC	100	---	---	MΩ
Switching Frequency		---	65	---	KHz
Hold-up Time	115VAC, Full Load	---	8	---	ms
MTBF (calculated)	MIL-HDBK-217F@25°C, Ground Benign	1,200,000			Hours
Protection Class II	According IEC/EN 60536				
Safety Approvals	UL/cUL 60950-1 recognition(UL certificate)				
	IEC/EN 60950-1(CB-scheme)				
	IEC/EN 60335-1 recognition(TUV certificata,CB-scheme)				

EMC Specifications

Parameter	Standards & Level	Performance	
EMI	EN55011, EN55014-1, EN55022, FCC part 15	Class B	
EMS	EN55014-2 ,EN55024		
	ESD	EN61000-4-2 air ± 8kV	A
	Radiated immunity	EN61000-4-3 10V/m	A
	Fast transient	EN61000-4-4 ±2kV	A
	Surge	EN61000-4-5 ±1kV	A
	Conducted immunity	EN61000-4-6 10Vrms	A
	PFMF	EN61000-4-8 30A/m	A
	Dips	EN61000-4-11 30% 10ms	A
Interruptions	EN61000-4-11 >95% 5000ms	B	

Environmental Specifications

Parameter	Conditions
Temperature Range (operational)	Ambient -25°C +70°C
Power Derating	+60°C to +70°C 0.15 W/°C
Storage Temperature Range	-40°C +85°C
Cooling	Free-Air convection
Humidity (non condensing)	--- 95 % rel. H

Notes

- Peak load lasting <30s with a maximum duty cycle of 10%, average output power not to exceed maximum power.
- All specifications typical at Ta=+25°C, resistive load, 115VAC, 60Hz input voltage and after warm-up time rated output current unless otherwise noted.
- We recommend to protect the converter by a slow blow fuse in the input supply line.
- Other input and output voltage may be available, please contact factory.
- That "natural convection" is about 20LFM but is not equal to still air (0 LFM).
- Specifications are subject to change without notice.

