



SSC8035GSB

P-Channel Enhancement Mode MOSFET

- **Features**

VDS	VGS	RDSon TYP	ID
-30V	±12V	51mR@-10V	-4.2A
		60mR@-4V5	
		98mR@-2V5	

- **General Description**

This device is particularly suited for low voltage application such as portable equipment, power management and other battery powered circuits, and low in-line power dissipation are needed in a very small outline surface mount package Excellent thermal and electrical capabilities.





- **Package Information**

- **Applications**

- Load Switch
- Portable Devices
- DCDC conversion

- **Pin configuration**

Top View



Units:mm
SOT23-6L



SSC8035GSB

● **Absolute Maximum Ratings @ $T_A=25^\circ\text{C}$ unless otherwise noted**

Parameter	Symbol	Ratings	Unit
Drain-Source Voltage	V_{DSS}	-30	V
Gate-Source Voltage	V_{GSS}	± 12	V
Maximum Drain Current – Continuous	I_D	-4.2	A
– Pulsed	I_{DM}	-30	
Continuous Power Dissipation	P_D	1000	mW
Operating and Storage Temperature Range	T_J, T_{STG}	-55 to 150	$^\circ\text{C}$

● **Electrical Characteristics @ $T_A=25^\circ\text{C}$ unless otherwise noted**

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0\text{ V}, I_D = 250\ \mu\text{A}$	30	--	--	V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = -30\text{V}, V_{GS} = 0\text{V}$	--	--	-1	μA
Gate - Body Leakage, Forward	I_{GSSF}	$V_{GS} = -12\text{V}$	--	--	-100	nA
Gate - Body Leakage, Reverse	I_{GSSR}	$V_{GS} = 12\text{V}$	--	--	100	nA
ON CHARACTERISTICS						
Gate Threshold Voltage	$V_{GS(TH)}$	$V_{DS} = V_{GS}, I_D = -250\ \mu\text{A}$	-0.7	-1.0	-1.3	V
Static Drain-Source On-Resistance	$R_{DS(ON)}$	$V_{GS} = -10\text{V}, I_D = -4.2\text{A}$	--	51	65	mR
		$V_{GS} = -4.5\text{V}, I_D = -4\text{A}$	--	60	75	
		$V_{GS} = -2.5\text{V}, I_D = -1\text{A}$	--	98	120	
DYNAMIC CHARACTERISTICS						
Input Capacitance	C_{ISS}	$V_{DS} = -30\text{V}, V_{GS} = 0\text{V},$ $F = 200\text{KHz}$	--	600	--	pF
Output Capacitance	C_{OSS}		--	85	--	pF
Reverse Transfer Capacitance	C_{RSS}		--	66	--	pF
SWITCHING CHARACTERISTICS						
Turn-on Delay Time	$T_{D(ON)}$	$V_{GS} = -10\text{V}, V_{DS} = -15\text{V},$ $R_L = 3.6\text{R}, R_{GEN} = 6\text{R}$	--	6.5	--	ns
Rise Time	T_R		--	3.5	--	
Turn-off Delay Time	$T_{D(OFF)}$		--	40	--	
Fall Time	T_F		--	13	--	
DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS						
Drain-Source Diode Forward Voltage	V_{SD}	$V_{GS} = 0\text{V}, I_S = -1\text{A}$	--	-0.78	-1	V

Note:

- $R_{\theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. $R_{\theta JC}$ is guaranteed by design while $R_{\theta CA}$ is determined by the user's board design.
- Pulse Test: Pulse Width $\leq 300\ \mu\text{s}$, Duty Cycle $\leq 2.0\%$

● Typical Performance Characteristics




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current




Figure 4. Capacitance




Figure 5. On-Resistance vs. Temperature




Figure 6. Diode Forward Characteristics



SSC8035GSB




Figure 7. On Resistance vs. G-S Voltage




Figure 8. Threshold vs. Temperature



SSC8035GSB

DISCLAIMER

AFSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. AFSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICIENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G., OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.