

MM1Z5221B~MM1Z5268B

SILICON PLANAR ZENER DIODES


Silicon planar zener diode in a small plastic
SMD SOD-123 package

Features

- Total power dissipation: max.500 mW
- Small plastic package suitable for surface mounted design
- Tolerance approximately + / - 5%

PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode




Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

	Symbol	Value	Unit
Zener Current see Table "Characteristics"			
Power Dissipation at $T_L = 75^\circ\text{C}$	P_D	500	mW
Derated above 75°C	P_D	6.7	mW/?
Junction Temperature	T_j	-55 to +150	?
Storage Temperature Range	T_s	-55 to +150	?

Characteristics at $T_{amb} = 25^\circ\text{C}$

	Symbol	Min.	Typ.	Max.	Unit
Thermal Resistance Junction to Ambient	$R_{\theta JA}$	-	-	340	? /W
Thermal Resistance Junction to Lead	$R_{\theta JL}$	-	-	150	? /W
Forward Voltage at $I_F = 10\text{mA}$	V_F	-	-	0.9	V



®

РАДИОТЕХ

Тел.: (495) 795-0805
Факс: (495) 234-1603
Эл. почта: info@rct.ru
Веб: www.rct.ru


MM1Z5221B~MM1Z5268B

Type	Marking Code	Zener Voltage Range ^{1), 2)}			Maximum Zener Impedance ³⁾			Reverse Leakage Current	
		V _{znom} V	I _{ZT} for mA	V _{ZT} V	r _{ZJT} Ω	r _{ZJK} Ω	at I _{ZK} mA	I _R μA	at V _R V
MM1Z5221B	A4	2.4	20	2.28...2.52	30	1200	0.25	100	1
MM1Z5222B	AB	2.5	20	2.38...2.63	30	1250	0.25	100	1
MM1Z5223B	B4	2.7	20	2.57...2.84	30	1300	0.25	75	1
MM1Z5224B	AC	2.8	20	2.66...2.94	30	1400	0.25	75	1
MM1Z5225B	C4	3.0	20	2.85...3.15	29	1600	0.25	50	1
MM1Z5226B	D4	3.3	20	3.14...3.47	28	1600	0.25	25	1
MM1Z5227B	E4	3.6	20	3.42...3.78	24	1700	0.25	15	1
MM1Z5228B	F4	3.9	20	3.71...4.10	23	1900	0.25	10	1
MM1Z5229B	H4	4.3	20	4.09...4.52	22	2000	0.25	5	1
MM1Z5230B	J4	4.7	20	4.47...4.94	19	1900	0.25	5	2
MM1Z5231B	K4	5.1	20	4.85...5.36	17	1600	0.25	5	2
MM1Z5232B	M4	5.6	20	5.32...5.88	11	1600	0.25	5	3
MM1Z5233B	AD	6.0	20	5.70...6.30	7	1600	0.25	5	3.5
MM1Z5234B	N4	6.2	20	5.89...6.51	7	1000	0.25	5	4
MM1Z5235B	P4	6.8	20	6.46...7.14	5	750	0.25	3	5
MM1Z5236B	R4	7.5	20	7.13...7.88	6	500	0.25	3	6
MM1Z5237B	X4	8.2	20	7.79...8.61	8	500	0.25	3	6.5
MM1Z5238B	AE	8.7	20	8.27...9.14	8	600	0.25	3	6.5
MM1Z5239B	Y4	9.1	20	8.65...9.56	10	600	0.25	3	7
MM1Z5240B	Z4	10	20	9.50...10.50	17	600	0.25	3	8
MM1Z5241B	A5	11	20	10.45...11.55	22	600	0.25	2	8.4
MM1Z5242B	B5	12	20	11.40...12.60	30	600	0.25	1	9.1
MM1Z5243B	C5	13	9.5	12.35...13.65	13	600	0.25	0.5	9.9
MM1Z5244B	AF	14	9.0	13.30...14.70	15	600	0.25	0.1	10
MM1Z5245B	D5	15	8.5	14.25...15.75	16	600	0.25	0.1	11
MM1Z5246B	E5	16	7.8	15.20...16.80	17	600	0.25	0.1	12
MM1Z5247B	AH	17	7.4	16.15...17.85	19	600	0.25	0.1	13
MM1Z5248B	F5	18	7.0	17.10...18.90	21	600	0.25	0.1	14
MM1Z5249B	K9	19	6.6	18.05...19.95	23	600	0.25	0.1	14
MM1Z5250B	H5	20	6.2	19.00...21.00	25	600	0.25	0.1	15
MM1Z5251B	J5	22	5.6	20.90...23.10	29	600	0.25	0.1	17
MM1Z5252B	K5	24	5.2	22.80...25.20	33	600	0.25	0.1	18
MM1Z5253B	M9	25	5.0	23.75...26.25	35	600	0.25	0.1	19
MM1Z5254B	M5	27	4.6	25.65...28.35	41	600	0.25	0.1	21
MM1Z5255B	AJ	28	4.5	26.60...29.40	44	600	0.25	0.1	21
MM1Z5256B	N5	30	4.2	28.50...31.50	49	600	0.25	0.1	23
MM1Z5257B	P5	33	3.8	31.35...34.65	58	700	0.25	0.1	25
MM1Z5258B	R5	36	3.4	34.20...37.80	70	700	0.25	0.1	27
MM1Z5259B	X5	39	3.2	37.05...40.95	80	800	0.25	0.1	30
MM1Z5260B	Y5	43	3.0	40.85...45.15	93	900	0.25	0.1	33
MM1Z5261B	Z5	47	2.7	44.65...49.35	105	1000	0.25	0.1	36
MM1Z5262B	A6	51	2.5	48.45...53.55	125	1100	0.25	0.1	39
MM1Z5263B	B6	56	2.2	53.20...58.80	150	1300	0.25	0.1	43
MM1Z5264B	AK	60	2.1	57.00...63.00	170	1400	0.25	0.1	46
MM1Z5265B	C6	62	2.0	58.90...65.10	185	1400	0.25	0.1	47
MM1Z5266B	D6	68	1.8	64.60...71.40	230	1600	0.25	0.1	52
MM1Z5267B	E6	75	1.7	71.25...78.75	270	1700	0.25	0.1	56
MM1Z5268B	F6	82	1.5	77.90...86.10	330	2000	0.25	0.1	62

1) V_Z is tested with pulses (20 ms)


2) Nominal Zener voltage is measured with the device junction in thermal equilibrium at T_L=30°C±1°C.

3) Z_{JT} and Z_{JK} are measured by dividing the AC voltage drop across the device by the AC current applied. The specified limits are for I_{Z(AC)}=0.1 I_{Z(DC)} with the AC frequency = 1KHz.



SEMTECH ELECTRONICS LTD.

(Subsidiary of Semtech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002
Certificate No. 05103










ISO 14001
Certificate No. 7116



ISO 9001 : 2000
Certificate No. 050-1009-002-01


Dated : 04/05/2005

MM1Z5221B~MM1Z5268B



SEMTECH ELECTRONICS LTD.

(Subsidiary of Semtech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002
Certificate No. 05103



ISO 14001
Certificate No. 7116



ISO 9001 : 2000
Certificate No. 009-109-002-001

Dated : 04/05/2005

MM1Z5221B~MM1Z5268B




Figure 7. Typical Capacitance




Figure 8. Typical Leakage Current




Figure 9. Zener Voltage versus Zener Current (V_Z Up to 12 V)






Figure 10. Zener Voltage versus Zener Current



SEMTECH ELECTRONICS LTD.

(Subsidiary of Semtech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)





Dated : 04/05/2005

MM1Z5221B~MM1Z5268B

PACKAGE OUTLINE


Plastic surface mounted package; 2 leads

SOD-123



SEMTECH ELECTRONICS LTD.

(Subsidiary of Semtech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002
Certificate No. 05103



ISO 14001
Certificate No. 7116



ISO 9001 : 2000
Certificate No. 555-105-42-24

Dated : 04/05/2005