

PFP65T260/PFF65T260


N-Channel Super Junction MOSFET

FEATURES

- New technology for high voltage device
- Low $R_{DS(on)}$ low conduction losses
- Small package
- Ultra low gate charge cause lower driving requirement
- 100% avalanche tested
- RoHS compliant

APPLICATION

- Power Factor Correction(PFC)
- Switched mode power supply (SMPS)
- Uninterruptible Power Supply (UPS)



Absolute Maximum Ratings $T_c=25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter	PFP65T260	PFF65T260	Units
V_{DS}	Drain-Source Voltage ($V_{GS}=0V$)	650		V
I_D	Drain Current – Continuous ($T_c = 25^\circ\text{C}$)	15	15*	A
	Drain Current – Continuous ($T_c = 100^\circ\text{C}$)	10	10*	A
$I_{DM(pulse)}$	Drain Current – Pulsed * Note 1	60	60*	A
V_{GS}	Gate-Source Voltage ($V_{DS}=0V$)	± 30		V
E_{AS}	Single Pulsed Avalanche Energy * Note 2	304		mJ
I_{AR}	Avalanche Current * Note 1	3		A
E_{AR}	Repetitive Avalanche Energy * Note 1	1.6		mJ
dv/dt	Drain Source Voltage Slope, $V_{DS} \leq 480V$	50		V/ns
	Reverse Diode dv/dt , $V_{DS} \leq 480V$	15		V/ns
P_D	Maximum Power Dissipation ($T_c = 25^\circ\text{C}$)	131	33.2	W
	Derate above 25°C	1.05	0.265	W/ $^\circ\text{C}$
T_J, T_{STG}	Operating and Storage Temperature Range	-55 to +150		$^\circ\text{C}$

* Limited by maximum junction temperature

Thermal Resistance Characteristics

Symbol	Parameter	PFP65T260	PFF65T260	Units
$R_{\theta JC}$	Junction-to-Case (Maximum)	0.95	3.76	$^\circ\text{C}/W$
$R_{\theta JA}$	Junction-to-Ambient (Maximum)	62.5	80	

Package Marking and Ordering Information

Marking	Device	Package	Remark
NCE65T260	PFP65T260	TO-220	RoHS
NCE65T260F	PFF65T260	TO-220F	RoHS

Electrical Characteristics $T_A=25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
--------	-----------	-----------------	-----	-----	-----	-------

On Characteristics

$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = 250 \mu\text{A}$	3.0	3.5	4.0	V
$R_{DS(ON)}$	Static Drain-Source On-Resistance	$V_{GS} = 10 \text{ V}, I_D = 8 \text{ A}$	--	220	260	m.ohm

Off Characteristics

BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS} = 0 \text{ V}, I_D = 250 \mu\text{A}$	650	--	--	V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS} = 650 \text{ V}, V_{GS} = 0 \text{ V}$	--	--	1	μA
		$V_{DS} = 520 \text{ V}, T_C=125^\circ\text{C}$	--	--	100	μA
I_{GSSF}	Gate-Body Leakage Current, Forward	$V_{GS} = 30 \text{ V}, V_{DS} = 0 \text{ V}$	--	--	100	nA
I_{GSSR}	Gate-Body Leakage Current, Reverse	$V_{GS} = -30 \text{ V}, V_{DS} = 0 \text{ V}$	--	--	-100	nA

Dynamic Characteristics

g_{FS}	Forward Transconductance	$V_{DS} = 40\text{V}, I_D = 8 \text{ A}$	--	10	--	S
C_{iss}	Input Capacitance	$V_{DS} = 50 \text{ V}, V_{GS} = 0 \text{ V},$ $f = 1.0 \text{ MHz}$	--	1210	--	pF
C_{oss}	Output Capacitance		--	74	--	pF
C_{rss}	Reverse Transfer Capacitance		--	0.2	--	pF
Q_g	Total Gate Charge		--	24.7	42	nC
Q_{gs}	Gate-Source Charge	$V_{DS} = 480 \text{ V}, I_D = 15 \text{ A},$ $V_{GS} = 10 \text{ V}$	--	8.2	--	nC
Q_{gd}	Gate-Drain Charge		--	8.5	--	nC

Switching Characteristics

$t_{d(on)}$	Turn-On Time	$V_{DS} = 380 \text{ V}, I_D = 8 \text{ A},$ $R_G = 2.3 \Omega, V_{GS} = 10\text{V}$	--	14	--	ns
t_r	Turn-On Rise Time		--	8	--	ns
$t_{d(off)}$	Turn-Off Delay Time		--	55	--	ns
t_f	Turn-Off Fall Time		--	7	--	ns

Source-Drain Diode Maximum Ratings and Characteristics


I_S	Continuous Source-Drain Diode Forward Current		--	--	15	A
I_{SM}	Pulsed Source-Drain Diode Forward Current		--	--	60	
V_{SD}	Source-Drain Diode Forward Voltage	$I_S = 15 \text{ A}, V_{GS} = 0 \text{ V}$	--	0.9	1.3	V
t_{rr}	Reverse Recovery Time	$I_S = 15 \text{ A}$ $di/dt = 100 \text{ A}/\mu\text{s}$	--	240	--	ns
Q_{rr}	Reverse Recovery Charge		--	2.0	--	μC

Notes ;


1. Repetitive Rating : Pulse width limited by maximum junction temperature
2. $V_{DS}=50\text{V}, V_G=10\text{V}, R_G=25\Omega, \text{Starting } T_J=25^\circ\text{C}$

Typical Characteristics


Safe Operation Area_TO-220




Safe Operation Area_TO-220F




Source-Drain Diode Forward Voltage




Output Characteristics








Transfer Characteristics



Static Drain-Source On Resistance




Typical Characteristics (continued)




Typical Characteristics (continued)



Transient Thermal Response Curve_TO-220





Transient Thermal Response Curve





Characteristics Test Circuit & Waveform



Switching Time Test Circuit & Waveforms







Gate Charge Test Circuit & Waveform



Unclamped Inductive Switching Test Circuit & Waveforms

Characteristics Test Circuit & Waveform (continued)



Peak Diode Recovery dv/dt Test Circuit & Waveforms